

Submit 3 Copies To Appropriate District
Office

District I

1625 N French Dr, Hobbs, NM 88240

District II

1301 W Grand Ave, Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St Francis Dr, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103

June 19, 2008

RECEIVED

AUG 24 2009

HOBBSOCD

CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.

30-025-39448

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

VB 1152

7. Lease Name or Unit Agreement Name

Moore Bailout 11 State

8. Well Number # 1H

9. OGRID Number 249099

10. Pool name or Wildcat

Wildcat WOI Camp

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☒

2. Name of Operator

Caza Operating, LLC

3. Address of Operator

200 North Loraine, Suite 1550, Midland, Texas 79701

4. Well Location

Unit Letter A : 660 feet from the NORTH line and 990 feet from the EAST line

Section 11 Township 11 S Range 32 E NMPM LEA County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

4362 GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPL ☐

DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

P AND A ☐

CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

8/9/09- 8/15/09 Drill 12.25" hole from 552 ft to 4748 ft.

8/16/09 Failed to get 9 5/8" casing below 1404 ft. POH L/D 9.625" casing.

8/17/09 Wash and Ream 12.25" hole to 4748 ft.

8/18/09 POH. Run 37 jts 9 5/8" 40 lb L-80 LTC followed by 84 jts 9 5/8" 36 lb K-55 LTC. FC @ 4704. Shoe @ 4748.

8/19/09 Cmt'd Csg w/ 1150 Sks Econo Cmt "C" 11.9 ppg followed by 200 sks C w/ 1% CaCl2 14.8 ppg. Circ 227 Sks. N/U

Well head & BOPE. Tested Hd to 1000 PSI. Test BOPE w/ Rig Pump to 1450 PSI. Tested Casing to 1450 PSI for 30 Minutes. Tested shoe to 11 ppg MWE.

Spud Date:

8/6/2009

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Richard L. Wright

TITLE Operations Manager

DATE 08/21/2009

Type or print name Richard L. Wright

E-mail address: rwright@cazapetro.com

PHONE: 432 682 7424

For State Use Only

APPROVED

BY:

[Signature]

TITLE

PETROLEUM ENGINEER

DATE

AUG 24 2009

Conditions of Approval (if any):