

Submit 3 Copies To Appropriate District
Office

District I

1625 N French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103

June 19, 2008

RECEIVED

APR 27 2009

HOBBSDO

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO 30-005-27983
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No
7. Lease Name or Unit Agreement Name CATO SAN ANDRES UNIT
8. Well Number 535
9. OGRID Number 248802
10. Pool name or Wildcat CATO; SAN ANDRES

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other	
2 Name of Operator CANO PETRO OF NEW MEXICO, INC.	
3. Address of Operator 801 CHERRY STR, UNIT 25 SUITE 3200 FT WORTH TX 76102	
4. Well Location Unit Letter I 2538 feet from the S line and 1296 feet from the E line Section 11 Township 08S Range 30E NMPM 27 County CHAVES	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4171	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS ☒ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103 For Multiple Completions Attach wellbore diagram of proposed completion or recompletion

Work Over:

1-5-08 Rig up Drill 12 1/4" hole to 520' Run 5201 8 5/8 basing. Cement 350 sx cement

1-6-08 WOC 8hrs. Install BOP & Test. Begin Drilling 7 7/8" hole

1-11-08 TD 4020 TOOH to log. Run 104 dts 5.5" csg cement w/700sx cement.

Completion:

1-14-08 Run cased hole logs & perfs. 3498-3538, 3570-3589, 3606-3614, 3646-3680

1-18-08 Acidize w/10,000 gal 15% acid

1-19-08 T.I.H 112 2 7/8 @ 3640'

1-20-08 Install Pumping Unit

Spud Date

1/5/08

Rig Release Date:

1/11/08

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Collin Strawn

TITLE

Engineer

DATE

4-14-09

Type or print name

Collin Strawn

E-mail address:

PHONE:

817-698-0900

For State Use Only

APPROVED BY

[Signature]

TITLE

PETROLEUM ENGINEER

DATE

SEP 09 2009

Conditions of Approval (if any):