

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

RECEIVED

CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

SEP 15 2009

HOBBSOCD

WELL API NO. 30-025-26738
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: Rodman Jones
8. Well Number 6
9. OGRID Number 00778
10. Pool name or Wildcat Jalmat Yates 7 Rivers

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other <input checked="" type="checkbox"/>	2. Name of Operator BP America Production Company
3. Address of Operator P.O. Box 1089 Eunice NM 88231	4. Well Location Unit Letter E : 1980 feet from the N line and 990 feet from the W line Section 35 Township 22S Range 36E NMPM County LEA
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3513.6' GR	
Pit or Below-grade Tank Application <input type="checkbox"/> or Closure <input type="checkbox"/> Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____ Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____	

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

9/8/09: CHECK WELL 20 PSI ON TBG AND 20 PSI ON CSG. BLEED OFF TO HALF PIT. POH W/ 2 3/8" PROD. TBG.
9/9/09: RIH W/ CIBP ON 2 3/8" TBG AND SET SAME @ 3120'. LOAD AND TEST BACKSIDE TO 500PSI. GOOD TEST. TOOK 62BBLs TO LOAD. MIX AND PUMP 300', 30SK PLUG AND SPOT FROM 3120-2820'. DISPLACE DOWN W/ FRESHWATER. POH TO 2750', 18 TOTAL JOINTS. DISPLACE HOLE W/ 9.0 PPG MUD. POH TO 1616'. MIX AND PUMP 50 SK 500' PLUG AND SPOT FROM 1600-1100' DISPLACE DOWN W/ 9.0 PPG MUD. POH TO 800'. WOC FOR MIDDLE PLUG.
Continued on page 2.

Approved for plugging of well bore only.
Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under www.oecd.state.nm.us/oecd.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐ , a general permit ☐ or an (attached) alternative OCD-approved plan ☐

SIGNATURE Barry C. Price TITLE Area Operations Team Lead DATE 9/14/09
E-mail address: barry.price@bp.com
Type or print name Barry C. Price Telephone No. 575-394-1648

For State Use Only

APPROVED BY Tammy M. Hill TITLE PETROLEUM ENGINEER DATE SEP 15 2009
Conditions of Approval, if any:

Form C-103
Rodman Jones #6
30-025-26738
Continued from Page 1

9/10/09: POH W/ 2 3/8" TBG AND LAY DOWN CIBP STINGER.
RIH W/ 2 3/8" TBG TO TAG TOC @ +/- 1100'. TAGGED @ 1098' PIPE
MEASUREMENT. POOH. N/D BOP STACK AND STRIPPER HEAD. MIX AND
PUMP 40SKS OF CEMENT AND SPOT FROM 400' TO SURFACE, GOT
CEMENT RETURNS AND SHUT DOWN PUMP. POH W/ 2 3/8". PUMP TOP
OFF INTO 5 1/2" CSG UNTIL CEMENT RETURNS TO SURFACE. RD PU.

9/14/09: DIG OUT AROUND WELLHEAD. CUT OFF ALL ANCHORS AND
WELL HEAD, WELD IN PLATE, 1" NIPPLE & VALVE, DRY HOLE MARKER,
BACKFILL AND LEVEL LOCATION.