

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis
Santa Fe, NM 87505

AMENDED

RECEIVED
APR 24 2009
HOBBSOCD

WELL API NO. 30-025-04719
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. 31466
7. Lease Name or Unit Agreement Name State C 20
8. Well Number # 2
9. OGRID Number 217817
10. Pool name or Wildcat Johnat, Tansit Yates-7 Rvrs (Gas) <u>Eumont</u>
4. Well Location Unit Letter <u>E</u> : <u>1980</u> feet from the <u>North</u> line and <u>660</u> feet from the <u>West</u> line Section <u>20</u> Township <u>21S</u> Range <u>36E</u> NMPM County <u>Lea</u>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3623 GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: Recompletion

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Workover: 3/26/2008-5/16/2008

MIRU. Kill Well. RIH and tag at 3693' (Existing CIBP@3790). Set composite plug @ 3385'. Test casing up hole and unseat plug. Perforated 3348-71, 3290-3309, and 3255-3262. Acidize well w/4500 gls 15% acid + 49058 gls water + 68636# sand. Flowback. Set composite plug @ 3255'. Perforated 3220-3223, 3158-3180, 3085-3103, and 3056-3070. No stimulation work done. Set composite plug at 3046'. Perforated 3017-3025 and 2905-2925. Acidize w/ 3000 gls 15% acid + 37715 gls water + 48319# sand. Flowback. Set 2 7/8" tubing at 3020.6'. Turned well to production. RDMO.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

Sr. Regulatory Specialist

DATE

4/28/09

Type or print name

Donna Williams

E-mail address:

Donna.J.Williams@

PHONE:

432-688-6943

For State Use Only

APPROVED BY:

TITLE

PETROLEUM ENGINEER

DATE

SEP 22 2009

Conditions of Approval (if any):