

District I

1625 N French Dr., Hobbs, NM 88241

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

RECEIVED
SEP 28 2009
HOBBSOCD

CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.
30-025-39455

5. Indicate Type of Lease
STATE ☐ FEE XX

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
Wynn

8. Well Number 1

9. OGRID Number
010155

10. Pool name or Wildcat
Garrett, Drinkard East

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well XX Gas Well ☐ Other

2. Name of Operator
Harvard Petroleum Company, LLC

3. Address of Operator
PO Box 936, Roswell, NM 88202-10936

4. Well Location

Unit Letter D : 330 feet from the North line and 330 feet from the West line
Section 26 Township 16S Range 38E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3701 GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS.XX P AND A ☐
CASING/CEMENT JOB XX

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Commence drilling a 12.25" hole on August 19, 2009, Drilled to 2147'.

Set 9 5/8" 36# J-55 at 2147'. The casing is equipped with guide shoe, float collar and 10 centralizers spaced approximately 160' apart
Cement 9 5/8" casing with 450 sx 50-50-10C+5%Salt+.125#CFR and 250 sx C+1%CaCl-2. Circulated 198 sx to surface.
Plug down @ 5:35 pm 8/21/09.

Drilled 8 3/4" hole to 8500' and logged hole.

Set 7" 26# J-55 and N-80 casing at TD. Casing configuration from top down: 238' N-80 - 6134' J-55 - 2121' N-80
Cement 7" casing with Lead: 1020 sx 50:50:10P,C,G+5%Salt+2%FL52A+13#/SXCF
Tail: 450 sx 15:61:11P,C,CSE2+5%Salt+3#/SXL1CM1+5%FL25+.25%SMS
Circulated 10 sx cement to surface, Plug down at 12:13 PM 9/6/09

Spud Date: 8/19/09

Rig Release Date: 9/6/09

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE  TITLE Consultant DATE 9/24/09

Type or print name Phelps White E-mail address: pwiv@zianet.com PHONE: 575 626 7660

For State Use Only

APPROVED BY:  TITLE PETROLEUM ENGINEER DATE SEP 28 2009

Conditions of Approval (if any):