Office	State of New Mexico		Form C-103	
District I	Energy, Minerals and Natural Resources		May 27, 2004 WELL API NO.	
1625 N French Dr., Hobbs, NM 88240 District II 1301 W. Grand Ave., Artesia, NM 88210 CONSERVATION DIVISION		30-025-39487		
District III Construct III Con			5. Indicate Type of	
District III 1000 Rio Brazos Rd., Aztec, NM 87410 SEP 2 8 701220 South St. Francis Dr. District IV Santa Fe, NM 87505			STATE X  6. State Oil & Gas	FEE
1220 S. St. Francis Dr., Santa Fe, NMHOBBSOCD				
SUNDRY NOTICES AND REPORTS ON WELLS				Jnit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			Pearsa	all 6 Federal
1. Type of Well: Oil Well X Ga	s Well - Other		8. Well Number	11
Name of Operator     NADEL AND GUSSMAN HEYCO, LLC			9. OGRID Number	258462
3. Address of Operator PO BOX 1936			10. Pool name or Wildcat	
ROSWELL NM 88202-1936			Young N Bone Spring	
4. Well Location	000	-1.t		
	660 feet from the SOUT		990 feet from	
Section 6	Township 18S Ra  1. Elevation (Show whether DR	ange 32E	NMPM	County Lea
		, KK <i>b,</i> K1, GK, <i>eic.)</i> 318' GR		
Pit or Below-grade Tank Application  or Cl	osure 🗌		1 2 5 2 5 2 5 2 5 2 5 2 5 2 5 2 5 2 5 2	A Younger County Tour State Mindle County Co
Pit typeDepth to Groundwater	Distance from nearest fresh w	vater well Dista	nce from nearest surface	e water
Pit Liner Thickness: mil	Below-Grade Tank: Volume	bbls; Co	nstruction Material	
12. Check App	propriate Box to Indicate N	fature of Notice,	Report or Other D	ata
NOTICE OF INTE	NITION TO	l Qup	·	
NOTICE OF INTENTION TO: SUBSEQ PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK			SEQUENT REP	OR LOF: LTERING CASING □
	HANGE PLANS	COMMENCE DRII		
	IULTIPLE COMPL	CASING/CEMENT		7.1.5
OTHER.	-	OTHER OUT	0	F71
OTHER:  13. Describe proposed or complete	d operations (Clearly state all a	OTHER: Surface	Csg and Cmt Report	including estimated data
of starting any proposed work).	SEE RULE 1103. For Multip	le Completions: Att	ach wellbore diagram	of proposed completion
or recompletion.	·	•	S	
8/23/09 - Spud well 9:30 pm.				
8/27/09 - TD 17 1/2" hole at 1055'. Total pipe ran 23 jts of 13 3/8" 54.5# J-55 STC csg ran with 5 centralizers. Set csg at 1055'. Lead 650 sk 65/35 Poz "C" 6% gel,+5% salt, +1/4# CF .25% R-38. Tail: 200 sks Class "C" neat .25%R-38. No problems w/pipe or cmt job. Plug Dn 9 12 am. Circ 113 sks cmt to				
	. Tail: 200 sks Class "C" neat .25%	R-38. No problems w/pi	tralizers. Set csg at 105! pe or cmt job. Plug Dn 9	5'. Lead 650 sk 65/35 Poz 3 12 am. Circ 113 sks cmt to
pit. Ck flow (held).	. Tail: 200 sks Class "C" neat .25%f	R-38. No problems w/pi	tralizers. Set csg at 1059 pe or cmt job. Plug Dn 9	5'. Lead 650 sk 65/35 Poz 9 12 am. Circ 113 sks cmt to
	. Tail: 200 sks Class "C" neat .25%f	R-38. No problems w/pi	tralizers. Set csg at 1059 pe or cmt job. Plug Dn 9	5'. Lead 650 sk 65/35 Poz 9 12 am. Circ 113 sks cmt to
	. Tail: 200 sks Class "C" neat .25%f	R-38. No problems w/pi	tralizers. Set csg at 1059 pe or cmt job. Plug Dn 9	5'. Lead 650 sk 65/35 Poz 9 12 am. Circ 113 sks cmt to
	. Tail: 200 sks Class "C" neat .25%f	R-38. No problems w/pi	tralizers. Set csg at 105: pe or cmt job. Plug Dn 9	5'. Lead 650 sk 65/35 Poz 9 12 am. Circ 113 sks cmt to
	. Tail: 200 sks Class "C" neat .25%f	R-38. No problems w/pi	tralizers. Set csg at 105t	5'. Lead 650 sk 65/35 Poz 9 12 am. Circ 113 sks cmt to
	. Tail: 200 sks Class "C" neat .25%f	R-38. No problems w/pi	tralizers. Set csg at 105t pe or cmt job. Plug Dn 9	5'. Lead 650 sk 65/35 Poz 9 12 am. Circ 113 sks cmt to
	. Tail: 200 sks Class "C" neat .25%f	R-38. No problems w/pi	tralizers. Set csg at 105t	5'. Lead 650 sk 65/35 Poz 9 12 am. Circ 113 sks cmt to
	. Tail: 200 sks Class "C" neat .25%f	R-38. No problems w/pi	tralizers. Set csg at 105t	5'. Lead 650 sk 65/35 Poz 9 12 am. Circ 113 sks cmt to
pit. Ck flow (held).  I hereby certify that the information abo	Tail: 200 sks Class "C" neat .25%f	R-38. No problems w/pi	pe or cmt job. Plug Dn 9	2 12 am. Circ 113 sks cmt to
pit. Ck flow (held).	ve is true and complete to the bed according to NMOCD guidelines	R-38. No problems w/pi	pe or cmt job. Plug Dn 9 and belief. I further or an (attached) alternati	2 12 am. Circ 113 sks cmt to
I hereby certify that the information abo grade tank has been/will be constructed or close  SIGNATURE  Type or print name	ve is true and complete to the bed according to NMOCD guidelines	est of my knowledge  ], a general permit   RODUCTION ANAL	e and belief. I further or an (attached) alternative	ertify that any pit or below-ve OCD-approved plan .
I hereby certify that the information abour grade tank has been/will be constructed or close	ve is true and complete to the bed according to NMOCD guidelines [Figure 1]  E-mail ad	est of my knowledge  ], a general permit   RODUCTION ANAL  idress: tlink@heycoe	e and belief. I further or an (attached) alternatives	certify that any pit or below-ve OCD-approved plan  DATE 9/22/09  phone No. 505.623.6601
I hereby certify that the information about grade tank has been/will be constructed or close SIGNATURE	ve is true and complete to the bed according to NMOCD guidelines [Figure 1]  E-mail ad	est of my knowledge  ], a general permit   RODUCTION ANAL	e and belief. I further or an (attached) alternatives YST Theregy.com	ertify that any pit or below- ve OCD-approved plan  OATE 9/22/09

## SUMMARY CASING AND CEMENTING REPORT

STRING:

SURFACE

DATE: 8/27/2009

**OPERATOR:** 

NADEL & GUSSMAN HEYCO

WELL: Pearsall 6 Federal #11

CONTRACTOR:

**EAGLE ROCK** 

**RIG:** #5

REP: KEITH CANNON

**CASING DETAIL** 

**HOLE SIZE:** 

17 1/2"

DEPTH: 1055'

17 1/2" HOLE FLOAT SHOE 1055.00

TLOAT SHOL

1054.00

1 JTS 13 3/8" 54.5# J55 STC Csg

36.51 1017.49

5 1/2" FLOAT COLLAR

2.00

22 JTS 13 3/8" 54.5# J55 STC Csg

1015.49 1018.78

-3.29

KB TO GL

11.60

CENTRALIZERS PLACED @ 1017.49, 978.95, 942.54, 906.39, 834.06

## **REMARKS**:

TOTAL CASING DELIVERED.... 33 JTS 13 3/8" 54.5# J55 STC (1127.79)
ALL CASING WAS DRIFTED, CLEANED, & VISUALLY INSPECTED ON LOCATION.
FLOAT SHOE, 1 SHOE JTS, FLOAT INSERT, WERE THREAD LOCKED.
TAGGED BOTTOM NO FILL. CIRCULATED CAPACITY & ANNULAR VOLUME
WOC F/5HRS, CUT OFF COND & MADE FINAL CUT. WELD ON 13 3/8" WELL HEAD.

## **EXCESS CASING**

CASING NOT USED .... 2 JTS 13 3/8" 54.5# J55 STC [72.50'].

DISPOSITION .... 2 JTS 13 3/8" 54.5# J55 TRANSFERRED TO NGP YARD (ARTESIA)

**CEMENTING DATA** 

COMPANY: RISING STAR

**DISTRICT: HOBBS** 

**1ST STAGE:** 

PREFLUSH: 20 bbls FW,

LEAD:

650 SKS 65/35 POZ "C" 6%GEL,+5%SALT,+1/4#CF.25%R-38

Page 1 of 2 9/22/2009

## SUMMARY CASING AND CEMENTING REPORT

**TAIL:** 200 SKS CLASS C NEAT .25%R-38.

NO PROBLEMS W/ PIPE OR CMT JOB. PLUG DN 9:12AM. CIRC 113 SKS CMT TO PIT.

NOTE: CK FLOW ( HELD). TALK W/ PATRICIA HUTCHINGS W/ HOBBS BLM. DID NOT

WITENS CMT JOB.

Page 2 of 2 9/22/2009