Office Office	State of N	lew Me	exico		Form C-103
District I	Energy, Minerals an	nd Natu	ral Resources		May 27, 2004
1625 N. French Dr , Hobbs, NM 88240	82,			WELL API NO.	
District II	OIL CONCEDU	A TION	DIMIGION	30-0	025-03521
1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVA			5. Indicate Type of Lease	
District III 1000 Rio Brazos Rd , Aztec, NM 87410	1220 South S	St. Fran	ncis Dr.	STATE 🛛	FEE
District IV	Santa Fe,	NM 87	7505	6. State Oil & Gas	
1220 S. St Francis Dr., Santa Fe, NM 87505	ŕ				B-158
SUNDRY NOTIC	CES AND REPORTS ON	WELLS			Unit Agreement Name:
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A				NM "BZ" State No	
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH				Tivi DZ State IV	C1-3
PROPOSALS.)					
1. Type of Well: Oil Well Gas Well Other			8. Well No. 1		
2. Name of Operator				9. OGRID Number	
State of New Mexico formerly Pronghorn Mgmt					
3. Address of Operator				10. Pool name or Wildcat	
1625 N. French Dr; Hobbs, NM 88240			San Simon; Yates, North Assoc. (53790)		
4. Well Location					
Unit Letter D :	660 feet from the N	orht	line and 66	0 feet from	n the West line
Section 29	Township 21-S		ange 35-E	NMPM	County Lea
	11. Elevation (Show wheth	her DR.	RKB. RT. GR. etc.		
	(,	,,,,		
Pit or Below-grade Tank Applicati	on or Closure				
	vater Distance from	n nearest i	fresh water well	Distance from neare	est surface water
Pit Liner Thickness: m				bls; Construction Materia	
12. Check Ap	opropriate Box to India	cate Na	iture of Notice,	Report or Other D	Pata
NOTICE OF IN	TENTION TO:		CLID	CECHENT DEC	ODT OF
		_		SEQUENT REP	
		_	REMEDIAL WORL		LTERING CASING
		\exists	COMMENCE DRI		AND A
FULL OR ALTER CASING 11	MULTIPLE [CASING/CEMENT	JOB 🗆	
	COMPLETION				
	COMPLETION				
OTHER:	_	¬	OTHER:		П
OTHER:	[all monti	OTHER:		
OTHER: 13. Describe proposed or completed	operations. (Clearly state	all perti	nent details, and gi	ve pertinent dates, inc	cluding estimated date of
OTHER: 13. Describe proposed or completed starting any proposed work). SE	operations. (Clearly state	all perti	nent details, and gi	ve pertinent dates, increallbore diagram of pr	cluding estimated date of roposed completion or
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion.	operations. (Clearly state	all perti	nent details, and gi	ve pertinent dates, inc ellbore diagram of pr	cluding estimated date of roposed completion or
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU	operations. (Clearly state EE RULE 1103. For Multi	all perti ple Com	nent details, and gi pletions: Attach w	rellbore diagram of pr	roposed completion or
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU 10/06/09 POH and lay down rods a	[operations. (Clearly state EE RULE 1103. For Multip and pump. dug out cellar.	all perti ple Com	nent details, and gi pletions: Attach w	ellbore diagram of pr aden head valves. NI	oposed completion or D well head. NU BOP.
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU 10/06/09 POH and lay down rods a POH w/ 123 jts. tbg. SN, perferated	operations. (Clearly state EE RULE 1103. For Multipand pump. dug out cellar d sub, and MA. RIH w/3	all perti ple Com , change 1/2 swe	nent details, and gi pletions: Attach w ed out csg. and bra dge on wireline to	ellbore diagram of pr aden head valves. NI 2768'. RIH w/ tbg.	oposed completion or D well head. NU BOP.
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU 10/06/09 POH and lay down rods a POH w/ 123 jts. tbg. SN, perferated bag of magna fiber. Pulled tbg to 3	operations. (Clearly state EE RULE 1103. For Multipand pump. dug out cellar d sub, and MA. RIH w/3	all perti ple Com , change 1/2 swe	nent details, and gi pletions: Attach w ed out csg. and bra dge on wireline to	ellbore diagram of pr aden head valves. NI 2768'. RIH w/ tbg.	oposed completion or D well head. NU BOP.
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU 10/06/09 POH and lay down rods a POH w/ 123 jts. tbg. SN, perferate bag of magna fiber. Pulled tbg to 3 SDFN.	operations. (Clearly state EE RULE 1103. For Multiple and pump. dug out cellar d sub, and MA. RIH w/ 3 685'. Spot 25 sx class C co	all perti ple Com , change 1/2 swe ement. (nent details, and gipletions: Attach we do ut csg. and bradge on wireline to (3685-3324). POH	rellbore diagram of produce den head valves. NI 2768'. RIH w/ tbg.	oposed completion or D well head. NU BOP. to 3748'. Pumped 1/2
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU 10/06/09 POH and lay down rods a POH w/ 123 jts. tbg. SN, perferate bag of magna fiber. Pulled tbg to 3 SDFN. 10/07/09 Tagged plug @ 3559'. Cir	operations. (Clearly state EE RULE 1103. For Multiple and pump. dug out cellar d sub, and MA. RIH w/ 3 685'. Spot 25 sx class C co culated hole w/ mud laide	all pertiple Com , change 1/2 sweement. (nent details, and gipletions: Attach wed out csg. and bradge on wireline to (3685-3324). POH	rellbore diagram of produce den head valves. NI 2768'. RIH w/tbg. w/2000' tbg.	oposed completion or D well head. NU BOP. to 3748'. Pumped 1/2
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU 10/06/09 POH and lay down rods a POH w/ 123 jts. tbg. SN, perferated bag of magna fiber. Pulled tbg to 3 SDFN. 10/07/09 Tagged plug @ 3559'. Cir WOC 4 hrs. Tagged plug @ 3357'.	operations. (Clearly state EE RULE 1103. For Multipland pump. dug out cellar d sub, and MA. RIH w/3 685'. Spot 25 sx class C co culated hole w/ mud laide RIH w/ tbg to 1921'. Sp	all pertiple Com , change 1/2 sweement. (en fluid.ot 25 sx	nent details, and gipletions: Attach weed out csg. and bradge on wireline to (3685-3324). POH	rellbore diagram of produce dead valves. NI 2768'. RIH w/ tbg. w/ 2000' tbg.	roposed completion or D well head. NU BOP. to 3748'. Pumped 1/2 97. POH w. 2000' tbg. / tbg. WOC 4 hrs.
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU 10/06/09 POH and lay down rods a POH w/ 123 jts. tbg. SN, perferated bag of magna fiber. Pulled tbg to 3 SDFN. 10/07/09 Tagged plug @ 3559'. Cir WOC 4 hrs. Tagged plug @ 3357'. Tagged plug @ 1602'. Perf'd casing	operations. (Clearly state EE RULE 1103. For Multipland pump. dug out cellar d sub, and MA. RIH w/3 685'. Spot 25 sx class C co culated hole w/ mud laide RIH w/ tbg to 1921'. Sp	all pertiple Com , change 1/2 sweement. (en fluid.ot 25 sx	nent details, and gipletions: Attach weed out csg. and bradge on wireline to (3685-3324). POH	rellbore diagram of produce dead valves. NI 2768'. RIH w/ tbg. w/ 2000' tbg.	roposed completion or D well head. NU BOP. to 3748'. Pumped 1/2 97. POH w. 2000' tbg. / tbg. WOC 4 hrs.
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU 10/06/09 POH and lay down rods a POH w/ 123 jts. tbg. SN, perferate bag of magna fiber. Pulled tbg to 3 SDFN. 10/07/09 Tagged plug @ 3559'. Cir WOC 4 hrs. Tagged plug @ 3357'. Tagged plug @ 1602'. Perf'd casing SDFN	operations. (Clearly state EE RULE 1103. For Multipland pump. dug out cellar. d sub, and MA. RIH w/ 3 685'. Spot 25 sx class C co culated hole w/ mud laide RIH w/ tbg to 1921'. Sp g @ 225'. Set 4 1/2 packer	all pertiple Com , change 1/2 sweement. (en fluid. ot 25 sxr @ 34'.	nent details, and gipletions: Attach we do ut csg. and bradge on wireline to (3685-3324). POH Spot 25 sx class C Class C cement. (Sqz'd 25 sx class	rellbore diagram of produce head valves. NI 2768'. RIH w/ tbg. w/ 2000' tbg. C cement @ 3559-319 (1921-1559). POH w/ C cement. Displaced	roposed completion or D well head. NU BOP. to 3748'. Pumped 1/2 97. POH w. 2000' tbg. / tbg. WOC 4 hrs. I to 175'. Closed well in,
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU 10/06/09 POH and lay down rods a POH w/ 123 jts. tbg. SN, perferated bag of magna fiber. Pulled tbg to 3 SDFN. 10/07/09 Tagged plug @ 3559'. Cir WOC 4 hrs. Tagged plug @ 3357'. Tagged plug @ 1602'. Perf'd casing SDFN 10/08/09 Released packer. Tagged	operations. (Clearly state EE RULE 1103. For Multiple and pump. dug out cellar d sub, and MA. RIH w/ 3 685'. Spot 25 sx class C collated hole w/ mud laide RIH w/ tbg to 1921'. Spot 26 @ 225'. Set 4 1/2 packer plug @ 167'. Spot 10 sx collated manual state of the sta	all pertiple Com , change 1/2 sweement. (en fluid. ot 25 sx r @ 34'.	nent details, and gipletions: Attach we do ut csg. and bradge on wireline to (3685-3324). POH Spot 25 sx class C Class C cement. (Sqz'd 25 sx class dement @ 60 to su	rellbore diagram of produce head valves. NI 2768'. RIH w/ tbg. w/ 2000' tbg. C cement @ 3559-319 (1921-1559). POH w/C cement. Displaced rface. Rigged down of	roposed completion or D well head. NU BOP. to 3748'. Pumped 1/2 97. POH w. 2000' tbg. / tbg. WOC 4 hrs. to 175'. Closed well in, cleaned loc.
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU 10/06/09 POH and lay down rods a POH w/ 123 jts. tbg. SN, perferate bag of magna fiber. Pulled tbg to 3 SDFN. 10/07/09 Tagged plug @ 3559'. Cir WOC 4 hrs. Tagged plug @ 3357'. Tagged plug @ 1602'. Perf'd casing SDFN 10/08/09 Released packer. Tagged 10/10/09 Road welder and backhool	operations. (Clearly state EE RULE 1103. For Multiple and pump. dug out cellar d sub, and MA. RIH w/ 3 685'. Spot 25 sx class C collated hole w/ mud laide RIH w/ tbg to 1921'. Spot 26 @ 225'. Set 4 1/2 packer plug @ 167'. Spot 10 sx collated manual state of the sta	all pertiple Com , change 1/2 sweement. (en fluid. ot 25 sx r @ 34'.	nent details, and gipletions: Attach we do ut csg. and bradge on wireline to (3685-3324). POH Spot 25 sx class C Class C cement. (Sqz'd 25 sx class dement @ 60 to su	rellbore diagram of produce head valves. NI 2768'. RIH w/ tbg. w/ 2000' tbg. C cement @ 3559-319 (1921-1559). POH w/C cement. Displaced rface. Rigged down of	roposed completion or D well head. NU BOP. to 3748'. Pumped 1/2 97. POH w. 2000' tbg. / tbg. WOC 4 hrs. to 175'. Closed well in, cleaned loc.
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU 10/06/09 POH and lay down rods a POH w/ 123 jts. tbg. SN, perferated bag of magna fiber. Pulled tbg to 3 SDFN. 10/07/09 Tagged plug @ 3559'. Cir WOC 4 hrs. Tagged plug @ 3357'. Tagged plug @ 1602'. Perf'd casing SDFN 10/08/09 Released packer. Tagged	operations. (Clearly state EE RULE 1103. For Multiple and pump. dug out cellar d sub, and MA. RIH w/ 3 685'. Spot 25 sx class C collated hole w/ mud laide RIH w/ tbg to 1921'. Spot 26 @ 225'. Set 4 1/2 packer plug @ 167'. Spot 10 sx collated manual state of the sta	all pertiple Com , change 1/2 sweement. (en fluid. ot 25 sx r @ 34'.	nent details, and gipletions: Attach we do ut csg. and bradge on wireline to (3685-3324). POH Spot 25 sx class C Class C cement. (Sqz'd 25 sx class dement @ 60 to suell head. Weld on	rellbore diagram of produce den head valves. NI 2768'. RIH w/tbg. w/2000' tbg. Cement @ 3559-319(1921-1559). POH w/C cement. Displaced rface. Rigged down of Dry Hole Marker. B	roposed completion or D well head. NU BOP. to 3748'. Pumped 1/2 97. POH w. 2000' tbg. / tbg. WOC 4 hrs. to 175'. Closed well in, cleaned loc.
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU 10/06/09 POH and lay down rods a POH w/ 123 jts. tbg. SN, perferate bag of magna fiber. Pulled tbg to 3 SDFN. 10/07/09 Tagged plug @ 3559'. Cir WOC 4 hrs. Tagged plug @ 3357'. Tagged plug @ 1602'. Perf'd casing SDFN 10/08/09 Released packer. Tagged 10/10/09 Road welder and backhool	operations. (Clearly state EE RULE 1103. For Multiple and pump. dug out cellar d sub, and MA. RIH w/ 3 685'. Spot 25 sx class C collated hole w/ mud laide RIH w/ tbg to 1921'. Spot 26 @ 225'. Set 4 1/2 packer plug @ 167'. Spot 10 sx collated manual state of the sta	all pertiple Com , change 1/2 sweement. (en fluid. ot 25 sx r @ 34'.	ed out csg. and bradge on wireline to (3685-3324). POH Spot 25 sx class (Class C cement. (Sqz'd 25 sx class) ement @ 60 to su cell head. Weld on	rellbore diagram of product den head valves. NI 2768'. RIH w/ tbg. w/ 2000' tbg. Cement @ 3559-319(1921-1559). POH w/C cement. Displaced rface. Rigged down of the diagram of well bore only.	oposed completion or D well head. NU BOP. to 3748'. Pumped 1/2 97. POH w. 2000' tbg. / tbg. WOC 4 hrs. I to 175'. Closed well in, cleaned loc. eack fill cellar. Dug out
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU 10/06/09 POH and lay down rods a POH w/ 123 jts. tbg. SN, perferate bag of magna fiber. Pulled tbg to 3 SDFN. 10/07/09 Tagged plug @ 3559'. Cir WOC 4 hrs. Tagged plug @ 3357'. Tagged plug @ 1602'. Perf'd casing SDFN 10/08/09 Released packer. Tagged 10/10/09 Road welder and backhool	operations. (Clearly state EE RULE 1103. For Multiple and pump. dug out cellar d sub, and MA. RIH w/ 3 685'. Spot 25 sx class C collated hole w/ mud laide RIH w/ tbg to 1921'. Spot 26 @ 225'. Set 4 1/2 packer plug @ 167'. Spot 10 sx collated manual state of the sta	all pertiple Com , change 1/2 sweement. (en fluid. ot 25 sx r @ 34'.	ed out csg. and bradge on wireline to (3685-3324). POH Spot 25 sx class (Class C cement. (Sqz'd 25 sx class) ement @ 60 to su cell head. Weld on	aden head valves. NI 2768'. RIH w/ tbg. w/ 2000' tbg. C cement @ 3559-319 (1921-1559). POH w/ C cement. Displaced rface. Rigged down of Dry Hole Marker. Bugging of well bore only.	roposed completion or D well head. NU BOP. to 3748'. Pumped 1/2 97. POH w. 2000' tbg. / tbg. WOC 4 hrs. I to 175'. Closed well in, cleaned loc. sack fill cellar. Dug out
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU 10/06/09 POH and lay down rods a POH w/ 123 jts. tbg. SN, perferate bag of magna fiber. Pulled tbg to 3 SDFN. 10/07/09 Tagged plug @ 3559'. Cir WOC 4 hrs. Tagged plug @ 3357'. Tagged plug @ 1602'. Perf'd casing SDFN 10/08/09 Released packer. Tagged 10/10/09 Road welder and backhool	operations. (Clearly state EE RULE 1103. For Multiple and pump. dug out cellar d sub, and MA. RIH w/ 3 685'. Spot 25 sx class C collated hole w/ mud laide RIH w/ tbg to 1921'. Spot 26 @ 225'. Set 4 1/2 packer plug @ 167'. Spot 10 sx collated manual state of the sta	all pertiple Com , change 1/2 sweement. (en fluid. ot 25 sx r @ 34'.	nent details, and gipletions: Attach we do ut csg. and bradge on wireline to (3685-3324). POH Spot 25 sx class (Class C cement. (Sqz'd 25 sx class dement @ 60 to sue lell head. Weld on Approved for pl Liability under to f C-103 (Subse which may be fo	aden head valves. NI 2768'. RIH w/ tbg. w/ 2000' tbg. cement @ 3559-319 1921-1559). POH w/ C cement. Displaced rface. Rigged down of Dry Hole Marker. B ugging of well bore only. cound is retained pending requent Report of Well Pluggund at OCD Web Page und	roposed completion or D well head. NU BOP. to 3748'. Pumped 1/2 97. POH w. 2000' tbg. / tbg. WOC 4 hrs. I to 175'. Closed well in, cleaned loc. sack fill cellar. Dug out
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU 10/06/09 POH and lay down rods a POH w/ 123 jts. tbg. SN, perferated bag of magna fiber. Pulled tbg to 3 SDFN. 10/07/09 Tagged plug @ 3559'. Cir WOC 4 hrs. Tagged plug @ 3357'. Tagged plug @ 1602'. Perf'd casing SDFN 10/08/09 Released packer. Tagged 10/10/09 Road welder and backhoo anchors. clean loc. move off.	operations. (Clearly state EE RULE 1103. For Multiple and pump. dug out cellar d sub, and MA. RIH w/3 685'. Spot 25 sx class C coulated hole w/ mud laide RIH w/ tbg to 1921'. Spg @ 225'. Set 4 1/2 packer plug @ 167'. Spot 10 sx ce to loc. Dug out cellar, cu	all pertiple Com , change 1/2 sweement. (en fluid. tot 25 sx r @ 34'. class C cut off we	ed out csg. and bradge on wireline to (3685-3324). POH Spot 25 sx class (Class C cement. (Sqz'd 25 sx class) ement @ 60 to su cell head. Weld on Approved for pl Linbility under to f C-103 (Subsewhich may be fo Forms, www.emi	aden head valves. NI 2768'. RIH w/ tbg. w/ 2000' tbg. Cement @ 3559-319 (1921-1559). POH w/ C cement. Displaced rface. Rigged down of Dry Hole Marker. Bugging of well bore only. Coond is retained pending requent Report of Well Pluggund at OCD Web Page und at OCD Web	roposed completion or D well head. NU BOP. to 3748'. Pumped 1/2 97. POH w. 2000' tbg. / tbg. WOC 4 hrs. l to 175'. Closed well in, cleaned loc. eack fill cellar. Dug out
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU 10/06/09 POH and lay down rods a POH w/ 123 jts. tbg. SN, perferated bag of magna fiber. Pulled tbg to 3 SDFN. 10/07/09 Tagged plug @ 3559'. Cir WOC 4 hrs. Tagged plug @ 3357'. Tagged plug @ 1602'. Perf'd casing SDFN 10/08/09 Released packer. Tagged 10/10/09 Road welder and backhood anchors. clean loc. move off.	operations. (Clearly state EE RULE 1103. For Multiple and pump. dug out cellar d sub, and MA. RIH w/3 685'. Spot 25 sx class C collated hole w/ mud laide RIH w/ tbg to 1921'. Spg @ 225'. Set 4 1/2 packer plug @ 167'. Spot 10 sx ce to loc. Dug out cellar, cut e is true and complete to the best endocations.	all pertiple Com 7, change 1/2 sweement. (en fluid. ot 25 sx r @ 34'. class C cut off we	ed out csg. and bradge on wireline to (3685-3324). POH Spot 25 sx class (Class C cement. (Sqz'd 25 sx class) ement @ 60 to su cell head. Weld on Approved for pl Liability under to f C-103 (Subse which may be fo Forms, www.emi y knowledge and beli	aden head valves. NI 2768'. RIH w/ tbg. w/ 2000' tbg. cement @ 3559-319 1921-1559). POH w/ Cement. Displaced rface. Rigged down of Dry Hole Marker. B ugging of well bore only. cond is retained pending requent Report of Well Pluggund at OCD Web Page und at distate.nm.us/ocd. ef. I further certify that	roposed completion or D well head. NU BOP. to 3748'. Pumped 1/2 97. POH w. 2000' tbg. / tbg. WOC 4 hrs. I to 175'. Closed well in, cleaned loc. cack fill cellar. Dug out
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU 10/06/09 POH and lay down rods a POH w/ 123 jts. tbg. SN, perferated bag of magna fiber. Pulled tbg to 3 SDFN. 10/07/09 Tagged plug @ 3559'. Cir WOC 4 hrs. Tagged plug @ 3357'. Tagged plug @ 1602'. Perf'd casing SDFN 10/08/09 Released packer. Tagged 10/10/09 Road welder and backhoo anchors. clean loc. move off.	operations. (Clearly state EE RULE 1103. For Multiple and pump. dug out cellar d sub, and MA. RIH w/3 685'. Spot 25 sx class C collated hole w/ mud laide RIH w/ tbg to 1921'. Spg @ 225'. Set 4 1/2 packer plug @ 167'. Spot 10 sx ce to loc. Dug out cellar, cut e is true and complete to the best endocations.	all pertiple Com 7, change 1/2 sweement. (en fluid. ot 25 sx r @ 34'. class C cut off we	ed out csg. and bradge on wireline to (3685-3324). POH Spot 25 sx class (Class C cement. (Sqz'd 25 sx class) ement @ 60 to su cell head. Weld on Approved for pl Liability under to f C-103 (Subse which may be fo Forms, www.emi y knowledge and beli	aden head valves. NI 2768'. RIH w/ tbg. w/ 2000' tbg. cement @ 3559-319 1921-1559). POH w/ Cement. Displaced rface. Rigged down of Dry Hole Marker. B ugging of well bore only. cond is retained pending requent Report of Well Pluggund at OCD Web Page und at distate.nm.us/ocd. ef. I further certify that	roposed completion or D well head. NU BOP. to 3748'. Pumped 1/2 97. POH w. 2000' tbg. / tbg. WOC 4 hrs. I to 175'. Closed well in, cleaned loc. cack fill cellar. Dug out
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU 10/06/09 POH and lay down rods a POH w/ 123 jts. tbg. SN, perferated bag of magna fiber. Pulled tbg to 3 SDFN. 10/07/09 Tagged plug @ 3559'. Cir WOC 4 hrs. Tagged plug @ 3357'. Tagged plug @ 1602'. Perf'd casing SDFN 10/08/09 Released packer. Tagged 10/10/09 Road welder and backhood anchors. clean loc. move off.	operations. (Clearly state EE RULE 1103. For Multiple and pump. dug out cellar d sub, and MA. RIH w/3 685'. Spot 25 sx class C collated hole w/ mud laide RIH w/ tbg to 1921'. Spg @ 225'. Set 4 1/2 packer plug @ 167'. Spot 10 sx ce to loc. Dug out cellar, cut e is true and complete to the best endocations.	all pertiple Com 7, change 1/2 sweement. (en fluid. ot 25 sx r @ 34'. class C cut off we	ed out csg. and bradge on wireline to (3685-3324). POH Spot 25 sx class (Class C cement. (Sqz'd 25 sx class) ement @ 60 to su cell head. Weld on Approved for pl Liability under to f C-103 (Subse which may be fo Forms, www.emi y knowledge and beli	aden head valves. NI 2768'. RIH w/ tbg. w/ 2000' tbg. Cement @ 3559-319 1921-1559). POH w/C cement. Displaced rface. Rigged down of Dry Hole Marker. Bugging of well bore only. Cond is retained pending requent Report of Well Pluggund at OCD Web Page und at OCD Web Pa	roposed completion or D well head. NU BOP. to 3748'. Pumped 1/2 97. POH w. 2000' tbg. / tbg. WOC 4 hrs. I to 175'. Closed well in, cleaned loc. Back fill cellar. Dug out eccipt ging) der any pit or below-grade tank to OCD-approved plan
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU 10/06/09 POH and lay down rods a POH w/ 123 jts. tbg. SN, perferated bag of magna fiber. Pulled tbg to 3 SDFN. 10/07/09 Tagged plug @ 3559'. Cir WOC 4 hrs. Tagged plug @ 3357'. Tagged plug @ 1602'. Perf'd casing SDFN 10/08/09 Released packer. Tagged 10/10/09 Road welder and backhood anchors. clean loc. move off.	operations. (Clearly state EE RULE 1103. For Multiple and pump. dug out cellar d sub, and MA. RIH w/3 685'. Spot 25 sx class C collated hole w/ mud laide RIH w/ tbg to 1921'. Spg @ 225'. Set 4 1/2 packer plug @ 167'. Spot 10 sx ce to loc. Dug out cellar, cut e is true and complete to the best endocations.	all pertiple Com 7, change 1/2 sweement. (en fluid. ot 25 sx r @ 34'. class C cut off we	ed out csg. and bradge on wireline to (3685-3324). POH Spot 25 sx class (Class C cement. (Sqz'd 25 sx class) ement @ 60 to su cell head. Weld on Approved for pl Liability under to f C-103 (Subse which may be fo Forms, www.emi y knowledge and beli	aden head valves. NI 2768'. RIH w/ tbg. w/ 2000' tbg. Cement @ 3559-319 1921-1559). POH w/C cement. Displaced rface. Rigged down of Dry Hole Marker. Bugging of well bore only. Cond is retained pending requent Report of Well Pluggund at OCD Web Page und at OCD Web Pa	roposed completion or D well head. NU BOP. to 3748'. Pumped 1/2 97. POH w. 2000' tbg. / tbg. WOC 4 hrs. I to 175'. Closed well in, cleaned loc. cack fill cellar. Dug out
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU 10/06/09 POH and lay down rods a POH w/ 123 jts. tbg. SN, perferated bag of magna fiber. Pulled tbg to 3 SDFN. 10/07/09 Tagged plug @ 3559'. Cir WOC 4 hrs. Tagged plug @ 3357'. Tagged plug @ 1602'. Perf'd casing SDFN 10/08/09 Released packer. Tagged 10/10/09 Road welder and backhool anchors. clean loc. move off.	operations. (Clearly state EE RULE 1103. For Multiple and pump. dug out cellar d sub, and MA. RIH w/3 685'. Spot 25 sx class C collated hole w/ mud laide RIH w/ tbg to 1921'. Spg @ 225'. Set 4 1/2 packer plug @ 167'. Spot 10 sx ce to loc. Dug out cellar, cut e is true and complete to the best endocations.	all pertiple Com 7, change 1/2 sweement. (en fluid. ot 25 sx r @ 34'. class C cut off we	ed out csg. and bradge on wireline to (3685-3324). POH Spot 25 sx class (Class C cement. (Sqz'd 25 sx class) ement @ 60 to su cell head. Weld on Approved for pl Liability under to f C-103 (Subse which may be fo Forms, www.emi y knowledge and beli	aden head valves. NI 2768'. RIH w/ tbg. w/ 2000' tbg. Cement @ 3559-319 1921-1559). POH w/C cement. Displaced rface. Rigged down of Dry Hole Marker. Bugging of well bore only. Cond is retained pending requent Report of Well Pluggund at OCD Web Page und at OCD Web Pa	roposed completion or D well head. NU BOP. to 3748'. Pumped 1/2 97. POH w. 2000' tbg. / tbg. WOC 4 hrs. I to 175'. Closed well in, cleaned loc. Back fill cellar. Dug out eccipt ging) der any pit or below-grade tank to OCD-approved plan
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU 10/06/09 POH and lay down rods a POH w/ 123 jts. tbg. SN, perferated bag of magna fiber. Pulled tbg to 3 SDFN. 10/07/09 Tagged plug @ 3559'. Cir WOC 4 hrs. Tagged plug @ 3357'. Tagged plug @ 1602'. Perf'd casing SDFN 10/08/09 Released packer. Tagged 10/10/09 Road welder and backhool anchors. clean loc. move off. I hereby certify that the information above has been/will be constructed or closed and SIGNATURE	operations. (Clearly state EE RULE 1103. For Multiple and pump. dug out cellar disub, and MA. RIH w/3 685'. Spot 25 sx class C coulated hole w/ mud laide RIH w/ tbg to 1921'. Spog @ 225'. Set 4 1/2 packer plug @ 167'. Spot 10 sx control of the coording to NMOCD guideline w/ Times and complete to the boording to NMOCD guideline	all pertiple Com , change 1/2 sweement. (en fluid. ot 25 sx r @ 34'. class C cut off we	ed out csg. and bradge on wireline to (3685-3324). POH Spot 25 sx class (Class C cement. (Sqz'd 25 sx class) ement @ 60 to su cell head. Weld on Approved for pl Liability under to f C-103 (Subse which may be for Forms, www.emicy knowledge and belieneral permit or constant of the co	aden head valves. NI 2768'. RIH w/ tbg. w/ 2000' tbg. Cement @ 3559-319 1921-1559). POH w/C cement. Displaced rface. Rigged down of Dry Hole Marker. Bugging of well bore only. Cond is retained pending requent Report of Well Pluggund at OCD Web Page und at OCD Web Pa	Proposed completion or D well head. NU BOP. to 3748'. Pumped 1/2 97. POH w. 2000' tbg. / tbg. WOC 4 hrs. I to 175'. Closed well in, cleaned loc. back fill cellar. Dug out ging) der any pit or below-grade tank to OCD-approved plan DATE 10/14/2009
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU 10/06/09 POH and lay down rods a POH w/ 123 jts. tbg. SN, perferated bag of magna fiber. Pulled tbg to 3 SDFN. 10/07/09 Tagged plug @ 3559'. Cir WOC 4 hrs. Tagged plug @ 3357'. Tagged plug @ 1602'. Perf'd casing SDFN 10/08/09 Released packer. Tagged 10/10/09 Road welder and backhool anchors. clean loc. move off.	operations. (Clearly state EE RULE 1103. For Multiple and pump. dug out cellar disub, and MA. RIH w/3 685'. Spot 25 sx class C coulated hole w/ mud laide RIH w/ tbg to 1921'. Spog @ 225'. Set 4 1/2 packer plug @ 167'. Spot 10 sx control of the coording to NMOCD guideline w/ Times and complete to the boording to NMOCD guideline	all pertiple Com 7, change 1/2 sweenent. (en fluid. ot 25 sx r @ 34'. class C cout off we	ed out csg. and bradge on wireline to (3685-3324). POH Spot 25 sx class (Class C cement. (Sqz'd 25 sx class) ement @ 60 to su cell head. Weld on Approved for pl Liability under the of C-103 (Subsequick Mich may be for Forms, www.emity knowledge and believed to the control of the control	aden head valves. NI 2768'. RIH w/ tbg. w/ 2000' tbg. Cement @ 3559-319 (1921-1559). POH w/ C cement. Displaced rface. Rigged down of Dry Hole Marker. Bugging of well bore only. Cond is retained pending requent Report of Well Plugging at Well Plugging at COD Web Page und at OCD Web Page und attached) alternative Company (attached) alterna	Proposed completion or D well head. NU BOP. to 3748'. Pumped 1/2 97. POH w. 2000' tbg. / tbg. WOC 4 hrs. I to 175'. Closed well in, cleaned loc. back fill cellar. Dug out ging) der any pit or below-grade tank to OCD-approved plan DATE 10/14/2009
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU 10/06/09 POH and lay down rods a POH w/ 123 jts. tbg. SN, perferated bag of magna fiber. Pulled tbg to 3 SDFN. 10/07/09 Tagged plug @ 3559'. Cir WOC 4 hrs. Tagged plug @ 3357'. Tagged plug @ 1602'. Perf'd casing SDFN 10/08/09 Released packer. Tagged 10/10/09 Road welder and backhoo anchors. clean loc. move off. I hereby certify that the information above has been/will be constructed or closed as SIGNATURE Type or print name For State Use Only	operations. (Clearly state EE RULE 1103. For Multiple and pump. dug out cellar d sub, and MA. RIH w/3 685'. Spot 25 sx class C coulated hole w/ mud laide RIH w/ tbg to 1921'. Spog @ 225'. Set 4 1/2 packer plug @ 167'. Spot 10 sx control of the cording to NMOCD guideline The E-ma	all pertiple Comple Com	ed out csg. and bradge on wireline to (3685-3324). POH Spot 25 sx class (Class C cement. (Sqz'd 25 sx class) ement @ 60 to su cell head. Weld on Approved for pl Liability under the of C-103 (Subsequick Mich may be for Forms, www.emity knowledge and believed to the control of the control	aden head valves. NI 2768'. RIH w/ tbg. w/ 2000' tbg. Cement @ 3559-319 (1921-1559). POH w/ C cement. Displaced rface. Rigged down of Dry Hole Marker. Bugging of well bore only. Cond is retained pending requent Report of Well Plugging at Well Plugging at COD Web Page und at OCD Web Page und attached) alternative Company (attached) alterna	proposed completion or D well head. NU BOP. to 3748'. Pumped 1/2 97. POH w. 2000' tbg. / tbg. WOC 4 hrs. I to 175'. Closed well in, cleaned loc. ack fill cellar. Dug out eccipt ging) der any pit or below-grade tank OCD-approved plan DATE 10/14/2009 ne No.
OTHER: 13. Describe proposed or completed starting any proposed work). SE recompletion. 10/05/09 MIRU 10/06/09 POH and lay down rods a POH w/ 123 jts. tbg. SN, perferated bag of magna fiber. Pulled tbg to 3 SDFN. 10/07/09 Tagged plug @ 3559'. Cir WOC 4 hrs. Tagged plug @ 3357'. Tagged plug @ 1602'. Perf'd casing SDFN 10/08/09 Released packer. Tagged 10/10/09 Road welder and backhool anchors. clean loc. move off. I hereby certify that the information above has been/will be constructed or closed and SIGNATURE	operations. (Clearly state EE RULE 1103. For Multiple and pump. dug out cellar d sub, and MA. RIH w/3 685'. Spot 25 sx class C coulated hole w/ mud laide RIH w/ tbg to 1921'. Spog @ 225'. Set 4 1/2 packer plug @ 167'. Spot 10 sx control of the cording to NMOCD guideline The E-ma	all pertiple Com 7, change 1/2 sweenent. (en fluid. ot 25 sx r @ 34'. class C cout off we	ed out csg. and bradge on wireline to (3685-3324). POH Spot 25 sx class (Class C cement. (Sqz'd 25 sx class) ement @ 60 to su cell head. Weld on Approved for pl Liability under to f C-103 (Subse which may be for Forms, www.emicy knowledge and belieneral permit or constant of the co	aden head valves. NI 2768'. RIH w/ tbg. w/ 2000' tbg. cement @ 3559-319 1921-1559). POH w/ C cement. Displaced rface. Rigged down of Dry Hole Marker. B ugging of well bore only. cond is retained pending requent Report of Well Plugg und at OCD Web Page und at OCD Web Page und ef. I further certify that an (attached) alternative	Proposed completion or D well head. NU BOP. to 3748'. Pumped 1/2 97. POH w. 2000' tbg. / tbg. WOC 4 hrs. I to 175'. Closed well in, cleaned loc. back fill cellar. Dug out ging) der any pit or below-grade tank to OCD-approved plan DATE 10/14/2009