

Submit 3 Copies To Appropriate District

Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505

State of New Mexico

Energy, Minerals and Natural Resources

Form C-103

June 19, 2008

RECEIVED

OCT 23 2009

HOBBSOCD

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.

30-025-39448

5. Indicate Type of Lease

STATE ☒FEE ☐

6. State Oil &amp; Gas Lease No.

VB 1152

7. Lease Name or Unit Agreement Name

Moore Bailout 11 State

8. Well Number # 1H

9. OGRID Number 249099

10. Pool name or Wildcat

Wildcat, Wolfcamp

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☒

2. Name of Operator

Caza Operating, LLC

3. Address of Operator

200 North Loraine, Suite 1550, Midland, Texas 79701

4. Well Location

Unit Letter A : 660 feet from the NORTH line and 990 feet from the EAST lineSection 11 Township 11 S Range 32 E NMPM LEA County ☒

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

4362 GR

## 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐CHANGE PLANS ☐PULL OR ALTER CASING ☐MULTIPLE COMPL ☐DOWNHOLE COMMINGLE ☐OTHER: ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐P AND A ☐CASING/CEMENT JOB ☐OTHER: Perf Toe and Acidize ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/14/09 – Perf Lateral Toe via tubing 10,260 ft (8) holes, 10,158 ft (7) holes, 10,101 ft (6) holes, 10,050 ft (5) holes, 9,999 ft (5) holes, 9,959 ft (4) holes, 9,850 ft (3) holes. Total 38 .35 EOD w/ 3 1/8" TCP gun.

10/14/09 - Acidized Perfs w/ total 5000 gals 7 1/2% HCL NEFE "Spot Acid". Treated w/ 5000 gals 15% HCL NEFE. AIR 16.2 BPM @ 5250 PSI. ISIP 3855 psi Dd Strg.

Spud Date:


8/6/2009

Rig Release Date:

9/26/2009

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE



TITLE Operations Manager

DATE 10/21/2009

Type or print name Richard L. Wright


E-mail address: rwright@cazapetro.com

PHONE: 432 682 7424

For State Use Only

APPROVED

BY:



TITLE

PETROLEUM ENGINEER

DATE

OCT 26 2009

Conditions of Approval (if any):