Do not	UNITED ST. DEPARTMENT OF BUREAU OF LAND NDRY NOTICES AND use this form for propos ned well. Use Form 3160	THE INTERIOR MANAGEMENT REPORTS ON W als to drill or to re	e-enterpool	JE Lease Seria	87700	
SUBMIT	N TRIPLICATE- Other	instructions on rev	verse side.		CA/Agreement, Name and/or 001-14277 (มามา-706	
1. Type of Well Oil Well		her		8. Well Nam		
2. Name of Operator Enste	or Grama Ridge Storage and Tr	ansportation, LLC		Grama 9. API We	Ridge Fed., 8817 JV-P, #1	
Ra Address	49, Suite 400, Houston, TX 7707	3b. Phone No. (incl	hude area code)	30-025-	30686	
	ge, Sec., T., R., M., or Survey Descrip		······································	-	Pool, or Exploratory Area Ridge, Morrow (Gas)	
UL-B-, Sec. 9, T22S, R	, .				r Parish. State	
660' FNL & 1980' FEL				Lea Co.	, NM	
I2. CHE	CK APPROPRIATE BOX(ES) TO INDICATE NAT	URE OF NOTICE, R	i EPORT, OR	OTHER DATA	
TYPE OF SUBMISSI			YPE OF ACTION			
(1 77)	Acidize	Deepen	Production (Str	art/Resume)	Water Shut-Off	
Notice of Intent	Alter Casing	Fracture Treat	Reclamation	,	Well Integrity	
Subsequent Report	Casing Repair	New Construction	president and a second s		Other	
Final Abandonment N	otice	Plug and Abandon	n Temporarily At Water Disposal	xundon		
following completion of	which the work will be performed or of the involved operations. If the oper	nation results in a multiple con	mulction or recompletion i	n a new interval	a Form 3160.4 shall be filed a	once
following completion on testing has been completed determined that the site Workover Procedu	which the work will be performed or of the involved operations. If the oper eted. Final Abandonment Notices sh is ready for final inspection.) re to Convert Well to Natural G Date November 2, 2009.	ration results in a multiple con all be filed only after all requi	mpletion or recompletion i irements, including reclam SEE ATTA	n a new interval, ation, have been ACHED	a Forn 3160-4 shall be filed of completed, and the operator h FOR	once las
following completion of testing has been completed determined that the site Workover Procedur Estimated Starting 1. MIRU wireline 1 2. MIRU workove 3. Release packer, 4. Mill and retriev 5. Run casing insp 6. Squeeze cement 7. Run GRN and C 8. Replace tubing I 9. Run new 4-1/2" 10. MIRU electric 11. MIRU colled to	of the involved operations. If the oper cted. Final Abandonment Notices sh is ready for final inspection.) re to Convert Well to Natural G Date November 2, 2009. anit, set plug in tubing, perforat rig, ND tree, install BOPs and pull tubing and packer. e packer in 4-1/2" liner. section logs in 4-1/2" and 7" casis perforations 12,677-99', drill ou	ation results in a multiple con all be filed only after all requi ins Injection. e hole in tubing, displace test. ng and set CIBP at 13,255 t and test. Isosantes er at 12,750'. nove BOPs, set tree, perfor 48' and 13,019-39', RDM cell. RDMO.	mpletion or recompletion i irements, including reclam SEE ATTA CONDITIO packer fluid with foam 5. 	n a new interval, ation, have been ACHED ONS OI ONS OI	a Form 3160-4 shall be filed completed, and the operator h FOR FAPPROVAL	once ins 4 8800.
following completion of testing has been completed determined that the site Workover Procedu Estimated Starting 1. MIRU wireline 1 2. MIRU workove 3. Release packer, 4. Mill and retriev 5. Run casing insp 6. Squeeze cement 7. Run GRN and C 8. Replace tubing I 9. Run new 4-1/2" 10. MIRU electric 11. MIRU colled th Attached are well a	of the involved operations. If the oper ted. Final Abandonment Notices sh is ready for final inspection.) re to Convert Well to Natural G Date November 2, 2009. anit, set plug in tubing, perforat rig. ND tree, install BOPs and pull tubing and packer. e packer in 4-1/2" liner. section logs in 4-1/2" and 7" casis perforations 12,677-99', drill ou BL logs. tead and set packer in 4-1/2" lin x 2-3/8" tubing, test packer, ren line unit and reperforate 12,844. bing and nitrogen and unload w schematics for well as it now exis-	ation results in a multiple con all be filed only after all requi ins Injection. e hole in tubing, displace test. ng and set CIBP at 13,255 t and test. Isosantes er at 12,750'. nove BOPs, set tree, perfor 48' and 13,019-39', RDM cell. RDMO.	mpletion or recompletion i irements, including reclam SEE ATTA CONDITIO packer fluid with foam 5. 	n a new interval, ation, have been ACHED ONS OI ONS OI	a Form 3160-4 shall be filed completed, and the operator h FOR FAPPROVAL	once ins 4 8800.
following completion of testing has been completed determined that the site Workover Procedu Estimated Starting 1. MIRU wireline 1 2. MIRU workove 3. Release packer, 4. Mill and retriev 5. Run casing insp 6. Squeeze cement 7. Run GRN and C 8. Replace tubing I 9. Run new 4-1/2" 10. MIRU electric 11. MIRU colled th Attached are well s	of the involved operations. If the oper ted. Final Abandonment Notices sh is ready for final inspection.) re to Convert Well to Natural G Date November 2, 2009. anit, set plug in tubing, perforat rig. ND tree, install BOPs and pull tubing and packer. e packer in 4-1/2" liner. setton logs in 4-1/2" and 7" casis perforations 12,677-99', drill ou BL logs. tead and set packer in 4-1/2" lin x 2-3/8" tubing, test packer, ren line unit and reperforate 12,844- bing and nitrogen and unload w ethematics for well as it now exis- ted foregoing is true and correct ed)	ation results in a multiple con all be filed only after all requi ins Injection. e hole in tubing, displace test. bg and set CIBP at 13,255 t and test. Isosantes er at 12,750'. hove BOPs, set tree, perfor 48' and 13,019-39', RDM vell. RDMO.	mpletion or recompletion i irements, including reclam SEE ATTA CONDITIO packer fluid with foam 5. 	n a new interval, ation, have been ACHED ONS OI IO workover r ber on file with	a Form 3160-4 shall be filed completed, and the operator h FOR FAPPROVAL	once ins 4 8800.
following completion of testing has been compl determined that the site Workover Procedu Estimated Starting 1. MIRU wireline 1 2. MIRU workove 3. Release packer, 4. Mill and retriev 5. Run casing insp 6. Squeeze cement 7. Run GRN and C 8. Replace tubing I 9. Run new 4-1/2" 10. MIRU electric 11. MIRU colled th Attached are well a	of the involved operations. If the oper ted. Final Abandonment Notices sh is ready for final inspection.) re to Convert Well to Natural G Date November 2, 2009. anit, set plug in tubing, perforat rig. ND tree, install BOPs and pull tubing and packer. e packer in 4-1/2" liner. setton logs in 4-1/2" and 7" casis perforations 12,677-99', drill ou BL logs. tead and set packer in 4-1/2" lin x 2-3/8" tubing, test packer, ren line unit and reperforate 12,844- bing and nitrogen and unload w ethematics for well as it now exis- ted foregoing is true and correct ed)	ation results in a multiple con all be filed only after all requi ins Injection. e hole in tubing, displace test. bg and set CIBP at 13,255 t and test. Isosantes er at 12,750'. hove BOPs, set tree, perfor 48' and 13,019-39', RDM vell. RDMO.	mpletion or recompletion i irements, including reclam SEE ATTA CONDITIO packer fluid with foam 5. 	n a new interval, ation, have been ACHED ONS OI IO workover r ber on file with	a Form 3160-4 shall be filed completed, and the operator h FOR FAPPROVAL	once ins 4 8800.
following completion of testing has been compl determined that the site Workover Procedu Estimated Starting 1. MIRU wireline 1 2. MIRU workove 3. Release packer, 4. Mill and retriev 5. Run casing insp 6. Squeeze cement 7. Run GRN and C 8. Replace tubing I 9. Run new 4-1/2" 10. MIRU electric 11. MIRU colled th Attached are well a 14. I hereby certify that t Name (Printed/Typ Dapyt W.	of the involved operations. If the oper ted. Final Abandonment Notices sh is ready for final inspection.) re to Convert Well to Natural G Date November 2, 2009. anit, set plug in tubing, perforat rig. ND tree, install BOPs and pull tubing and packer. e packer in 4-1/2" liner. section logs in 4-1/2" and 7" casin perforations 12,677-99', drill ou BL logs. tead and set packer in 4-1/2" lin x 2-3/8" tubing, test packer, ren line unit and reperforate 12,844. bing and nitrogen and unload w schematics for well as it now exist the foregoing is true and correct ed)	ation results in a multiple con all be filed only after all requi ins Injection. e hole in tubing, displace test. ng and set CIBP at 13,255 t and test. Isosantes er at 12,750'. nove BOPs, set tree, perfor 48' and 13,019-39', RDM well. RDMO. ts and after the proposed Title	mpletion or recompletion i irements, including reclam SEE ATTA CONDITIO packer fluid with foam 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5.	n a new interval, ation, have been ACHED ONS OI ONS OI	a Form 3160-4 shall be filed completed, and the operator h FOR F APPROVAL F From 12,600-134 rig. a BLM/BIA is NMB00030	once ins 4 8800.
following completion of testing has been compl determined that the site Workover Procedu Estimated Starting 1. MIRU wireline 1 2. MIRU workove 3. Release packer, 4. Mill and retriev 5. Run casing insp 6. Squeeze cement 7. Run GRN and C 8. Replace tubing I 9. Run new 4-1/2" 10. MIRU electric 11. MIRU colled th Attached are well a 14. I hereby certify that the Name (Printed/Typ Daryt W. Signature	of the involved operations. If the oper ted. Final Abandonment Notices sh is ready for final inspection.) re to Convert Well to Natural G Date November 2, 2009. anit, set plug in tubing, perforat rig. ND tree, install BOPs and pull tubing and packer. e packer in 4-1/2" liner. setton logs in 4-1/2" and 7" casis perforations 12,677-99', drill ou BL logs. tead and set packer in 4-1/2" lin x 2-3/8" tubing, test packer, ren line unit and reperforate 12,844. bling and nitrogen and unload w echematics for well as it now exis the foregoing is true and correct ed) THIS SPACE FC	ation results in a multiple con all be filed only after all requi- is Injection. e hole in tubing, displace test. ng and set CIBP at 13,255 t and test. Isosarts be er at 12,750'. hove BOPs, set tree, perfor 48' and 13,019-39', RDM well. RDMO. ts and after the proposed Title Date DR FEDERAL OR	mpletion or recompletion i irements, including reclam SEE ATTA CONDITIO packer fluid with foam 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5.	n a new interval, ation, have been ACHED ONS OI we referred to workover r ber on file with http://www.com/ ber on file with Ministrand Lan 0/28/2009	a Form 3160-4 shall be filed completed, and the operator h FOR F APPROVAL F From 12,600-134 rig. a BLM/BIA is NMB00030	once ins 4 8800.
following completion of testing has been completed determined that the site Workover Procedur Estimated Starting 1. MIRU wireline 1 2. MIRU workove 3. Release packer, 4. MIII and retriev 5. Run casing insp 6. Squeeze cement 7. Run GRN and C 8. Replace tubing I 9. Run new 4-1/2" 10. MIRU electric 11. MIRU colled th Attached are well s 14. Thereby certify that t Name (Printed/Typ Daryt W. Signature	of the involved operations. If the oper ted. Final Abandonment Notices sh is ready for final inspection.) re to Convert Well to Natural G Date November 2, 2009. anit, set plug in tubing, perforat rig, ND tree, install BOPs and pull tubing and packer. e packer in 4-1/2" liner. ection logs in 4-1/2" and 7" casis perforations 12,677-99', drill ou BL logs. nead and set packer in 4-1/2" line x 2-3/8" tubing, test packer, ren line unit and reperforate 12,844. bing and nitrogen and unload w chematics for well as it now exis the foregoing is true and correct ed/) Green THIS SPACE FC	ation results in a multiple con all be filed only after all requi- ins Injection. e hole in tubing, displace test. ng and set CIBP at 13,255 t and test. Isosantes er at 12,750'. nove BOPs, set tree, perfor 48' and 13,019-39', RDM well. RDMO. ts and after the proposed Title Date DR FEDERAL OR S	mpletion or recompletion i irements, including reclam SEE ATTA CONDITIO packer fluid with foam 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5.	n a new interval, ation, have been ACHED ONS OI 	a Form 3160-4 shall be filed completed, and the operator h FOR FAPPROVAL if Form 12,600-1,34 if BLM/BIA is NMB00030 md Management PROVED	ero.'
following completion of testing has been completed determined that the site Workover Procedur Estimated Starting 1. MIRU wireline 1 2. MIRU workover 3. Release packer, 4. MIII and retriev 5. Run casing insp 6. Squeeze cement 7. Run GRN and C 8. Replace tubing I 9. Run new 4-1/2" 10. MIRU electric 11. MIRU colled th Attached are well s 14. Thereby certify that th Name (Printed/Typ Daryt W. Signature	of the involved operations. If the oper ted. Final Abandonment Notices sh is ready for final inspection.) re to Convert Well to Natural G Date November 2, 2009. anit, set plug in tubing, perforat rig. ND tree, install BOPs and pull tubing and packer. e packer in 4-1/2" liner. tection logs in 4-1/2" and 7" casis perforations 12,677-99', drill ou BL logs. tead and set packer in 4-1/2" lin x 2-3/8" tubing, test packer, ren line unit and reperforate 12,844 (bling and nitrogen and unload w chematics for well as it now exist the foregoing is true and correct ed/) Gec THIS SPACE FC	ation results in a multiple con all be filed only after all requi- ins Injection. e hole in tubing, displace test. ng and set CIBP at 13,255 t and test. Isosantes er at 12,750'. nove BOPs, set tree, perfor 48' and 13,019-39', RDM well. RDMO. ts and after the proposed Title Date DR FEDERAL OR otice does not warrant or phts in the subject lease a it a crime for our generation	mpletion or recompletion i irements, including reclam SEE ATTA CONDITIO packer fluid with foam 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5.	n a new interval, ation, have been ACHED ONS OI 	a Form 3160-4 shall be filed completed, and the operator h FOR FAPPROVAL if Form 12,600-1,34 if BLM/BIA is NMB00030 md Management PROVED	ero.'



Grama Ridge Federal, 8817 JV-P, #1

API # 30-025-30686 660' FNL, 1980' FEL Sec. 9, T22S, R34E

Following Conversion to Natural Gas Storage



Essex Energy Storage Services, Inc.

Grama Ridge Fed 8817 JV-P #1 30-025-30686 Enstor Grama Ridge Storage and Transportation, LLC October 29, 2009 Conditions of Approval

- 1. Surface disturbance beyond the existing pad must have prior approval.
- 2. Closed loop system required.
- 3. Operator to have H2S monitoring equipment and personal protection equipment on location as H2S has been reported in the area with measurements up to 21000 ppm.

:

- 4. 5M BOP to be installed and tested.
- 5. Subsequent sundry detailing work performed is to be submitted.

WWI 102909