	1625 N. French Drive							
	Form 3160-5 (April 2004) UNITED STATES Hobbs, NM 88240 DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT				FORM APPROVED OMB No 1064-0137 Expires. March 31, 2007			
					5 Lease Seri			
	SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an				NMNM     6. If Indian	, Allottee or Tribe Name		
	abandoned well. Use Form 3160-3 (APD) for such proposals.							
	SUBMIT IN TRIPLICATE- Other instructions on reverse side.					7. If Unit of	r CA/Agreement, Name and/or No	
	1. Type of Well Gas Well Other ✓				<ul> <li>8. Well Name and No.</li> <li>Las Cruces B #3</li> <li>9 API Well No.</li> </ul>			
	2 Name of Operator Kerns Petroleum Inc.							
	3a Address		3b. Phone No. (include area code) 210-829-7881		30-041-0023#C			
	1777 NE Loop 410 San Antonio, TX 78217         4. Location of Well (Footage, Sec., T, R, M, or Survey Description)			210-829-7881		10 Field and Pool, or Exploratory Area Allison Upper Penn		
	Unit H, 1830' FNL & 660' FEL, Section 30, T-08-S, R-37-E				11 County or Parish, State			
	V					Repsevoir, New Mexico		
	12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, RE					REPORT, OF	COTHER DATA	
	TYPE OF SUBMISSION			TYF	PE OF ACTION			
	Notice of Intent	Acıdize	Deepen Fracture	Treat	Production (S Reclamation	art/Resume)	Water Shut-Off	
	Subsequent Report	Casing Repair	·	nstruction Abandon	Recomplete	handan	Other	
	Final Abandonment Notice	Convert to Injection	Plug and Plug Back		Water Disposal			
	Attach the Bond under which following completion of the ir testing has been completed. F determined that the site is read	the work will be performed or pro- nvolved operations. If the operation final Abandonment Notices shall be dy for final inspection )	ovide the Bond N on results in a mu be filed only after	lo on file w altiple compl	vith BLM/BIA. Requi letion or recompletion	red subsequent r in a new interva	is of all pertinent markers and zones eports shall be filed within 30 days I, a Form 3160-4 shall be filed once n completed, and the operator has	
	Attach the Bond under which following completion of the ir testing has been completed. F determined that the site is read 10/9/2009 Spot 35sxs cmt 10/12/2009 Perf @ 7000' 10/14/2009 Cut 5 1/2'' cas 10/15/2009 Spot 150sxs ci 10/16/2009 Cut 8 5/8'' cas 10/16/2009 Spot 65sxs cm	the work will be performed or pro- nvolved operations. If the operation Final Abandonment Notices shall be dy for final inspection ) t @ 9507' WOC tag plug @ 91 Pressure up to 1800 PSI held sing @ 4404' LD casing mt @ 4457' tag plug @ 3800', sing @ 857' LD casing tt @ 907' tag plug @ 779'	ovide the Bond N on resul's in a mu be filed only after 195' (Okayed to sp , Spot 35sxs cm	No on file w ultiple compl r all requirer pot 35sxs cr nt @ 2310'-	vith BLM/BIA. Requi letion or recompletion ments, including reclar mt @ 7050') Spot 35 -2151'	red subsequent r in a new interva nation, have bee	eports shall be filed within 30 days I, a Form 3160-4 shall be filed once n completed, and the operator has 50' tag plug @ 6805'	
	Attach the Bond under which following completion of the ir testing has been completed. F determined that the site is read 10/9/2009 Spot 35sxs cmt 10/12/2009 Perf @ 7000' 10/14/2009 Cut 5 1/2'' cas 10/15/2009 Spot 150sxs ci 10/16/2009 Cut 8 5/8'' cas 10/16/2009 Spot 65sxs cm	the work will be performed or pro- nvolved operations. If the operation Final Abandonment Notices shall be dy for final inspection ) t @ 9507' WOC tag plug @ 91 Pressure up to 1800 PSI held sing @ 4404' LD casing mt @ 4457' tag plug @ 3800', sing @ 857' LD casing tt @ 907' tag plug @ 779' mt @ 440' tag plug @ 233' Sp	ovide the Bond N on resul's in a mu be filed only after 195' (Okayed to sp , Spot 35sxs cm	No on file w ultiple compl r all requirer pot 35sxs cr nt @ 2310'-	vith BLM/BIA. Requi letion or recompletion ments, including reclar mt @ 7050') Spot 35 -2151'	red subsequent r in a new interva nation, have bee	eports shall be filed within 30 days I, a Form 3160-4 shall be filed once n completed, and the operator has 50' tag plug @ 6805'	
	Attach the Bond under which following completion of the ir testing has been completed. F determined that the site is read 10/9/2009 Spot 35sxs cmt 10/12/2009 Perf @ 7000' 10/14/2009 Cut 5 1/2'' cas 10/15/2009 Spot 150sxs cn 10/16/2009 Spot 65sxs cm 10/16/2009 Spot 65sxs cm 10/19/2009 Spot 100sxs cn	the work will be performed or pro- nvolved operations. If the operation Final Abandonment Notices shall be dy for final inspection ) t @ 9507' WOC tag plug @ 91 Pressure up to 1800 PSI held sing @ 4404' LD casing mt @ 4457' tag plug @ 3800', sing @ 857' LD casing tt @ 907' tag plug @ 779' mt @ 440' tag plug @ 233' Sp	ovide the Bond N on resul's in a mu be filed only after 195' (Okayed to sp , Spot 35sxs cm	No on file w ultiple compl r all requirer pot 35sxs cr nt @ 2310'-	vith BLM/BIA. Requi letton or recompletion nents, including reclar nt @ 7050') Spot 35 -2151' ce	red subsequent r in a new interva nation, have bee Ssxs cmt @ 705	eports shall be filed within 30 days I, a Form 3160-4 shall be filed once in completed, and the operator has 50' tag plug @ 6805' RECEIVE NI IV 2 A 2000	
	Attach the Bond under which following completion of the ir testing has been completed. F determined that the site is read 10/9/2009 Spot 35sxs cmt 10/12/2009 Perf @ 7000' 10/14/2009 Cut 5 1/2'' cas 10/15/2009 Spot 150sxs cn 10/16/2009 Spot 65sxs cm 10/16/2009 Spot 65sxs cm 10/19/2009 Spot 100sxs cn	the work will be performed or pro- nvolved operations. If the operation Final Abandonment Notices shall be dy for final inspection ) t @ 9507' WOC tag plug @ 91 Pressure up to 1800 PSI held sing @ 4404' LD casing mt @ 4457' tag plug @ 3800', sing @ 857' LD casing tt @ 907' tag plug @ 779' mt @ 440' tag plug @ 233' Sp	ovide the Bond N on resul's in a mu be filed only after 195' (Okayed to sp , Spot 35sxs cm	No on file w ultuple compi r all requirer oot 35sxs cr nt @ 2310'- i0' to surfa	<ul> <li>with BL.M/BIA. Requi letion or recompletion nents, including reclar</li> <li>mt @ 7050') Spot 35</li> <li>-2151'</li> <li>ce</li> <li>APPROVED AS TO PI WELL BORE. LIABILI</li> </ul>	red subsequent r in a new interva nation, have bee isxs cmt @ 705 UGGING OF THIS TY UNDER BOND	eports shall be filed within 30 days I, a Form 3160-4 shall be filed once in completed, and the operator has 50' tag plug @ 6805' RECEIVE NUV 2 4 200	
	Attach the Bond under which following completion of the ir testing has been completed. F determined that the site is read 10/9/2009 Spot 35sxs cmt 10/12/2009 Perf @ 7000' 10/14/2009 Cut 5 1/2'' cas 10/15/2009 Spot 150sxs cn 10/16/2009 Spot 65sxs cm 10/16/2009 Spot 65sxs cm 10/19/2009 Spot 100sxs cn	the work will be performed or pro- nvolved operations. If the operation Final Abandonment Notices shall be dy for final inspection ) t @ 9507' WOC tag plug @ 91 Pressure up to 1800 PSI held sing @ 4404' LD casing mt @ 4457' tag plug @ 3800', sing @ 857' LD casing tt @ 907' tag plug @ 779' mt @ 440' tag plug @ 233' Sp	ovide the Bond N on resul's in a mu be filed only after 195' (Okayed to sp , Spot 35sxs cm	No on file w ultuple compi r all requirer oot 35sxs cr nt @ 2310'- i0' to surfa	vith BLM/BIA. Requi letton or recompletion nents, including reclar nt @ 7050') Spot 35 -2151' ce APPROVED AS TO PI	red subsequent r in a new interva nation, have bee isxs cmt @ 705 UGGING OF THIS TY UNDER BOND FACE RESTORATIO	eports shall be filed within 30 days I, a Form 3160-4 shall be filed once in completed, and the operator has 50' tag plug @ 6805' RECEIVE NUV 2 4 200 HOBBSOCE MW/OCD	
	Attach the Bond under which following completion of the ir testing has been completed. F determined that the site is read 10/9/2009 Spot 35sxs cmt 10/12/2009 Perf @ 7000' 10/14/2009 Cut 5 1/2" cas 10/16/2009 Spot 150sxs cn 10/16/2009 Spot 150sxs cm 10/19/2009 Spot 100sxs cn 10/19/2009 Install Dry Ho	the work will be performed or pro- nvolved operations. If the operation inal Abandonment Notices shall be dy for final inspection ) the @ 9507' WOC tag plug @ 91 Pressure up to 1800 PSI held sing @ 4404' LD casing mt @ 4457' tag plug @ 3800', sing @ 857' LD casing nt @ 907' tag plug @ 779' mt @ 440' tag plug @ 233' Sp ole Marker	ovide the Bond N on resul's in a mu be filed only after 195' (Okayed to sp , Spot 35sxs cm	Jo on file w ultuple compi r all requirer out 35sxs cr nt @ 2310'- i0' to surfa	vith BL.M/BIA. Requi letton or recompletion nents, including reclar mt @ 7050') Spot 35 -2151' ce APPROVED AS TO PI WELL BORE. LIABILI IS RETAINED UNTIL SUR IS COMPI	red subsequent r in a new interva nation, have bee isxs cmt @ 709 UGGING OF THIS TY UNDER BOND FACE RESTORATIK ETED	eports shall be filed within 30 days I, a Form 3160-4 shall be filed once in completed, and the operator has 50' tag plug @ 6805' RECEIVE NUV 2 4 2000 HOBBSOCE MW/OCD 11-25-09	
	Attach the Bond under which following completion of the ir testing has been completed. F determined that the site is read 10/9/2009 Spot 35sxs cmt 10/12/2009 Perf @ 7000' 10/14/2009 Cut 5 1/2'' cas 10/15/2009 Spot 150sxs cn 10/16/2009 Spot 150sxs cn 10/16/2009 Spot 65sxs cm 10/19/2009 Spot 100sxs cn 10/19/2009 Install Dry Ho	the work will be performed or pro- nvolved operations. If the operation inal Abandonment Notices shall be dy for final inspection ) the @ 9507' WOC tag plug @ 91 Pressure up to 1800 PSI held sing @ 4404' LD casing mt @ 4457' tag plug @ 3800', sing @ 857' LD casing nt @ 907' tag plug @ 779' mt @ 440' tag plug @ 233' Sp ole Marker	ovide the Bond N on resul's in a mu be filed only after 195' (Okayed to sp , Spot 35sxs cm	Jo on file w ultuple compi r all requirer out 35sxs cr nt @ 2310'- i0' to surfa	vith BL.M/BIA. Requi letton or recompletion nents, including reclar mt @ 7050') Spot 35 -2151' ce APPROVED AS TO PI WELL BORE. LIABILI IS RETAINED UNTIL SUR IS COMPI	red subsequent r in a new interva nation, have bee isxs cmt @ 709 UGGING OF THIS TY UNDER BOND FACE RESTORATIK ETED	eports shall be filed within 30 days I, a Form 3160-4 shall be filed once in completed, and the operator has 50' tag plug @ 6805' RECEIVE NUV 2 4 2000 HOBBSOCE MW/OCD 11-25-09	
	Attach the Bond under which following completion of the ir testing has been completed. F determined that the site is read 10/9/2009 Spot 35sxs cmt 10/12/2009 Perf @ 7000' 10/14/2009 Cut 5 1/2'' cas 10/16/2009 Spot 150sxs cn 10/16/2009 Spot 150sxs cn 10/19/2009 Spot 100sxs cn 10/19/2009 Install Dry Ho 10/19/2009 Install Dry Ho 10/19/2009 Install Dry Ho 11 I hereby certify that the form Name ( <i>Printed/Typed</i> ) Larry Winn.	the work will be performed or pro- nvolved operations. If the operation inal Abandonment Notices shall be dy for final inspection ) the @ 9507' WOC tag plug @ 91 Pressure up to 1800 PSI held sing @ 4404' LD casing mt @ 4457' tag plug @ 3800', sing @ 857' LD casing nt @ 907' tag plug @ 779' mt @ 440' tag plug @ 233' Sp ole Marker	ovide the Bond N on results in a mu be filed only after (Okayed to sp , Spot 35sxs cm bot 20sxs cmt 6	Jo on file w ultuple compi r all requirer out 35sxs cr nt @ 2310'- 50' to surfa 50' to surfa Title Ar Date	vith BL.M/BIA. Requi letion or recompletion nents, including reclar mt @ 7050') Spot 35 -2151' ce APPROVED AS TO PI WELL BORE. LIABILI IS RETAINED UNTIL SUR IS COMPL	red subsequent r in a new interva nation, have bee isxs cmt @ 709 isxs cmt @ 709	eports shall be filed within 30 days I, a Form 3160-4 shall be filed once in completed, and the operator has 50' tag plug @ 6805' RECEIVE NUV 2 4 2000 HOBBSOCE MW/OCD 11-25-09	
· ·	Attach the Bond under which following completion of the ir testing has been completed. F determined that the site is read 10/9/2009 Spot 35sxs cmt 10/12/2009 Perf @ 7000' 10/14/2009 Cut 5 1/2'' cas 10/15/2009 Spot 150sxs cm 10/16/2009 Spot 65sxs cm 10/19/2009 Spot 65sxs cm 10/19/2009 Spot 100sxs cr 10/19/2009 Install Dry Ho 14 Ihereby certify that the ford Name (Printed Typed) Larry Winn. Signature Approved by /S/DA	the work will be performed or pro- nvolved operations. If the operation inal Abandonment Notices shall be dy for final inspection ) the @ 9507' WOC tag plug @ 91 Pressure up to 1800 PSI held sing @ 4404' LD casing mt @ 4457' tag plug @ 3800', sing @ 857' LD casing the @ 907' tag plug @ 779' mt @ 440' tag plug @ 233' Sp ole Marker egoing is true and correct THIS SPACE FOR VID R. GLA	ASS	Vo on file w ultuple compl r all requirer oot 35sxs cr nt @ 2310'- i0' to surfa i0' to surfa L OR S1	vith BL.M/BIA. Requi letion or recompletion nents, including reclar mt @ 7050') Spot 35 -2151' ce APPROVED AS TO PI WELL BORE. LIABILI IS RETAINED UNTIL SUR IS COMPL	red subsequent r in a new interva nation, have bee isss cmt @ 709 UGGING OF THIS TY UNDER BOND FACE RESTORATIK ETED Basic Energy 10/26/2009 USE	eports shall be filed within 30 days I, a Form 3160-4 shall be filed once in completed, and the operator has 50' tag plug @ 6805' RECEIVE NUV 2 4 2001 HOBBSOCI MW /0CD N-25-09 Services 432-530-0907	
•	Attach the Bond under which following completion of the ir testing has been completed. F determined that the site is read 10/9/2009 Spot 35sxs cmt 10/12/2009 Perf @ 7000' 10/14/2009 Cut 5 1/2'' cas 10/15/2009 Spot 150sxs cm 10/16/2009 Spot 150sxs cm 10/19/2009 Spot 65sxs cm 10/19/2009 Spot 100sxs cr 10/19/2009 Install Dry Ho 14 Thereby certify that the fore Name (Printed/Typed) Larry Winn. Signature	the work will be performed or pro- nvolved operations. If the operation inal Abandonment Notices shall be dy for final inspection ) the 9507' WOC tag plug @ 91 Pressure up to 1800 PSI held sing @ 4404' LD casing mt @ 4457' tag plug @ 3800', sing @ 857' LD casing the 907' tag plug @ 779' mt @ 440' tag plug @ 233' Sp ole Marker egoing is true and correct THIS SPACE FOR ALTACE Approval of this notice al or equitable title to those rights	ovide the Bond N on results in a mu be filed only after (Okayed to sp , Spot 35sxs cm tot 20sxs cmt 6 CFEDERAI ASS e does not warra	Vo on file w ultuple compl r all requirer pot 35sxs cr nt @ 2310'- 50' to surfa 50' to surfa 10' to surfa L OR ST ant or	vith BLM/BIA. Requi letion or recompletion nents, including reclar nt @ 7050') Spot 35 -2151' ce APPROVED AS TO PI WELL BORE. LIABILI IS RETAINED UNTIL SUR IS COMPL rea Manager, P&A TATE OFFICE PETROLEUM E	red subsequent r in a new interva nation, have bee isss cmt @ 709 UGGING OF THIS TY UNDER BOND FACE RESTORATIK ETED Basic Energy 10/26/2009 USE	eports shall be filed within 30 days I, a Form 3160-4 shall be filed once in completed, and the operator has 50' tag plug @ 6805' RECEIVE NUV 2 4 2001 DN HOBBSOCE MW/OCD 11-25-09 Services 432-530-0907 ate NOV 1 6 2009	
Fina	Attach the Bond under which following completion of the ir testing has been completed. F determined that the site is read 10/9/2009 Spot 35sxs cmt 10/12/2009 Perf @ 7000' 10/14/2009 Cut 5 1/2'' cas 10/15/2009 Spot 150sxs cn 10/16/2009 Spot 65sxs cm 10/19/2009 Spot 65sxs cm 10/19/2009 Spot 100sxs cr 10/19/2009 Install Dry Ho United Typed Larry Winn. Signature Approved by /S/DA Conditions of approval, if any, are certify that the applicant holds lega	the work will be performed or pro- nvolved operations. If the operation inal Abandonment Notices shall be dy for final inspection ) the @ 9507' WOC tag plug @ 91 Pressure up to 1800 PSI held sing @ 4404' LD casing mt @ 4457' tag plug @ 3800', sing @ 857' LD casing nt @ 907' tag plug @ 779' mt @ 440' tag plug @ 233' Sp ole Marker egoing is true and correct THIS SPACE FOR MID B. GLA attached Approval of this notice al or equitable title to those rights to conduct operations thereon.	bovide the Bond N on results in a mu be filed only after (Okayed to sp , Spot 35sxs cm bot 20sxs cmt 6 Cost 20sx cmt 7 Cost 20sx cmt 7 Co	Vo on file w ultuple compl r all requirer oot 35sxs cr nt @ 2310'- i0' to surfa i0' to surfa Title Ar Date LOR SI ant or ease Of y person knc	vith BLM/BIA. Requi letion or recompletion nents, including reclar nt @ 7050') Spot 35 -2151' ce APPROVED AS TO PI WELL BORE. LIABILI IS RETAINED UNTIL SUR IS COMPL rea Manager, P&A TATE OFFICE DETROLEUM E Thice ROSW	red subsequent r in a new interva nation, have bee isss cmt @ 709 UGGING OF THIS TY UNDER BOND FACE RESTORATIK ETED Basic Energy U0/26/2009 USE ENGINEER MAINEER TELL FIELI	eports shall be filed within 30 days I, a Form 3160-4 shall be filed once in completed, and the operator has 50' tag plug @ 6805' RECEIVE NUV 2 4 2001 DN HOBBSOCE MW/OCD 11-25-09 Services 432-530-0907 ate NOV 1 6 2009	