	traffered	and the second of the second o
Submit 3 Copies To Appropriate D	State of Mem Mexico	Form C-103
<u>District I</u> 1625 N. French Dr., Hobbs NM	Energy, Minerals and Natural Resources	June 19, 2008
District II	Energy, Minerals and Natural Resources ECCURE ONSERVATION DIVISION DEC 0.2 2000 1220 South St. Francis Dr.	WELL API NO.
1301 W. Grand Ave., Artesia, NM District III	88210 UIL CONSERVATION DIVISION	30-005-27970 / 5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec NM 8	7410	STATE STEE
District IV 1220 S. St. Francis Dr., Santa Felix	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
87505		
SUNDRY	NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR, USE	PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 'APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	/ Cint regreement ivaline
TROI OURLD.)		CATO SAN ANDRES UNIT
1. Type of Well: Oil Well	☐ Other	8. Well Number 407
2. Name of Operator	DEED CONTRACTOR	9. OGRID Number
3 Address of Operator	PETRO OF NEW MEXICO, INC.	248802
	IT 25 SUITE 3200 FT WORTH TX 76102	10. Pool name or Wildcat
4. Well Location		Cato San Andres
Unit Letter J	· 1980 feet from the NORTH 1: 30	OS OSO
Section 27	line and 20	feet from the East line
Section 27	Township 08S Range 30E	NMPM County Chaves
	11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4169 FT GL	
	Market 4109 L1 GD	
12 Che	ack Appropriate Roy to Indicate National Control	
	eck Appropriate Box to Indicate Nature of Notice, I	Report or Other Data
NOTICE O	FINTENTION TO: SUBS	SEQUENT REPORT OF:
PERFORM REMEDIAL WOR	THE FEOGRAND ABANDON LI REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	LI CHANGE PLANS COMMENCE DRIL	
PULL OR ALTER CASING DOWNHOLE COMMINGLE	LI MULTIPLE COMPL CASING/CEMENT	JOB 🗵
DOWN IOLE COMMINGLE		_
OTHER:		
Describe proposed or c		e, acidize, frac, install pump
of starting any propose	ed work). SEE RULE 1103. For Multiple Completions: Atta	give pertinent dates, including estimated date
or recompletion.	1	wensore diagram of proposed completion
10/23/2007:	Spudded 12-1/4" hole and drilled from surfac	
		0 to E1E! Day to
	21# Cbg flom Surface to 515'. Cemented w/ 3	50 gy C Wood o 1
10/24 - 11/2/2007:	Drilled 7-7/8" hole from 515' to 4000' (TD)	50 sx C. WOC 8 hours.
10/24 - 11/2/2007: 11/3/2007:	Drilled 7-7/8" hole from 515' to 4000' (TD). Ran open-hole logs. Ran 5-1/2" 17# J-55 CSG	50 sx C. WOC 8 hours.
11/3/2007:	Drilled 7-7/8" hole from 515' to 4000' (TD). Ran open-hole logs. Ran 5-1/2" 17# J-55 csg w/ 900 sx 65/35 Pozmix. WOC 24 hours.	50 sx C. WOC 8 hours. TOOH for log. from surface to 3995. Cemented
11/3/2007:	Drilled 7-7/8" hole from 515' to 4000' (TD). Ran open-hole logs. Ran 5-1/2" 17# J-55 csg w/ 900 sx 65/35 Pozmix. WOC 24 hours. Ran GR/CBL and perforated San Andres @ 4 spf	50 sx C. WOC 8 hours. TOOH for log. from surface to 3995. Cemented
11/3/2007: 11/8/2007: 12/1/2007:	Drilled 7-7/8" hole from 515' to 4000' (TD). Ran open-hole logs. Ran 5-1/2" 17# J-55 csg w/ 900 sx 65/35 Pozmix. WOC 24 hours. Ran GR/CBL and perforated San Andres @ 4 spf Acidized well w/ 13,500 gal 15% HCl @ 7.5 RDM	50 sx C. WOC 8 hours. TOOH for log. from surface to 3995. Cemented : 3510-3558' and 3578-3592'
11/3/2007:	Drilled 7-7/8" hole from 515' to 4000' (TD). Ran open-hole logs. Ran 5-1/2" 17# J-55 csg w/ 900 sx 65/35 Pozmix. WOC 24 hours. Ran GR/CBL and perforated San Andres @ 4 spf Acidized well w/ 13,500 gal 15% HCl @ 7.5 RDM	50 sx C. WOC 8 hours. TOOH for log. from surface to 3995. Cemented : 3510-3558' and 3578-3592'
11/3/2007: 11/8/2007: 12/1/2007:	Drilled 7-7/8" hole from 515' to 4000' (TD). Ran open-hole logs. Ran 5-1/2" 17# J-55 csg w/ 900 sx 65/35 Pozmix. WOC 24 hours. Ran GR/CBL and perforated San Andres @ 4 spf	50 sx C. WOC 8 hours. TOOH for log. from surface to 3995. Cemented : 3510-3558' and 3578-3592'
11/3/2007: 11/8/2007: 12/1/2007:	Drilled 7-7/8" hole from 515' to 4000' (TD). Ran open-hole logs. Ran 5-1/2" 17# J-55 csg w/ 900 sx 65/35 Pozmix. WOC 24 hours. Ran GR/CBL and perforated San Andres @ 4 spf Acidized well w/ 13,500 gal 15% HCl @ 7.5 RDM	50 sx C. WOC 8 hours. TOOH for log. from surface to 3995. Cemented : 3510-3558' and 3578-3592'
11/3/2007: 11/8/2007: 12/1/2007:	Drilled 7-7/8" hole from 515' to 4000' (TD). Ran open-hole logs. Ran 5-1/2" 17# J-55 csg w/ 900 sx 65/35 Pozmix. WOC 24 hours. Ran GR/CBL and perforated San Andres @ 4 spf Acidized well w/ 13,500 gal 15% HCl @ 7.5 RDM	50 sx C. WOC 8 hours. TOOH for log. from surface to 3995. Cemented : 3510-3558' and 3578-3592'
11/3/2007: 11/8/2007: 12/1/2007: 12/7/2007:	Drilled 7-7/8" hole from 515' to 4000' (TD). Ran open-hole logs. Ran 5-1/2" 17# J-55 csg w/ 900 sx 65/35 Pozmix. WOC 24 hours. Ran GR/CBL and perforated San Andres @ 4 spf Acidized well w/ 13,500 gal 15% HCl @ 7.5 BPN RIH w/ 3583' 2-3/8" tbg, rods, and 2.0" x 1.5	50 sx C. WOC 8 hours. TOOH for log. from surface to 3995. Cemented : 3510-3558' and 3578-3592'
11/3/2007: 11/8/2007: 12/1/2007: 12/7/2007:	Drilled 7-7/8" hole from 515' to 4000' (TD). Ran open-hole logs. Ran 5-1/2" 17# J-55 csg w/ 900 sx 65/35 Pozmix. WOC 24 hours. Ran GR/CBL and perforated San Andres @ 4 spf Acidized well w/ 13,500 gal 15% HCl @ 7.5 BPN RIH w/ 3583' 2-3/8" tbg, rods, and 2.0" x 1.5	50 sx C. WOC 8 hours. TOOH for log. from surface to 3995. Cemented : 3510-3558' and 3578-3592'
11/3/2007: 11/8/2007: 12/1/2007: 12/7/2007:	Drilled 7-7/8" hole from 515' to 4000' (TD). Ran open-hole logs. Ran 5-1/2" 17# J-55 csg w/ 900 sx 65/35 Pozmix. WOC 24 hours. Ran GR/CBL and perforated San Andres @ 4 spf Acidized well w/ 13,500 gal 15% HCl @ 7.5 BPN RIH w/ 3583' 2-3/8" tbg, rods, and 2.0" x 1.5	50 sx C. WOC 8 hours. TOOH for log. from surface to 3995. Cemented : 3510-3558' and 3578-3592'
11/3/2007: 11/8/2007: 12/1/2007: 12/7/2007:	Drilled 7-7/8" hole from 515' to 4000' (TD). Ran open-hole logs. Ran 5-1/2" 17# J-55 csg w/ 900 sx 65/35 Pozmix. WOC 24 hours. Ran GR/CBL and perforated San Andres @ 4 spf Acidized well w/ 13,500 gal 15% HCl @ 7.5 BPN RIH w/ 3583' 2-3/8" tbg, rods, and 2.0" x 1.5	50 sx C. WOC 8 hours. TOOH for log. from surface to 3995. Cemented : 3510-3558' and 3578-3592' M 5" x 16' pump and hung on
11/3/2007: 11/8/2007: 12/1/2007: 12/7/2007:	Drilled 7-7/8" hole from 515' to 4000' (TD). Ran open-hole logs. Ran 5-1/2" 17# J-55 csg w/ 900 sx 65/35 Pozmix. WOC 24 hours. Ran GR/CBL and perforated San Andres @ 4 spf Acidized well w/ 13,500 gal 15% HCl @ 7.5 BPN RIH w/ 3583' 2-3/8" tbg, rods, and 2.0" x 1.5	50 sx C. WOC 8 hours. TOOH for log. from surface to 3995. Cemented : 3510-3558' and 3578-3592' M 5" x 16' pump and hung on
11/3/2007: 11/8/2007: 12/1/2007: 12/7/2007: Spud Date: 10/23/2007 hereby certify that the informat	Drilled 7-7/8" hole from 515' to 4000' (TD). Ran open-hole logs. Ran 5-1/2" 17# J-55 csg w/ 900 sx 65/35 Pozmix. WOC 24 hours. Ran GR/CBL and perforated San Andres @ 4 spf Acidized well w/ 13,500 gal 15% HCl @ 7.5 BPN RIH w/ 3583' 2-3/8" tbg, rods, and 2.0" x 1.5	50 sx C. WOC 8 hours. TOOH for log. from surface to 3995. Cemented : 3510-3558' and 3578-3592' M 5" x 16' pump and hung on
11/3/2007: 11/8/2007: 12/1/2007: 12/7/2007:	Drilled 7-7/8" hole from 515' to 4000' (TD). Ran open-hole logs. Ran 5-1/2" 17# J-55 csg w/ 900 sx 65/35 Pozmix. WOC 24 hours. Ran GR/CBL and perforated San Andres @ 4 spf Acidized well w/ 13,500 gal 15% HCl @ 7.5 BPN RIH w/ 3583' 2-3/8" tbg, rods, and 2.0" x 1.5	TOOH for log. from surface to 3995. Cemented : 3510-3558' and 3578-3592' M 5" x 16' pump and hung on
11/3/2007: 11/8/2007: 12/1/2007: 12/7/2007: Spud Date: 10/23/2007 hereby certify that the informat	Drilled 7-7/8" hole from 515' to 4000' (TD). Ran open-hole logs. Ran 5-1/2" 17# J-55 csg w/ 900 sx 65/35 Pozmix. WOC 24 hours. Ran GR/CBL and perforated San Andres @ 4 spf Acidized well w/ 13,500 gal 15% HCl @ 7.5 BPN RIH w/ 3583' 2-3/8" tbg, rods, and 2.0" x 1.5 Rig Release Date: 12/8/07 TITLE Engineer	50 sx C. WOC 8 hours. TOOH for log. from surface to 3995. Cemented : 3510-3558' and 3578-3592' M 5" x 16' pump and hung on
11/3/2007: 11/8/2007: 12/1/2007: 12/7/2007: Spud Date: 10/23/2007 hereby certify that the informate of th	Drilled 7-7/8" hole from 515' to 4000' (TD). Ran open-hole logs. Ran 5-1/2" 17# J-55 csg w/ 900 sx 65/35 Pozmix. WOC 24 hours. Ran GR/CBL and perforated San Andres @ 4 spf Acidized well w/ 13,500 gal 15% HCl @ 7.5 BPN RIH w/ 3583' 2-3/8" tbg, rods, and 2.0" x 1.5 Rig Release Date: 12/8/07 TITLE Engineer	TOOH for log. from surface to 3995. Cemented : 3510-3558' and 3578-3592' M 5" x 16' pump and hung on nd belief. DATE 5/1/09
11/3/2007: 11/8/2007: 12/1/2007: 12/7/2007: Spud Date: 10/23/2007 hereby certify that the informat	Drilled 7-7/8" hole from 515' to 4000' (TD). Ran open-hole logs. Ran 5-1/2" 17# J-55 csg w/ 900 sx 65/35 Pozmix. WOC 24 hours. Ran GR/CBL and perforated San Andres @ 4 spf Acidized well w/ 13,500 gal 15% HCl @ 7.5 BPN RIH w/ 3583' 2-3/8" tbg, rods, and 2.0" x 1.5 Rig Release Date: 12/8/07 TITLE Engineer TITLE Engineer TITLE CEngineer TITLE CEngineer TITLE CEngineer TITLE CEngineer TITLE CEngineer	TOOH for log. from surface to 3995. Cemented : 3510-3558' and 3578-3592' M 5" x 16' pump and hung on
11/3/2007: 11/8/2007: 12/1/2007: 12/7/2007: Spud Date: 10/23/2007 hereby certify that the informat GIGNATURE Colling Type or print name Colling Tor State Use Only	Drilled 7-7/8" hole from 515' to 4000' (TD). Ran open-hole logs. Ran 5-1/2" 17# J-55 csg w/ 900 sx 65/35 Pozmix. WOC 24 hours. Ran GR/CBL and perforated San Andres @ 4 spf Acidized well w/ 13,500 gal 15% HCl @ 7.5 BPN RIH w/ 3583' 2-3/8" tbg, rods, and 2.0" x 1.5 Rig Release Date: 12/8/07 Rig Release Date: 12/8/07 Strawn E-mail address: 28:21 No. 1000 to 4000' (TD). Comented w/ 3 TITLE CEngine 2.00' x 1.5 TITLE CEngine 2.00' x 1.5 ANN 6000 to 4000' (TD).	50 sx C. WOC 8 hours. TOOH for log. from surface to 3995. Cemented : 3510-3558' and 3578-3592' M 5" x 16' pump and hung on nd belief. DATE 5/1/09 PHONE: 817-698-0900
11/3/2007: 11/8/2007: 12/1/2007: 12/7/2007: Spud Date: 10/23/2007 hereby certify that the informate of th	Drilled 7-7/8" hole from 515' to 4000' (TD). Ran open-hole logs. Ran 5-1/2" 17# J-55 csg w/ 900 sx 65/35 Pozmix. WOC 24 hours. Ran GR/CBL and perforated San Andres @ 4 spf Acidized well w/ 13,500 gal 15% HCl @ 7.5 BPN RIH w/ 3583' 2-3/8" tbg, rods, and 2.0" x 1.5 Rig Release Date: 12/8/07 TITLE Engineer TITLE Engineer TITLE CEngineer TITLE CEngineer TITLE CEngineer TITLE CEngineer TITLE CEngineer	50 sx C. WOC 8 hours. TOOH for log. from surface to 3995. Cemented : 3510-3558' and 3578-3592' M 5" x 16' pump and hung on nd belief. DATE 5/1/09 PHONE: 817-698-0900