

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88201

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

RECEIVED

DEC 07 2009

HOBBSOCD

CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.  
30-005-29108

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name  
Mohawk State

8. Well Number 001

9. OGRID Number 155615

10. Pool name or Wildcat  
Wildcat, Morrow

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator  
Nadel and Gussman Permian, LLC

3. Address of Operator  
601 N. Marienfeld, Suite 508, Midland, TX 79701

4. Well Location

Unit Letter P 660 feet from the South line and 660 feet from the East line  
Section 20 Township 8S Range 33E NMPM County Chaves

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
4389'

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

11/11/09: Notified Mark Whitaker of the OCD at 9:00 PM of intent to spud at 10:00 PM and cement surface casing the next morning.

11/12/09: Drilled 17-1/2" hole to 410'. Ran 10 jts of 13-3/8" / 48# / H-40 / STC casing to 410'. Cemented to surface with 166 sx 35:65 Poz and 200 sx Class C cement. Circulated 91 sx to surface.

11/19/09: Drilled 12-1/4" hole to 3755'. Ran 89 jts 9-5/8" / 40# / J-55 / LTC casing to 3775'. Pumped 850 sx 50/50 Poz lead and 200 sx Class C tail. Circulated 162 sx cement to surface.

Spud Date:

Nov. 11, 2009

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Terry West TITLE Engineer DATE 11/20/09

Type or print name Terry West E-mail address: TerryW@NaGuss.com PHONE: 432-682-4429

For State Use Only

APPROVED BY: [Signature] TITLE PETROLEUM ENGINEER DATE DEC 08 2009

Conditions of Approval (if any):