

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources
RECEIVED
OIL CONSERVATION DIVISION
DEC 23 2009 1220 South St. Francis Dr.
Santa Fe, NM 87505
HOBBSOCD

Form C-103
May 27, 2004

WELL API NO. 30-025-20064 ✓	
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> ✓	
6. State Oil & Gas Lease No. B-1732	
7. Lease Name or Unit Agreement Name: W.A. Ramsey NCT C ✓	
8. Well Number 5 ✓	
9. OGRID Number 16696 ✓	
10. Pool name or Wildcat Justis Blinbry ✓	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/> ✓	
2. Name of Operator OXY USA Inc. ✓	
3. Address of Operator P.O. Box 50250 Midland, TX 79710-0250	
4. Well Location Unit Letter <u>D</u> : <u>660</u> feet from the <u>north</u> line and <u>330</u> feet from the <u>west</u> line Section <u>36</u> Township <u>24S</u> Range <u>37E</u> NMPM County <u>Lea</u>	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) <u>3149' GR</u>	
Pit or Below-grade Tank Application <input type="checkbox"/> or Closure <input type="checkbox"/> Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____ Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____	

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

See Attachment

Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 (Subsequent Report of Well Plugging)
which may be found at OCD Web Page under
Forms, www.emnrd.state.nm.us/oed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐ , a general permit ☐ or an (attached) alternative OCD-approved plan ☐

SIGNATURE David Stewart TITLE Sr. Regulatory Analyst DATE 12/21/09

Type or print name David Stewart

E-mail address:

david_stewart@oxy.com

Telephone No. 432-685-5717

For State Use Only

APPROVED BY Carol W. Hill TITLE DISTRICT 1 SUPERVISOR DATE DEC 28 2009

Conditions of Approval, if any:

W.A. RAMSEY NCT C #5

12/7/09 MIRU, DIG OUT CELLAR CHANGE OUT SURFACE VALVE, NDWH, NUBOP
12/8/09 RIH & TAG CIBP @ 5058', CIRC W/ 65 BBLS 10# MLF
12/9/09 PUH TO 4845', SPOT 25SX, CALC TOC @ 4485'
PUH TO 3834' , SPOT 25SX, POOH W/ TBG, RIH W/ PKR TO 2220', WOC.
12/10/09 RU WL, RIH & TAG CMT @ 3355', PUH & PERF @ 2770', RD WL.
EIR @ 2 BPM @ 1400#, SQZ 55SX W/ 2% CACL2, SI @ 400#, WOC 3HRS.
PUH W/ PKR, SET @ 1710'. RIH W. WL, TAG CMT @ 2564', PUH & PERF @ 2510', RDWL
EIR @ 2 BPM @ 1300#, SQZ 100SX W/ 2% CACL2, SI @ 400#, PUH W/ PKR, SET @ 710', WOC.
RIH WL, TAG CMT @ 2155', PUH & PERF @ 1355', RDWL.
12/11/09 EIR @ 2 BPM W/ FULL RETURNS, SQZ 50SX W/ 2% CACL2, PUH W/ PKR TO 670', WOC
RIH WL, TAG CMT @ 1187', PUH & PERF @ 843', RDWL, SQZ 50SX W/ 2% CACL2, PUH W/ PKR,
WOC
12/12/09 RIH W/ TBG & TAG CMT @ 620', POOH & PERF @ 150', ND BOP, NUWH, SQZ 65SX @ 150' TO
SURF, CIRC ON ALL STRINGS, RD, TOP OFF, WELL P&A'd.