

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION

RECEIVED

JUL 29 2009

HOBBS

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Mewbourne Oil Company

3. Address of Operator
PO Box 5270 Hobbs, NM 88240

4. Well Location

Unit Letter O: 760 feet from the South line and 1650 feet from the East line

Section 26 Township 19S Range 35E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3691' GL

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ P AND A ☐

CASING/CEMENT JOB ☐

OTHER: Isolate Bone Springs & Complete San Andres ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

6-26-09 POOH w/ rods & tbg. Set isolation plug @ 10500' w/35' cement (Top Bone Springs perf @ 10538').

Set isolation plug @ 7500' w/35' cement. Shot Circl holes @ 5820' (TOC @ 590')

6-27-09 RIH w/tbg & 5 1/2" cement retainer to 5745'. Cement 5 1/2"x9 5/8" annulus w/450 sks 35/65 'C' w/additives, mixed @ 12.6 #/g & 1.99 yd. Tailed w/500 sks 'C' w/additives, mixed @ 14.8 #/g & 1.33 yd. POOH w/tbg. Calc TOC @ 3400'. New PBTD @ 5710'.

6-30-09 Perf San Andres @ 5260-5268'. 8 ft, 2 SPF, 16 holes. Frac w/500 gals 7 1/2% HCl, 26000 gals 1500 XL w/20000# 20/40 sand & 5000# 16/30 resin sand. Flow back for clean up.

7-03-09 RIH w/tbg & rods. PWOL.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 7/24/09

Type or print name Jackie Lathan

E-mail address:

Telephone No. 505-393-5905

For State Use Only

APPROVED BY: [Signature] TITLE PETROLEUM ENGINEER DATE DEC 30 2009

Conditions of Approval (if any):

ZA Bone Springs