Submit 3 Copies To Appropriate I		
Office	State of New Mexico	Form C-103
District I	Energy, Minerals and Natural Resou	
District II 1301 W. Grand Avg. Antonia NIM	Energy, Minerals and Natural Resources RECEIVED 88210 OILE CONSERVATION DIVISION AND A 20001220 South St. Francis Dr.	WELL API NO. 30-005-28029
District III	38210 GIB GONGBRYATION BY VISION 174 NOV 18 20091220 South St. Francis Dr.	5 Indicate Type of Lease
District IV	Santa re. Nivi 8/303	STATE K FEE 6. State Oil & Gas Lease No.
1220 S. St. Francis Dr , Santa Fe, 1 87505	HOBBSOCD	o. State Oil & Gas Lease No.
SUNDRY	NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR DIFFERENT RESERVOIR. USE	PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	OA /
PROPOSALS.)		CATO SAN ANDRES UNIT
Type of Well: Oil Well Name of Operator	Gas Well Other	8. Well Number 561
CANC	PETRO OF NEW MEXICO, INC.	9. OGRID Number 248802
3. Address of Operator		10 Pool name or Wildcat
801 CHERRY STR, UN	IT 25 SUITE 3200 FT WORTH TX 761	02 CATO; SAN ANDRES
4 Well Location Unit Letter 0	· 115 feet from the S	1240
Section 11	neet from thenme	and 1340 feet from the E line
Section 11	Township 08S Range 11 Elevation (Show whether DR, RKB, RT,	30E NMPM 27 County CHAVES
	4156 A156	ON, etc.)
12. Ch	eck Appropriate Box to Indicate Nature of N	Notice, Report or Other Data
NOTICE (OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WO	RK PLUG AND ABANDON REMEDIA	ALWORK
TEMPORARILY ABANDON PULL OR ALTER CASING	[] Maria Front Control	ICE DRILLING OPNS.☑ P AND A □
DOWNHOLE COMMINGLE	☐ MULTIPLE COMPL ☐ CASING/	CEMENT JOB
· · -		
OTHER:	OTHER: F	perforate, acidize, run tubing, rods and pump X
13. Describe proposed or	completed operations. (Clearly state all pertinent de	tails and give pertinent dates, maladen a action to 1.1.
13. Describe proposed or of starting any propose or recompletion	completed operations. (Clearly state all pertinent de sed work). SEE RULE 1103. For Multiple Completi	tails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion
13. Describe proposed or of starting any proposed	completed operations. (Clearly state all pertinent de sed work). SEE RULE 1103. For Multiple Complete Spudded 12-1/4" hole and drilled to 1250'.	tails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion Ran. 8-5/8" 24# J-55 csg from surface to 1250.
13. Describe proposed or of starting any propose or recompletion	completed operations. (Clearly state all pertinent de sed work). SEE RULE 1103. For Multiple Completi Spudded 12-1/4" hole and drilled to 1250'. Cemented w/ 425 sx class C. Circulated to	tails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion Ran. 8-5/8" 24# J-55 csg from surface to 1250'. surface. WOC on 8/1/2008
13. Describe proposed or of starting any propose or recompletion 7/31/2008:	completed operations. (Clearly state all pertinent de sed work). SEE RULE 1103. For Multiple Completi Spudded 12-1/4" hole and drilled to 1250'. Cemented w/ 425 sx class C. Circulated to Nippled up BOP and drilled 7-7/8" hole from Ran open-hole logs and ran 5-1/2" J-55 csg	tails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion Ran. 8-5/8" 24# J-55 csg from surface to 1250'. surface. WOC on 8/1/2008.
13. Describe proposed or of starting any propose or recompletion 7/31/2008: 8/2 - 8/6/2008: 8/7/2008:	completed operations. (Clearly state all pertinent de sed work). SEE RULE 1103. For Multiple Completi Spudded 12-1/4" hole and drilled to 1250'. Cemented w/ 425 sx class C. Circulated to Nippled up BOP and drilled 7-7/8" hole from Ran open-hole logs and ran 5-1/2" J-55 csg 65/35 Pozmix and WOC 24 hours.	tails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion Ran. 8-5/8" 24# J-55 csg from surface to 1250'. surface. WOC on 8/1/2008. 1 1250' to 4100' (TD). from surface to TD. Cemented w/ 1200 sx
13. Describe proposed or of starting any propose or recompletion 7/31/2008:	completed operations. (Clearly state all pertinent de sed work). SEE RULE 1103. For Multiple Complete Spudded 12-1/4" hole and drilled to 1250'. Cemented w/ 425 sx class C. Circulated to Nippled up BOP and drilled 7-7/8" hole from Ran open-hole logs and ran 5-1/2" J-55 csg 65/35 Pozmix and WOC 24 hours. Ran cased hole logs (GR/CBL). Perforated States and States are sed for the sed of the sed	tails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion Ran. 8-5/8" 24# J-55 csg from surface to 1250'. surface. WOC on 8/1/2008. 1250' to 4100' (TD). from surface to TD. Cemented w/ 1200 sx San Andres @ 1 spf: 3508-3552'. 3584-3588'
13. Describe proposed or of starting any proposed or recompletion 7/31/2008: 8/2 - 8/6/2008: 8/10/2008:	completed operations. (Clearly state all pertinent de sed work). SEE RULE 1103. For Multiple Complete Spudded 12-1/4" hole and drilled to 1250'. Cemented w/ 425 sx class C. Circulated to Nippled up BOP and drilled 7-7/8" hole from Ran open-hole logs and ran 5-1/2" J-55 csg 65/35 Pozmix and WOC 24 hours. Ran cased hole logs (GR/CBL). Perforated S 3603-3607', 3659-3690', 3804-3813', 3885-39 Acidized San Andres w/ 14,000 gal 28% HCl	tails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion Ran. 8-5/8" 24# J-55 csg from surface to 1250'. surface. WOC on 8/1/2008. 1250' to 4100' (TD). from surface to TD. Cemented w/ 1200 sx San Andres @ 1 spf: 3508-3552', 3584-3588', 211', 3931-3960' 8 6 BPM
13. Describe proposed or of starting any propose or recompletion 7/31/2008: 8/2 - 8/6/2008: 8/7/2008:	completed operations. (Clearly state all pertinent de sed work). SEE RULE 1103. For Multiple Complete Spudded 12-1/4" hole and drilled to 1250'. Cemented w/ 425 sx class C. Circulated to Nippled up BOP and drilled 7-7/8" hole from Ran open-hole logs and ran 5-1/2" J-55 csg 65/35 Pozmix and WOC 24 hours. Ran cased hole logs (GR/CBL). Perforated S 3603-3607', 3659-3690', 3804-3813', 3885-39	tails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion Ran. 8-5/8" 24# J-55 csg from surface to 1250'. surface. WOC on 8/1/2008. 1250' to 4100' (TD). from surface to TD. Cemented w/ 1200 sx San Andres @ 1 spf: 3508-3552', 3584-3588', 211', 3931-3960' 8 6 BPM
13. Describe proposed or of starting any proposed or recompletion 7/31/2008: 8/2 - 8/6/2008: 8/10/2008:	completed operations. (Clearly state all pertinent de sed work). SEE RULE 1103. For Multiple Complete Spudded 12-1/4" hole and drilled to 1250'. Cemented w/ 425 sx class C. Circulated to Nippled up BOP and drilled 7-7/8" hole from Ran open-hole logs and ran 5-1/2" J-55 csg 65/35 Pozmix and WOC 24 hours. Ran cased hole logs (GR/CBL). Perforated S 3603-3607', 3659-3690', 3804-3813', 3885-39 Acidized San Andres w/ 14,000 gal 28% HCl	tails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion Ran. 8-5/8" 24# J-55 csg from surface to 1250'. surface. WOC on 8/1/2008. 1250' to 4100' (TD). from surface to TD. Cemented w/ 1200 sx San Andres @ 1 spf: 3508-3552', 3584-3588', 211', 3931-3960' 8 6 BPM
13. Describe proposed or of starting any proposed or recompletion 7/31/2008: 8/2 - 8/6/2008: 8/10/2008:	completed operations. (Clearly state all pertinent de sed work). SEE RULE 1103. For Multiple Complete Spudded 12-1/4" hole and drilled to 1250'. Cemented w/ 425 sx class C. Circulated to Nippled up BOP and drilled 7-7/8" hole from Ran open-hole logs and ran 5-1/2" J-55 csg 65/35 Pozmix and WOC 24 hours. Ran cased hole logs (GR/CBL). Perforated S 3603-3607', 3659-3690', 3804-3813', 3885-39 Acidized San Andres w/ 14,000 gal 28% HCl	tails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion Ran. 8-5/8" 24# J-55 csg from surface to 1250'. surface. WOC on 8/1/2008. 1250' to 4100' (TD). from surface to TD. Cemented w/ 1200 sx San Andres @ 1 spf: 3508-3552', 3584-3588', 211', 3931-3960' 8 6 BPM
13. Describe proposed or of starting any proposed or recompletion 7/31/2008: 8/2 - 8/6/2008: 8/10/2008: 8/11/2008: 8/14/2008:	completed operations. (Clearly state all pertinent desed work). SEE RULE 1103. For Multiple Complete Sed work). SEE RULE 1103. For Multiple Complete Spudded 12-1/4" hole and drilled to 1250'. Cemented w/ 425 sx class C. Circulated to Nippled up BOP and drilled 7-7/8" hole from Ran open-hole logs and ran 5-1/2" J-55 csg 65/35 Pozmix and WOC 24 hours. Ran cased hole logs (GR/CBL). Perforated S 3603-3607', 3659-3690', 3804-3813', 3885-39 Acidized San Andres w/ 14,000 gal 28% HCl (Ran tubing, rods, and 2.5" x 2.0" x 16' ins	tails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion Ran. 8-5/8" 24# J-55 csg from surface to 1250'. surface. WOC on 8/1/2008. 1250' to 4100' (TD). from surface to TD. Cemented w/ 1200 sx San Andres @ 1 spf: 3508-3552', 3584-3588', 211', 3931-3960' 8 6 BPM
13. Describe proposed or of starting any proposed or recompletion 7/31/2008: 8/2 - 8/6/2008: 8/10/2008:	completed operations. (Clearly state all pertinent desed work). SEE RULE 1103. For Multiple Complete Spudded 12-1/4" hole and drilled to 1250'. Cemented w/ 425 sx class C. Circulated to Nippled up BOP and drilled 7-7/8" hole from Ran open-hole logs and ran 5-1/2" J-55 csg 65/35 Pozmix and WOC 24 hours. Ran cased hole logs (GR/CBL). Perforated S 3603-3607', 3659-3690', 3804-3813', 3885-39 Acidized San Andres w/ 14,000 gal 28% HCl & Ran tubing, rods, and 2.5" x 2.0" x 16' ins	tails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion Ran. 8-5/8" 24# J-55 csg from surface to 1250'. surface. WOC on 8/1/2008. 1250' to 4100' (TD). from surface to TD. Cemented w/ 1200 sx San Andres @ 1 spf: 3508-3552', 3584-3588', 211', 3931-3960' 6 BPM Sert pump, and hung on
13. Describe proposed or of starting any proposed or recompletion 7/31/2008: 8/2 - 8/6/2008: 8/7/2008: 8/10/2008: 8/11/2008: 8/14/2008:	completed operations. (Clearly state all pertinent desed work). SEE RULE 1103. For Multiple Complete Spudded 12-1/4" hole and drilled to 1250'. Cemented w/ 425 sx class C. Circulated to Nippled up BOP and drilled 7-7/8" hole from Ran open-hole logs and ran 5-1/2" J-55 csg 65/35 Pozmix and WOC 24 hours. Ran cased hole logs (GR/CBL). Perforated S 3603-3607', 3659-3690', 3804-3813', 3885-39 Acidized San Andres w/ 14,000 gal 28% HCl & Ran tubing, rods, and 2.5" x 2.0" x 16' ins	tails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion Ran. 8-5/8" 24# J-55 csg from surface to 1250'. surface. WOC on 8/1/2008. 1250' to 4100' (TD). from surface to TD. Cemented w/ 1200 sx San Andres @ 1 spf: 3508-3552', 3584-3588', 211', 3931-3960' 8 6 BPM
13. Describe proposed or of starting any proposed or recompletion 7/31/2008: 8/2 - 8/6/2008: 8/10/2008: 8/10/2008: 8/11/2008: 8/14/2008: Spud Date 7/31/2008	completed operations. (Clearly state all pertinent desed work). SEE RULE 1103. For Multiple Complete Spudded 12-1/4" hole and drilled to 1250'. Cemented w/ 425 sx class C. Circulated to Nippled up BOP and drilled 7-7/8" hole from Ran open-hole logs and ran 5-1/2" J-55 csg 65/35 Pozmix and WOC 24 hours. Ran cased hole logs (GR/CBL). Perforated 8 3603-3607', 3659-3690', 3804-3813', 3885-39 Acidized San Andres w/ 14,000 gal 28% HCl 6 Ran tubing, rods, and 2.5" x 2.0" x 16' ins	tails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion Ran. 8-5/8" 24# J-55 csg from surface to 1250'. surface. WOC on 8/1/2008. 1250' to 4100' (TD). from surface to TD. Cemented w/ 1200 sx San Andres @ 1 spf: 3508-3552', 3584-3588', 211', 3931-3960' 6 BPM Sert pump, and hung on
13. Describe proposed or of starting any proposed or recompletion 7/31/2008: 8/2 - 8/6/2008: 8/10/2008: 8/10/2008: 8/11/2008: 8/14/2008: Spud Date 7/31/2008	completed operations. (Clearly state all pertinent desed work). SEE RULE 1103. For Multiple Complete Spudded 12-1/4" hole and drilled to 1250'. Cemented w/ 425 sx class C. Circulated to Nippled up BOP and drilled 7-7/8" hole from Ran open-hole logs and ran 5-1/2" J-55 csg 65/35 Pozmix and WOC 24 hours. Ran cased hole logs (GR/CBL). Perforated S 3603-3607', 3659-3690', 3804-3813', 3885-39 Acidized San Andres w/ 14,000 gal 28% HCl & Ran tubing, rods, and 2.5" x 2.0" x 16' ins	tails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion Ran. 8-5/8" 24# J-55 csg from surface to 1250'. surface. WOC on 8/1/2008. 1250' to 4100' (TD). from surface to TD. Cemented w/ 1200 sx San Andres @ 1 spf: 3508-3552', 3584-3588', 211', 3931-3960' 6 BPM Sert pump, and hung on
13. Describe proposed or of starting any proposed or recompletion 7/31/2008: 8/2 - 8/6/2008: 8/7/2008: 8/10/2008: 8/11/2008: 8/14/2008: Spud Date 7/31/2008	completed operations. (Clearly state all pertinent desed work). SEE RULE 1103. For Multiple Complete Seed work). SEE RULE 1103. For Multiple Complete Spudded 12-1/4" hole and drilled to 1250'. Cemented w/ 425 sx class C. Circulated to Nippled up BOP and drilled 7-7/8" hole from Ran open-hole logs and ran 5-1/2" J-55 csg 65/35 Pozmix and WOC 24 hours. Ran cased hole logs (GR/CBL). Perforated 93603-3607', 3659-3690', 3804-3813', 3885-394. Acidized San Andres w/ 14,000 gal 28% HCl 68 Ran tubing, rods, and 2.5" x 2.0" x 16' insertion above is true and complete to the best of my knowledge.	tails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion Ran. 8-5/8" 24# J-55 csg from surface to 1250'. surface. WOC on 8/1/2008. 1250' to 4100' (TD). from surface to TD. Cemented w/ 1200 sx San Andres @ 1 spf: 3508-3552', 3584-3588', 211', 3931-3960' 6 BPM Sert pump, and hung on
13. Describe proposed or of starting any proposed or recompletion 7/31/2008: 8/2 - 8/6/2008: 8/7/2008: 8/10/2008: 8/11/2008: 8/14/2008: Spud Date 7/31/2008 I hereby certify that the information of the	completed operations. (Clearly state all pertinent desed work). SEE RULE 1103. For Multiple Complete Sed work). SEE RULE 1103. For Multiple Complete Spudded 12-1/4" hole and drilled to 1250'. Cemented w/ 425 sx class C. Circulated to Nippled up BOP and drilled 7-7/8" hole from Ran open-hole logs and ran 5-1/2" J-55 csg 65/35 Pozmix and WOC 24 hours. Ran cased hole logs (GR/CBL). Perforated S 3603-3607', 3659-3690', 3804-3813', 3885-39. Acidized San Andres w/ 14,000 gal 28% HCl & Ran tubing, rods, and 2.5" x 2.0" x 16' insertion above is true and complete to the best of my knowledge. Rig Release Date: TITLE Engineer	tails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion Ran. 8-5/8" 24# J-55 csg from surface to 1250'. surface. WOC on 8/1/2008. 1250' to 4100' (TD). from surface to TD. Cemented w/ 1200 sx San Andres @ 1 spf: 3508-3552', 3584-3588', 211', 3931-3960' 6 BPM Sert pump, and hung on
13. Describe proposed or of starting any proposed or recompletion 7/31/2008: 8/2 - 8/6/2008: 8/7/2008: 8/10/2008: 8/11/2008: 8/14/2008: Spud Date 7/31/2008 I hereby certify that the information of the starting any proposed or recompletion 7/31/2008: Spud Date 7/31/2008 Type or print name Colling	completed operations. (Clearly state all pertinent desed work). SEE RULE 1103. For Multiple Complete Sed work). SEE RULE 1103. For Multiple Complete Spudded 12-1/4" hole and drilled to 1250'. Cemented w/ 425 sx class C. Circulated to Nippled up BOP and drilled 7-7/8" hole from Ran open-hole logs and ran 5-1/2" J-55 csg 65/35 Pozmix and WOC 24 hours. Ran cased hole logs (GR/CBL). Perforated S 3603-3607', 3659-3690', 3804-3813', 3885-39. Acidized San Andres w/ 14,000 gal 28% HCl & Ran tubing, rods, and 2.5" x 2.0" x 16' insertion above is true and complete to the best of my knowledge. Rig Release Date: TITLE Engineer	tails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion Ran. 8-5/8" 24# J-55 csg from surface to 1250'. surface. WOC on 8/1/2008. 1250' to 4100' (TD). from surface to TD. Cemented w/ 1200 sx San Andres @ 1 spf: 3508-3552', 3584-3588', 211', 3931-3960' 6 BPM Sert pump, and hung on
13. Describe proposed or of starting any proposed or recompletion 7/31/2008: 8/2 - 8/6/2008: 8/7/2008: 8/10/2008: 8/11/2008: 8/14/2008: Spud Date 7/31/2008 I hereby certify that the information of the state Use Only	completed operations. (Clearly state all pertinent de sed work). SEE RULE 1103. For Multiple Complete Spudded 12-1/4" hole and drilled to 1250'. Cemented w/ 425 sx class C. Circulated to Nippled up BOP and drilled 7-7/8" hole from Ran open-hole logs and ran 5-1/2" J-55 csg 65/35 Pozmix and WOC 24 hours. Ran cased hole logs (GR/CBL). Perforated 8 3603-3607', 3659-3690', 3804-3813', 3885-39 Acidized San Andres w/ 14,000 gal 28% HCl 6 Ran tubing, rods, and 2.5" x 2.0" x 16' ins	tails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion Ran. 8-5/8" 24# J-55 csg from surface to 1250'. surface. WOC on 8/1/2008. 1250' to 4100' (TD). from surface to TD. Cemented w/ 1200 sx San Andres @ 1 spf: 3508-3552', 3584-3588', 211', 3931-3960' 6 BPM Sert pump, and hung on DATE 4-14-09
13. Describe proposed or of starting any proposed or recompletion 7/31/2008: 8/2 - 8/6/2008: 8/7/2008: 8/10/2008: 8/11/2008: 8/14/2008: Spud Date 7/31/2008 I hereby certify that the information of the starting any proposed or recompletion 7/31/2008: Spud Date 7/31/2008 Type or print name Colling	completed operations. (Clearly state all pertinent desed work). SEE RULE 1103. For Multiple Complete Seed work). SEE RULE 1103. For Multiple Complete Spudded 12-1/4" hole and drilled to 1250'. Cemented w/ 425 sx class C. Circulated to Nippled up BOP and drilled 7-7/8" hole from Ran open-hole logs and ran 5-1/2" J-55 csg 65/35 Pozmix and WOC 24 hours. Ran cased hole logs (GR/CBL). Perforated S 3603-3607', 3659-3690', 3804-3813', 3885-39 Acidized San Andres w/ 14,000 gal 28% HCl & Ran tubing, rods, and 2.5" x 2.0" x 16' insection above is true and complete to the best of my known and Strawn Figure Engineer Strawn E-mail address:	tails, and give pertinent dates, including estimated date ons: Attach wellbore diagram of proposed completion Ran. 8-5/8" 24# J-55 csg from surface to 1250'. surface. WOC on 8/1/2008. 1250' to 4100' (TD). from surface to TD. Cemented w/ 1200 sx San Andres @ 1 spf: 3508-3552', 3584-3588', 211', 3931-3960' 6 BPM Sert pump, and hung on DATE 4-14-09