#### UNITED STATES GCD Hobbi RECEIVED DEPARTMENT OF THE INTERIOR FORM APPROVER OMB No 1004-0137 Expires: March 31, 2007 BUREAU OF LAND MANAGEMENT JAN 05 200 UNDRY NOTICES AND REPORTS ON WELLS 5. Lease Serial No. LC 030467B HOBBSONDUSE this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals. If Indian, Allottee or Tribe Name SUBMIT IN TRIPLICATE- Other instructions on reverse side. 7 If Unit or CA/Agreement, Name and/or No 1. Type of Well Gas Well Other 8. Well Name and No. 2. Name of Operator ConocoPhillips Company ATTN: Donna Williams Vaughan B-1 #5 API Well No. 3a. Address 3b. Phone No (include area code) 30-025-21656 P.O. Box 51810 Midland, Texas 79710-1810 432-688-6884 10 Field and Pool, or Exploratory Area 4 Location of Well (Footage, Sec., T., R., M., or Survey Description) Jalmat Yates Gas Unit D, 660' FNL & 660' FWL, Section 1, T-24-S, R-36-E 11 County or Parish, State Lea, New Mexico 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Acidize Deepen ✓ Notice of Intent Production (Start/Resume) Water Shut-Off Alter Casing Fracture Treat Reclamation Well Integrity Casing Repair Subsequent Report New Construction Recomplete Change Plans Plug and Abandon Final Abandonment Notice Temporarily Abandon Convert to Injection Plug Back Water Disposal Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markets and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) Set 4 1/2" CIBP @ 2818' Cap w/25sxs cmt Perf @ 1345' Sqz 40sxs cmt 1345'-1245' WOC tag Perf @ 364' Pump 85sxs cmt from 364' to surface ou of 7 5/8" casing Install Dry Hole Marker SEE ATTACHED FOR CONDITIONS OF APPROVAL DEDEC 3 0 2009 /s/ iviyies Kristof 14. I hereby certify that the foregoing is true and correct Name (Printed/Typed) Larry Winn Title Area Manager, P&A Basic Energy Services Signature Date 11/23/2009 THIS SPACE FOR FEDERAL OR STATE OFFICE USE Conditions of approval, if any, are attached. Approval of this notice does not warrant or Title Date certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Office Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

## WELLBORE SKETCH ConocoPhillips Company -- Lower 48 - Mid-Continent BU / Permian Operations

RKB@ DF@ 3355 GĻ@

Date November 9, 2009

Lease & Well No · Vaughan B-1 No. 5 Legal Description 660' FNL & 660' FWL, Sec 1, T24S, R36E, UL "D" County · Lea State . Field Jalmat Yates Gas Date Spudded: 11/9/65 Rig Released 11/19/65 API Number 30-025-21656 Status Serial Lse No. LC030467B CA Agreement No. 071030467B

Stimulation History:

		' '		, `-	
Interval	<u>Date</u>	<u>Type</u> <u>Gals</u>	Lbs. Max Sand Pres		Down
	11/21/65	Perforate 3492, 3512, 3535, 3547,	3556 3575 3583	, , , , ,	
, ,		3591, 3602, and 3651 w/ 2 JSPF	,,,,,	<b>'</b> '	٠.
3492-3651	11/21/65	15% LSTNE 1.000	16 BS 1800		
3492-3651	11/23/65	Crude 40.000		1200 3.0	
2 2		40,000	60,000		
•			<ul> <li>2,000# Adomi</li> </ul>	te	
	9/9/96	Set 4 4/2" CIRD @ 04001	2800	600 37.4	
		Set 4-1/2" CIBP @ 3460'; spot cem	ent on CIBP		
	9/11/96	Perforate Jalmat w/ 1 JSPF 2918-3	296		
2918-3296	9/12/96	70 Quality CO2 Pad 182 bbls			
		60-55 Quality CO2 Foam 521 bbis	252,2440		٠
`, `	9/26/96	Test: 0 BO, 142 Mcf, 1 BW	252,2440		
	4/3/97	Tag fill @ 3437', clean out, circulate, r	ran in holo w/n		
	-	SN @ 3378'	an at note w/pum	ib aud tods	

SN @ 3378'

Top Salt @ 1295

.-11", Hole

7-5/8" 24# H-40 @ 314'

Cmt'd w/ 200 sx, circ

TOC @ Surface

TOC 4-1/2" Csg @ 2200' (T.S.)

. Base Salt @ 2760'

== ==

== ==

==

PBTD:

3425' TD: 3700'

==

==

<u>Jalm</u>		,				
2918	2926	2932	2938	2944	2948	
2956	2966	2966	2969	2974	2978	2982
3002	3004	3008	3012	3016	3026	3036
3052	3054	3059	3068	3082	3087	3092
3102	3120	3124	3133	3186		
3244				•		
3305						
3372	3386	3393	3396			

4-1/2" CIBP @ 3460' w/cmt on top Queen 3492 3512 3535 3547 3556 3575 3583 3591 3602 3651

6-3/4" Hole 4-1/2" 9.5# J-55 @ 3700' Cmt'd w/ 200 sx Class "C" TOC @ 2200' (T.S )

Formation Tops: Rustler 1195' Top Salt 1295' Base Salt 2760' Yates 2915 Seven Rivers 3140' Queen Marker 35281

# WELLBORE SKETCH ConocoPhillips Company -- Lower 48 - Mid-Continent BU / Permian Operations

RKB @ 3356' DF @ 3355' GL @ 3347'

Date November 9, 2009

			*		
Lease & Well No	Vaughan B-1	No. 5			
Legal Description	660' FNL & 660' FWL, Sec. 1, T24S, R36E, UL "D"				
County	Lea	State New M			
Field .	Jalmat Yates Gas	,			
Date Spudded .	11/9/65	Rig Released. 11/1	9/65		
API Number .	30-025-21656				
Status		Serial Lse No.	LC030467B		
4 8 9 9		CA Agreement No.	.071030467B		

7-5/8" 24# H-40 @ 314'
Cmt'd w/ 200 sx, circ
TOC @ Surface
Perf @ 364' Pump 85sxxs cmt from 364' to surface

Top Salt @ 1295'
Perf @ 1345' Sqz 40sxs cmt 1345'-1245' WOC tag

Stimulation History: Max Max Interval Date Type -. Gals <u>Sand</u> <u>Press</u> ISIP Rate Down 11/21/65 Perforate 3492, 3512, 3535, 3547, 3556, 3575, 3583 3591, 3602, and 3651 w/ 2 JSPF 3492-3651 11/21/65 15% LSTNE 1,000 16 BS 1800 120030 3492-3651 11/23/65 Crude 40,000 60.000 2,000# Adomite 2800 600 37.4 9/9/96 Set 4-1/2" CIBP @ 3460'; spot cement on CIBP 9/11/96 Perforate Jalmat w/ 1 JSPF 2918-3296 2918-3296 9/12/96 70 Quality CO2 Pad 182 bbls 60-55 Quality CO2 Foam 521 bbls 252,2440 Test: 0 BO, 142 Mcf, 1 BW
Tag fill @ 3437', clean out, circulate, ran in hole w/pump and rods 9/26/96 4/3/97 SN @ 3378'

TOC 4-1/2" Csg @ 2200' (T.S.)

Base Salt @ 2760'

CIPB @ 2818' w/25sxs cmt 2818'-2456'

Jalmat

2918 2926 2932 2938 2944 2948

2956 2966 2966 2969 2974 2978 2982

3002 3004 3008 3012 3016 3026 3036

3052 3054 3059 3068 3082 3087 3092

3102 3120 3124 3133 3186

3244

3305 3316 3327 3345

3372 3386 3393 3396

4-1/2" CIBP @ 3460' w/cmt on top Queen 3492 3512 3535 3547 3556 3575 3583 3591 3602 3651

6-3/4" Hole 4-1/2" 9.5# J-55 @ 3700' Cmt'd w/ 200 sx Class "C" TOC @ 2200' (T.S.)

PBTD: 3425

TD: 3700'

## Vaughan B-1 #5 30-025-21656 ConocoPhillips Company December 30, 2009 Conditions of Approval

Operator to have H2S monitoring equipment on location as H2S has been reported.

- 1. OK Perfs & Base of Salt
- 2. Set Plug from 1,245'-1,125' and tag no shallower than 1,125' Top of Salt
- 3. OK Surface
- 4. OK
- 5. See attached general plugging COA and reclamation procedures.

MAK 123009

#### **BUREAU OF LAND MANAGEMENT**

Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

### Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. In lieu of a cement plug in a cased hole, a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Any plug that requires a tag will have a minimum WOC time of 4 hours.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

- 6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). **The BLM is to be notified when the wellhead is cut off to verify that cement is to surface in the casing and all annuluses.** The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement. The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).
- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation procedure.

DHW 112309



# **United States Department of the Interior**

#### **BUREAU OF LAND MANAGEMENT**

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To 1310

#### **Reclamation Objectives and Procedures**

**Reclamation Objective:** Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- 1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Environmental Protection Specialist 575-234-5909, 575-361-2648 (Cell)

Terry Gregston Environmental Protection Specialist 575-234-5958

Bobby Ballard Environmental Protection Specialist 575-234-2230

Randy Rust Environmental Protection Specialist 575-234-5943

Linda Denniston Environmental Protection Specialist 575-234-5974

Jennifer Van Curen Environmental Protection Specialist 575-234-5905

Justin Frye Environmental Protection Specialist 575-234-5922 Cody Layton Natural Resource Specialist 575-234-5959

Trishia Bad Bear Natural Resource Specialist 575-393-3612

Todd Suter Surface Protection Specialist 575-234-5987

Doug Hoag Civil Engineering Technician 575-234-5979