Form 3160-5 (August 1999)	DEPART BUREAU	JNITED STATES MENT OF THE INTERIOR OF LAND MANAGEMENT <b>SES AND REPORTS ON W</b>	RECEIVE	30	OMB N	M APROVED IO. 1004-0135 OVEMBER 30, 20	00	_	
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals SUBMIT IN TRIPLICATE					NMNM-68084 6. If Indian, Allottee or Tribe Name				
	SUE	MIT IN TRIPLICATE	- ACAPONCT	)					
1a. Type of Well	Oil Well Gas	Well Other -			7. Unit or CA Agreem	ent Name and No.			
				<u>, , , , , , , , , , , , , , , , , , , </u>	8 Well Name and No.		(		
2. Name of Opera DEVO	tor N ENERGY PRODUCTION	Mesa Verde 7 Federal 3H 4							
3. Address and Te		···· · · · · · · · · · · · · · · · · ·			30-	025-39444			
20 No	rth Broadway, Oklahon	10. Field and Pool, or Exploratory							
<ol> <li>Location of Well (Report location clearly and in accordance with Federal requirements)*</li> <li>330 FSL &amp; 1980 FWL, Section 7, T24S R32E Unit N</li> </ol>					Mesa Verde Delaware 12. County or Parish 13. State				
BH		WL, Section 7, T24S R32			Lea	NM			
TYPE OS	CHECK AI	PROPRIATE BOX(s) TO I	NDICATE NATURE OF NOT TYPE	ICE, REPORT	, OR OTHER DATA				
Notice of Ir	Notice of Intent       Acidize       Deepen       Producti         Alter Casing       Fracture Treat       Reclama         Subsequent Report       Casing Repair       New Construction       Recomption					Water Shut-Off Well Integrity Other Drilling	F		
🗌 Final Aband	Ionment Notice	Change Plans	Plug and Abandon	U Temporar	rily Abandon	Operatio	ons		
he Bond No on file with nterval, a Form 3160-4 s Jetermined that the site is 11/20/09 Notified 11/21/09 MIRU. 11/22/09 Spud with 11/23/2009 TD 17 11/24/09 RU and water, 6.35 gal/sx 11/29/2009 TD 11 joints of 24# 8 5/8 sacks 60:40 Poz 0 12/3/09 TD 7 7/8" 12/5/09 MIRU. Ris 12/6/09 Cement f	BLM/BIA Required subsequer shall be filed once testing has be s ready for final inspection) Marland with the BLM ell. 1/2" hole at 915'. Circ cement with 650 sacks . Circulate 369 sacks fi ' Intermediate hole @ 4 '', J-55, ST&C/LT&C an Class C; 13.8 yield, 1.3 hole at 8797'. an in with 5 1/2" casing irst stage with 300 sac ith 150 sacks Poz Clas	t reports shall be filed within 30 days en completed Final Abandonment of intent to spud. ulate hole clean. Ran in v Class C mixed at 13.5 yie o catch pit. Witnessed by 500'. Notified Andy Corte d set at 4500'. Cement wi 7 water, and 6.43 gal/sx. C ; 43 joints of 17# and 158 ks Modified Super C; 13.3	rue vertical depths of all pertinent mar following completion of the involved o Notices shall be filed only after all requ vith 22 jts of 13 3/8", 48#, H- ild, 1.75 water, and 9.17 gall v Pat McKelvy with the BLM v Pat McKelvy with the BLM ez with BLM of intent to run th 1045 sacks 35:65:6 Poz 0 Circulate 200 sacks to catch joints of 17#, J-55 LT&C an ppg, 1.56 cf/sx. Cement se Calculated top of cement at	-40 ST&C cas /sx; tail with 3 . WOC 33.5 f 8 5/8 interme Class C; 12.5 a pit. d set at 8, 79 econd stage w	ing and set at 915'. 800 sacks Class C mi hours. diate casing. Run wi yield, 2.04 water, 11.2	xed at 14.8 yield, xed at 14.8 yield, th 56 joints of 32 24 gal/sx; tail with	1.35 # and 4 300	4	
	that the foregoing is tri deral or State Office use	Narr Title	Sr. Staff Engineering PETROLEUM ENGIN	Technician	ACCEPTED Date JAN	FOR RECC 12/21/2009 1 9 2010 1ris Walls	JAN	2 2 2010	
				KZ	BUREAU OF LA	ND MANAGEMEI		ແຮເໜີເດເດ	
its jurisdiction	oon, makes it a crime for any pe		any department Or agency of the Onite	States any dise	CARLSBAL	94410215 94410215			

*See Instructio	n on Reverse Si	de

- -

~