

## District I

1625 N. French Dr., Hobbs, NM 88240

## District II

1301 W. Grand Ave., Artesia, NM 88210

## District III

1000 Rio Brazos Rd., Aztec, NM 87001

## District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

**RECEIVED**  
FEB 08 2010  
HOBBS

## CONSERVATION DIVISION

1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. ✓

30-025-01301

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil &amp; Gas Lease No.

7. Lease Name or Unit Agreement Name  
MALMAR UNIT

8. Well Number 414 ✓

9. OGRID Number

266091 ✓

10. Pool name or Wildcat

MALJAMAR ; Grayburg, SA ✓

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other Inj ✓

2. Name of Operator ✓

VPR Operating, LLC

3. Address of Operator

PO Box 2769, Hobbs, New Mexico 88241

4. Well Location

Unit Letter N : 660 feet from the SOUTH line and 1980 feet from theEAST West lineSection 7 Township 17S Range 33E NMPM LEA County ✓

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

## 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐DOWNHOLE COMMINGLE ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ P AND A ☒CASING/CEMENT JOB ☐OTHER: ☐OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

VPR Operating LLC did plug and abandon the Malmar 414 with the following procedure, verbally approved by Paul Kautz, on 1.29.10:

A) Set CIBP @ 4,075, with 35' of cement on top.

B) Set 100 sack Class C plug @ 2,550'.

C) Perforated 5-1/2" casing @ 1,250' ✓

D) Squeezed perforations @ 1,250' with 100 sacks Class C. ✓

E) WOC. Tagged top of squeeze cement @ 1,228' ✓

E) Perforated 5-1/2" casing @ 350'.

F) Squeezed perforations @ 350' with 100 sacks Class C.

G) Set 60 sack Class C surface plug..

H) Cut off wellhead.

I) Installed NMOCD approved dry hole marker.

J) Cleaned and leveled location.

Approved for plugging of well bore only.  
Liability under bond is retained pending receipt  
of C-103 (Subsequent Report of Well Plugging)  
which may be found at OGD Web Page under  
Forms, [www.emnrd.state.nm.us/odg](http://www.emnrd.state.nm.us/odg).

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Mymerch

Agent

TITLE

DATE

2/1/10

M.Y Merchant

mymerch@penrocoil.com

575-492-1236

Type or print name

E-mail address:

PHONE:

For State Use Only

APPROVED

BY:

TITLE

DATE

2-9-10

Conditions