		OPER. C	GRID NO	17	891				ivision, District	
1.2		PROPER	TY NO.	043	41			French Dr	-, -	
Form 3160-3 (July 1992)		POOL C	Ø	27-	20			MEDRINA COMB NO. 10		
(,	DEPAR		•	5-	1011			Expires: Februar	ry 28, 1995	
	BURE	EFF. DA	TE 12	21	104			SE DESIGNATION AN	ID SERIAL NO.	
		API NO.	30-0	25	36549			-86149 IDIAN, ALLOTTEE OF		
······	CATION F									
b. TYPE OF WELL	DRILL 🕅		DEEPEN				7	. UNIT AGREEMENT NAM	E	
	GAS WELL	OTHER					8	Red Tank 26		
Pogo Produci							9	API WELL NO.	21-1.0	
3. ADDRESS AND TELEPH P. O. Box 10.		nd, TX	79702-734	0	432-685-8100)	1	30-025 0. FIELD AND POOL, OR V	WILDCAT	
4. LOCATION OF WELL (Re					20 D22F			Red Tank Mor		
At proposed prod. zon	_	U' FWL,	Section 2	0,12	25, K32E		1	1. SEC., T., R., M., OR BLI AND SURVEY OR AREA		
A proposed prod. Zon	Same		lait (<u>_</u>				Section 26,	T225, R32E	
14. DISTANCE IN MILES AN	ND DIRECTION FROM	NEARESTTO	WN OR POST OFFICE	E'	,		1	2. COUNTY OR PARISH	13. STATE	
<u>Approximatel</u>		East o	f Carlsbad			1		Lea County	NM	
15. DISTANCE FROM PRO LOCATION TO NEARES PROPERTY OR LEASE (Also to nearest drig. unit	T	660	, i	16. NO.	OF ACRES IN LEASE		10. OF AC O THIS W	RES ASSIGNED ELL 320)	
18. DISTANCE FROM PRO TO NEAREST WELL, DR OR APPLIED FOR, ON 1	POSED LOCATION" RILLING, COM PLETE	^{».} 330	1		,400	20. R	-	or cable tools Rotary		
21. ELEVATIONS (Show wh	ether DF, RT, GR, etc	:.)			a ma banto a6			22. APPROX. DATE WOR		
3704' GR		<u> </u>	Carts	bod Ce	artrelled Weter N	265617		When approv	ed	
23.			PROPOSED CA	SING AN	CEMENTING PROGR	RAM				
SIZE OF HOLE	GRADE, SIZE	OF CASING	WEIGHT PER F	• 0 0T	SETTING DEPTH			QUANTILY OF CEME	דא	
25"	Conducto		NA		40'	<u> </u>			ledi-mix	
17-1/2"		3-3/8"	54.5	.	1000'		00/ \$			
<u>12-1/4"</u> 8-1/2"	N-80 S-95, P-	9-5/8"	40.5 29		4700'			Sks-circ cmt to surface		
6-1/8"	S-95	5"	18		15,400-12,20		IN	top of chit 1	2,200'	
		CO011	1		and the De diamin	·	19	HODDS	ī)	
1. Drill 25" hol 2. Drill 17-1/2" Circulate cm	hole to 1000'.	Run & set 10°	000' of 13-3/8" 5	54.5# J-5	ace with Redi-mix. 5 ST&C csg. Cmt w	// 1000 sk		$\operatorname{cmt}^{*} + 2\% \operatorname{CaCl}^{+} + \frac{1}{2}$	/4# Flocele/sk.	
		Run & set 4	700' of 9-5/8" 40).5# N-8	0 ST&C csg. Cmt w	/ 1800 sk	s Cl "C'	Char + 2% CaCl + 1/	4# Flocele/sk.	
Circulate cm 4. Drill 8-1/2" 1 7000'+ & cm	nole to 12,400'.	Run & set 1	2,400' 7" csg as additives. Est T	follows:	4400' S-95 29# LT	&C, 8000)' P-110) 29# LT&C csg. Se	et stage tool @	
5. Drill 6-1/8" l		Run & set 3			om TD to 12,200'.	Cmt w/ 40	00 sks C	cl "H" low water loss	; cmt +	
	-				APPRO	WAL S	SUBJ	ect to		
					GENE	RAL R	EQUI	REMENTS M	40)	
					SPECI.	AL ST	IPŪL	ATIONS		
IN ABOVE SPACE DES deepen directionally, giv	CRIBE PROGRAM	f: If proposal i subsurface k	s to deepen, give d	lata on pre ured and t	ATTA esent productive zone ar rue vertical depths. Give		d new pr	oductive zone. If propos	al is to drill or	
24.								Program, a 2007		
	thy U	righ	<u>t_</u>	ITLE	r. Operation	Tech		DATE12/1	.6/03	
(This space for Feder	ral or State office u	se)							· /	
PERMIT NO.					APPROVAL DATE				/	
Application approval doe CONDITIONS OF APPR	es not warrant or certify IOVAL, IF A NY:	/ that the applica	int holds legal or equit	able title to t	hose rights in the subject lea	ase which wo	uld entitle	the applicant to conduct ope	arations the real	
				,5,00						
APPROVED BY	/S/ JO	EG.L		FIE	LD MANAG			JAN 2		
T W- 4044 0 0 0	-11		*See Instruc	tion s O	n Reverse Side	MEE		AL FUR I		

2

•

.

:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

D'STRICT I P.O. Bez 1980, Hobbs, NM 66241-1960

DISTRICT II P.O. Drawer BD, Artonia, NM 85211-0719

DISTRICT III 1000 Rio Brasos Ed., Astoc, NM 87410

DISTRICT IV

P.O. BOX 2065, SANTA FR. N.M. 87604-2086

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number Pool Name Pool Code 0-025.36549 83730 RED TANK MORROW EAST Well Number Property Name **Property** Code 9341 **RED TANK 26 FEDERAL** - 13 OGRID No. **Operator** Name ELEVATION 3704' POGO PRODUCING COMPANY 17891

Surface Location

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
С	26	22–S	32-E		660	NORTH	1980	WEST	LEA

Bottom Hole Location If Different From Surface

UL or lot No. Section Township Range Lot Idn	Feet from the North/South line	Feet from the	East/West line	County
Dedicated Acres Joint or Infill Consolidation Code Ord	er No.	· · · · · · · · · · · · · · · · · · ·	·	
320				

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

3700.6'	GEODETIC COORDINATES SPC NME NAD 1927 Y = 498296.5 X = 711877.4 LAT. 32'22'05.03"N LONG. 10.3'38'49.55"W	OPERATOR CERTIFICATION I hereby certify the the information contained herein is true and complete to the best of my knowledge and belief.
		NOVEMBER 06, 2001 Date Surveyor Professional Surveyor OI. 11.1204 Cortificate No. RONGEN JEIDSON 3239 GART, EDBON 18641

State of New Mexico

Form C-102 Revised February 10, 1994 Submit to Appropriate District Office State Lease - 4 Copies Fee Lease - 3 Copies

C AMENDED REPORT

Energy, Minerals and Natural Resources Department OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

VICINITY MAP



SCALE: 1'' = 2 MILES

SEC. <u>26</u> TWP.<u>22–S</u> RGE.<u>32–E</u> SURVEY <u>N.M.P.M.</u> COUNTY <u>LEA</u> DESCRIPTION <u>660' FNL & 1980' FWL</u> ELEVATION <u>3704.4'</u> OPERATOR <u>POGO PRODUCING COMPANY</u> LEASE <u>RED TANK 26 FED. #13</u>

1

JOHN WEST SURVEYING HOBBS, NEW MEXICO (505) 393-3117

LOCATION VERIFICATION MAP



U.S.G.S. TOPOGRAPHIC MAP BOOTLEG RIDGE, N.M.

APPLICATION TO DRILL

POGO PRODUCING COMPANY RED TANK "26" FEDERAL # 13 UNIT "C" SECTION 26 T22S-R32E LEA CO. NM

In response to questions asked under Section II of Bulletin NTL-6 the following information on the above well is provided for your consideration.

- 1. Location: 660' FNL & 1980' FWL SEC. 26 T22S-R32E LEA CO. NM
- 2. Elevation above Sea Level: 3704' GR.
- 3. Geologic name of surface formation: Quaternery Aeolian Deposits.
- 4. <u>Drilling tools and associated equipment:</u> Conventional rotary drilling rig using drilling mud as a circulating medium for solids removal from hole.
- 5. Proposed drilling depth: 15,400'
- 6. Estimated tops of geological markers:

Rustler Anhydrite	900	Bone Spring	8665	Atoka 13590'
Delaware	4815 '	Wolfcamp	12090'	Morrow 14242'
Cherry Canyon	5976;	Strawn	12850'	Lower Morrow 15263'

7. Possible mineral bearing formations:

Delaware	Oil	Wolfcamp	Gas	Atoka	Gas
Bone Spring	011	Strawn	Gas	Morrow	Gas

8. Casing program:

Hole size	Interval	OD of casing	Weight	Thread	Collar	Grade
25"	0-40'	20''	NA	NA	NA	Conductor
17½''	0-1000'	13 3/8"	54.5	8-R	ST&C	J-55
124"	0-4700'	9 5/8"	40.5	8R	ST&C	N-80
8½''	0-12,400'	7"	29	8-R	LT&C	S-95 & P-1
6 1/8"	12,200-15,400'	5" (liner)	18	8-R	ST&C	S-95

APPLICATION TO DRILL

POGO PRODUCING COMPANY RED TANK "26" FEDERAL # 13 UNIT "C" SECTION 26 T22S-R32E LEA CO. NM

.

9: <u>CEMENTING</u> AND SETTING DEPTH:

20" Conductor Set 40' of 20" conductor pipe and cement to surface with Redi-mix.

- 13 3/8" Surface Set 1000' of 13 3/8" 54.5# J-55 ST&C casing. Cement wi 1000 Sx. of Class "C" cement + additives top of cement surface.
- 9 5/8" 1st Inter. Set 4700' of 9 5/8" 40.5# N-80 ST&C casing. Cement with 1800 Sx. of Class "C" cement +2% CaCl, + ½# Flocele/Sx. Circulate cement to surface.
- 7" 2nd Inter. Set 12,400' of 7" 29# S-95 & P-110 LT&C casing. Cement in two stages with DV tool at 7000'±. Cement with 1200 of Class "H" cement + additives, estimate top of cement 3000' from surface.
- 5" Liner Run 3200' of 5" 18# S-95 ST&C Liner from 15,400' back t 12,200', Cement with 400 Sx. of Class "H" Premium Plus, low water loss cement. Cement back to top of liner.
- 10. PRESSURE CONTROL EQUIPMENT: B.O.P.to be used from 1,000' to 12,400' will be 13 3/8" 5000 PSI, Top bag, Middle blind, Bottom pipe rams. Choke manifold will be 2" 5000 PS with two hand adjustable chokes, (see exhibits "E" & "E-1").B.O.P. to be used from 12,400' to TD. will be a 7 1/16" 10,000 PSI B.O.P. with Top bag, Middle top pipe rams Middle bottom blind rams, Bottom pipe rams. Choke manifold will be a 3" 10,000 PSI with one hand conrtoled outlet and one remote controled panel on the derrick floor. (See exhibits "F" & "F-1") B.O.Ps will be tested to API specs, and will be operated once each day, blind rams will be operated when DP is out of hole. Full opening stabb valve upper kelly cock and PVT systems will be in place.
- 11. PROPOSED MUD CIRCULATING SYSTEM:

			•	
DEPTH	MUD WT:	VISC.	FLUID LOSS	TYPE MUD
40-1000'	8.4-8.7	29-34	NC	Fresh water mud use paper (control seepage.
1000-4700'	10.1-10.3	29-38	NC	Brine water use paper to control seepage and high viscosity sweeps to clean hole.
4700-12,400'	8.4-8.7	29-38	NC	Fresh water mud using high viscosity sweeps to clean hole.
12,400-15,400'	10.5-10.9	29-38	10 cc or less	Brine mud system using high viscosity sweeps to clean hole and a polymer system i water loss is to be control
				water loss is to be

Sufficient mud materials will be kept on location at all time to combat lost circulation, or unexpected kicks. In order to run DST's, open hole logs, and run casing, viscosity and vater loss may have to be adjusted in training.

APPLICATION TO DRILL

POGO PRODÚCING COMPANY RED TANK "26" FEDERAL # 13 UNIT "C" SECTION 26 T22S-R32E LEA CO. NM

12. TESTING, LOGGING, & COREING PROGRAM:

A. Open hole logs: Run # 1 Dual -Laterolog , SNP.LDT. Gamma Ray, Caliper from 4700' t0 1000'. Run # 2 Dual-Induction, SNP, LDT, Gamma Ray, Caliper from 12,400 to 4700'. Run # 3 Dual-laterolog, SNP, LDT, Gamma Ray, Caliper from Td. back to 12,400'.

B. Mud logger will be placed on hole at 4700' and remain on hole to 15,400'.

C. DST's and cores will be taken as shows dictate.

13. POTENTIAL HAZARDS:

No abnormal pressures or temperatures are expected. Hydrogen Sulfide gas may be encountered, H_2S detectors will be in place to detect any presence of unsafe levels of H_2S . No lost circulation is expected to occur. All personnel will be familiar with all aspects of safe operations of all equipment that will be used. Estimated BHP 9000 PSI & estimated BHT 200°

14. ANTICIPATED STARTING DATE AND DURATION OF OPERATION:

Roads and location construction will begin after the BLM approves the APD. Anticipated spud date will be as soon as pad & road construction has been completed. Drilling time for the well is estimated to take 80 days. If production casing is run an additional 35 days will be required to complete well and construct surface facilities.

15. OTHER FACETS OF OPERATION:

After running production casing, cased hole Gamma-Neutron & Collar logs will be run over all possible pay intervals. If commercial production from the <u>Morrow</u> pay is indicated it will be perforated and stimulated. Then if necessary the pay will be swab tested and completed as a gas well.

HYDROGEN SULFIDE DRILLING OPERATIONS PLAN

- All Company and Contract personnel admitted on location must be trained by a qualified H₂S safety instructor to the following:
 - A. Characteristics of H₂S
 - B. Physical effects and hazzards
 - C. Proper use of safety equipment and life support systems.
 - D. Principle and operation of H₂S detectors, warning system and briefing areas.
 - E. Evacuation procedure, routes and first aid.
 - F. Proper use of 30 minute pressure demand air pack.
- 2. H₂S Detection and Alarm Systems
 - A. H₂S detectors and audio alarm system to be located at bell nipple, end of blooie line (mud pit) and on derrick floor or doghouse.
- 3. Windsock and/or wind streamers
 - A. Windsock at mudpit area should be high enough to be visible.
 - B. Windsock at briefing area should be high enough to be visible.
 - C. There should be a windsock at entrance to location.
- 4. Condition Flags and Signs
 - A. Warning sign on access road to location.
 - B. Flags to be displayed on sign at entrance to location. Green flag, normal safe condition. Yellow flag indicates potential pressure and danger. Red flag, danger, H₂S present in dangerous concentration. Only emergency personnel admitted to location.
- 5. Well control equipment
 - A. See exhibit "E"
- 6. Communication
 - A. While working under masks chalkboards will be used for communication.
 - B. Hand signals will be used where chalk board is inappropriate.
 - C. Two way radio will be used to communicate off location in case of emergency help is required. In most cases cellular telephoned will be available at most drilling foreman's trailer or living quarters.
- 7. Drillstem Testing
 - A. Exhausts will be watered.
 - B. Flare line will be equipped with an electric ignitor or a propane pilot light in case gas reaches the surface.
 - C. If location is near any dwelling a closed D.S.T. will be performed.

HYDROGEN SULFIDE DRILLING OPERATIONS PLAN

- 8. Drilling contractor supervisor will be required to be familiar with the effects H_2S has on tubular goods and other mechanical equipment.
- 9. If H_2S is encountered, mud system will be altered if necessary to maintain control of formation. A mud gas seperator will be brought into service along with H_2S scavengers if necessary.

POGO PRODUCING COMPANY RED TANK "26" FEDERAL # 13 UNIT "C" SECTION 26 T22S-R32E LEA CO. NM

 EXISTING ROADS. Area map, Exhibit "B" is a reproduction of the New Mexico General Hi-way Co. Map. Exhibit "C" is a reproduction of a topographic map. Existing roads and proposed roads are shown on each exhibit. All roads will be maintained in a condition equal to or better than existed prior to start of construction.

- A. Exhibit "A" shows the proposed developement well as staked.
- B. From Hobbs New Mexico take U.S. High-Way 62-180 West toward Carlabad NM. go 38 miles to Co. Road C-29, turn South go 14 miles to Mills Ranch Road turn East and follow well traveled road for 7.2 miles, turn South go 1.3 miles turn West go 800' turn South go 200' to location.
- C. Lay flowlines along road R-O-W to gas sales line.
- 2. PLANNED ACCESS ROADS Approximately 100' of new road will be constructed.
 - A. the access road will be crowned and ditched to a 12'00" wide travel surface with a 40' right-of-way.
 - B. Gradient on all roads will be less tha 5.00%.
 - C. No turnouts will be necessary.

 ~ 2

- D. If needed, road will be surfaced with a minimum of 4" of caliche. This material will be obtained from a local source.
- E. Centerline for the new access road has been flagged. Earthwork will be as required by field conditions.
- F. Culverts in the access road will not be used. The road will be constructed to utilize low water crossings for drainage as required by the Lopography.
- 3. LOCATION OF EXISTING WELLS IN A ONE-MILE RADIUS EXHIBIT "A-1"

Α.	Water wells -	One approximately 1.75 miles north of location.
в.	Disposal wells -	One in Unit "H" in section 27.
с.	Drilling wells -	None known
D.	Producing wells -	As shown on Exhibit "A-1"

E. Abandoned wells - As shown on Exhibit "A-1"

Page 4

POGO PRODUCING COMPANY RED TANK "26" FEDERAL # 13 UNIT "C" SECTION 26 T22S-R32E LEA CO. NM

4. If upon completion this well is a producer Pogo Producing Company will furnish maps and/or plats with a Sundry showing on site facilities or off site facilities with pipelines, flowlines, powerlines that will be required to produce this lease.

5. LOCATION AND TYPE OF WATER SUPPLY:

......

Water will be purchased locally from a commercial source and trucked over the access roads or piped in flexible lines laid on top of the ground.

6. SOURCE OF CONSTRUCTION MATERIAL:

If possible construction will be obtained from the excavation of drill site, if additional material is needed it will be purchased from a local source and transported over the access route as shown on Exhibit"C".

7. METHODS OF HANDLING WASTE MATERIAL:

- A. Drill cuttings will be disposed of in the reserve pit.
- B. All trash, junk and other waste material will be contained in trash cages or bins to prevent scattering. When the job is completed all contents will be removed and disposed of in a approved sanitary land fill.
- C. Salts remaining after completion of well will be picked up by supplier including broken sacks.
- D. Sewage from living quaters will drain into holes with a minium depth of 10'. These holes will be covered during drilling and will be back filled upon completion. A Porta-John will be provided for the rig crews. This equipment will be properly maintained during the drilling operations and removed upon completion of the well.
- E. Remaining drilling fluids will be allowed to evaporate in the reserve pit until the pit is dry enough for breaking out. In the event that drilling fluids do not evaporate in a reasonable time they will be hauled off by transports and be disposed of at a state approved disposal facility. Later pits will be broken out to speed drying. Water produced during testing will be put in reserve pits. Any oil or condensate produced will be stored in test tanks until sold and hauled from the site.
- 8. ANCILLARY FACILITIES:

A. No camps or airstrips to be constructed.

POGO PRODUCING COMPANY RED TANK "26" FEDERAL # 13 UNIT "C" SECTION 26 T22S-R32E LEA CO. NM

9. WELL SITE LAYOUT:

- A. Exhibit "D" shows the proposed well site layout.
- B. This exhibit indicated proposed location of reserve and sump pits and living facilities.
- C. Mud pits in the active circulating system will be steel pits & the reserve pit is proposed to be unlined unless subsurface condition encountered during pit construction indicate that lining is needed for lateral containment of fluids.
- D. If needed, the reserve pit is to be lined with polyethelene. The pit liner will be 6 mils thick. Pit liner will entend a minimum of 2'00" over the reserve pits dikes where the liner will be anchored down.
- E. The reserve pit will be fenced on three sides with four strands of barbed wire during drilling and completion phases. The fourth side will be fenced after all drilling operations have ceased. If the well is a producer, the reserve pit fence will be torn down. The reserve pit and those areas of the location not essential to production facilities will be reclaimed and seeded per BLM requirements.

10. PLANS FOR RESTORATION OF SURFACE:

Rehabilitation of the location and reserve pit will start in a timely manner after all drilling operations cease. The type of reclamation will depend on whether the well is a producer or a dry hole.

However, in either event, the reserve pit will be allowed to dry properly, and fluid removed and disposed of in accordance with Article 7.3 as previously noted. The pit area will then be leveled and contoured to conform to the original and surrounding area. Drainage systems, if any, will be reshaped to the original configuration with provisions made to alleviate erosion. These may need to be modified in certain circumstances to prevent inundation of the location's pad and surface facilities. After the area has been shaped and contoured, topsoil from the spoil pile will be placed over the disturbed area to the extent possible. Revegetation procedures will comply with 3LM standards.

If the well is a dry hole, the pad and road area will be contoured to match the existing certain. Topsoil will be spread to the extent possible. Revegetation will comply with BLM standards.

Should the well be a producer, the previously noted procedures will apply to those areas which are not required for production facilities.

POGO PRODUCING COMPANY RED TANK "26" FEDERAL # 13 UNIT "C" SECTION 26 T22S-R32E LEA CO. NM

11. OTHER INFORMATION:

- A. Topography consists of sand dunes with a slight dip toward the West. Deep sandy soil supports native grasses, mesquite, and shinnery Oak.
- B. Surface is owned by the Bureau of Land Management U.S. Department of Interior. Surface is used for grazing of livestock and is leased to ranchers for this purpose.
- C. An archaeological survey will be conducted and copies of the survey will be filed in the Carlsbad Office of The Bureau of Land Management.
- D. There are no dwellings or habitation within three miles of this location.

12. OPERATORS REPRESENTIVE:

Before construction:

TIERRA EXPLORATION INC. P.O. BOX 2188 HOBBS, NEW MEXICO 88241 OFFICE PHONE 505-391-8503 JOE T. JANICA

During and after construction:

POGO PRODUCING COMPANY P.O. BOX 10340 MIDLAND, TEXAS 79702-7340 OFFICE PHONE 915-685-8100 MR. RICHARD WRIGHT 915-685-8140

13. <u>CERTIFICATION:</u> - I hereby certify that I, or persons under my direct supervision have inspected the proposed drill site and access route; that I am familiar with the conditions which currently exist; that the statements made in this plan are to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed by Pogo Producing company, its contractors/subcontractors is in the conformity with this plan and the terms and conditions under which it is approved. This statement is subject to the provision of U.S.C. 1001 for the filing of a false statement.

NAME DATE TITLE

anca 11/16/01 Agent

	U.S. U.C. Frate V.S. State	"Trumpeters St," •1	1	· · · · · · · · · · · · · · · · · · ·	103870 250 221 U.S.	
-	U.S. U.E. Frances 412 Auto Melling And Prop. Mellings And Prog. Mellings And Prog. Prog. Prog. Prog. Prog.	Staie	Siere U.C. & Frances Mills Rom, Prilost Arkland Prod. Philips	U.S. Marala, Phillips	Maralo	State M M4 Pogo Prod.
j	90586 166 23 169 7 90586 166 7 90586	Lower Deven Ener. Porthers: 17057	Arkland Prod. Philkps 55557 9447 902 Wm.tro Wm.tro Wills Family Ark	1 101.133 HBP	inc.etai 85937	v 4617 De Jean ∜
ť	to to the second	V 4084 V 4084 C 5 Franch, V 5 St Franch, V 5 St Franch, Martin Star Franch, Martin Sta	A 3-1-97 Moralo S.I. 188161 156429 1 86147	105832 1 10-1-33	(*************************************	
		Santa re fair Sy Lowe white Sman 25 Partners	Maralo L = -10 I R.Franch		ON FED UNIT	The star A 7 Page I mitchell Page # 0997 # 0117754 B Toris 35 Pro Toris 121
	α	Philips Wann Stars	State Wild Jurkey-St	*Prohibition-Fed Unit*	Drad-11-62 Prohibition-Fed. Ut."	The set of
	U.S. 17 Vates Pet, etal	Yahaa Dak atal	Pier U.S. Stretz (Mobil)	U ₁ S. Morolo, Inc.,etal	Pogo Prod.	NSL A
224	Ciecrufed. TDET40 05148	Yotes Pet., etal TA VB-134 Axx		05937	58940	Pogo Prod. Jémas II L-4780
•	E. LIVINGSTON	2 7 5×0 €ριά6 βιι2 3 16	1 Stroto Activero Act	Prohibition-Fed	·姿**	\mathfrak{S}^{2}_{TOR}
	PS60 (Citary Prt.) (wp) Citary Prt.)	5 2 Pise •	Marcury Expl. D Strate And et al. A to 15,115' O'Line (August Fail) A to 15,115' O'Line (August Fail) A to 15,115' O'Line (August Fail)	EGG RH. 14 [EGG Rts (FOCOT) 194076 (X410150 194076 (************************************		
	Mala Cleary-Fed."	* Kiwi-51.* P119 P102 * 6 c. P34 * 2 21	A to relieve on (construction) 	(Lenger) F159 F200 (Poco / Poco (Keg / gnk) Ard (Koorrec (Maril 66) Q2 Tan - Fed Com	San Trent (futci ring) San Trent (futci ring) (19:53 Si 19:537 San Sen (US 200 mm)	0/4123-61 \$.504
: 47 73 (* *3	U, S. A.R.Ca. 13 Getty 13	700	Pla 21 (ERxon) Pogo Prnd.	S.I. (WO US UNI LEFTER	-d2.weg 1	Srafe 92 Pogo Prod Pogo Prod 7:1:2295 , 7 - 1 - 2005
s at	Cities Serv. Yates 01936 Zamet Pet. 2tal View Port Tornet (robase Marr.), Pet. Harre Dae	Gries Servies A R. Co. 7 (Euson) (R.E. Lan- Yates Pet. 77058 Grithan etal	Ar Strata Prod (Exxon) 17058 Strate Prod (Exxon) Strate Prod (Exxon) Strate Prod (Exxon) Strate Prod (Exxon)	THE BIGSUPPER 412 1357	Jochelops LC (Senture Ener	- 0 346 1 V 5866 346 175 11 04/44. 77
are."	20-22-1	Li te Morrison Cubertson Linvin 21 Ch Cany Disc Linvin 21 Ch Cany Disc	Ce - 1, 22	5 La Bootigg Ridge		
•7	Cit Service Cit Se	E.I. Win Jimore 19 4846 1 I-Swoo DA 6 I-So 1	E13692 1 19 707313 045-10-02 PZZ	•7 500 Part 23 1 1 0	CGG Dr. etall Conche Land Trak (Micra)	Bootleg Ridge-Sf.
, ¢	t E Inner the Inner U.S. Fabrica	U,S. Cercion-Fed	Cercion Fed us "Prize-Fed."	A (Com) 2 / 2 / 2 / 2 / 2 / 2 / 2 / 2 / 2 / 2	Ganta Contraction Contraction Real Track, Saless Prove Frechers See Prove Salest Sal	Concho Resi
در م. در م.	Devon SFS Getty Oil 6-1-2006 A.H.Co.	Getty Oil el Pogo turn le Pogo	Pogo 3 ' (Exxon) 8/2/" 69376 • ' Pogo Prod - 03	1000 000 100 000 100 000 100 000 000 00	(main 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Mitchellen Pogo Prod. (Cal-Man stal) + 4-3526
; ;1	76856 39000 + Cities Servis Porterol	71 660		2379 ⁴¹	Catego Prod Catego J3 P71 LiJMil) 2379 04 LiJMil) 6.14 Fiod	(1000)+0 Prodite 1000-1 100
.rrew)	1(ta Dase Morrow)	. To base Marr. /	5 41 7 (wo) 6 7 1 9 128 27 (Excent)	● 1 ← Culber team F478 ← Culber team 26 Culbertson ● 4 26 Culbertson ● 4 26 Culbertson	1 36 25 13	11-1- 1
		Concho Res. 3 - 1 - 7 336 96238 210 99 9 9 9 9	FILSS T PILSS T Prove Filso Prove Filso	F530 •[PH] 20.4	4 5 FIGE (we) 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	
	U. S.	u <mark>s</mark> .	Fred OUS Prize FCT 42	Red Tonk -		(m) Red Tank St " (m) State Keller RV, (S)
inte Engr.	Yates Pet.,etai	1000 Anod 6 1 10031 Pago Prod. 90501 9 1 93 600 22 9 1 93	Il good Ocad.	1 Pogo Prod. 25.4 86150 Pogo Prod. ps	Pogg Prod. 1 Fere 1 rad VISIL Ever I EOG RES. FLIDO	174 71 (1778) 1728 Pogo Prod
202	V- 2443 Yates Ni dat "ALT" 2 bet. bret. Pag	459	1060 (mg) (mg) (mg) (mg) (mg) (mg) (mg) (mg)	3-E 2375 26-A 0Pogo Pi7	● 2 ² ma f m [router] / 160G Res. 109 € Shell St / Villet (Shell St / Rest. 105 € (Shell St / Rest.	V-3527 92 785
 _1F	32	33	34 607 ford ford	60000 Act Tonk Fed. 10600 35 03 03 03 03	1950 5246 (001) 015C) 36 NTO 8500	5444 F 31
147 147	LIMNGSTON	RIGE, SE		Contractor Service Connection Contra	-shell-st.	
1	" Lotus-St." State	"Red Tank "jø Fed." U.S.	Puese Freed Red Tank Fed Puese Free 6:1:2007 Red Tank Fed 6:1:709 90903 90903 90903 1900 U.S. 1900	u,s	Siere e or	
istan d	Devon SFS Pogo Prod. HBP 3 2007	ран ишин Луан Лаас Родо Ргос. 1 Техасо 3.1 2007 ИВР 989: 1 18848	Pago Prod. 102009 Pogo Prod. 102009 3 1 2009 102043 102043	Vates Petretal	100 100 100 100 100 100 100 100 100 100	
	 	Pogo Prod. 2 1 99 VA 1148	102024 3 7 2003 102024 10 2043 10204 1020	v8 · 286	Yutes Pet. etal - 400" 91274 APY" P90 17012	
I	5 Lillie Yates	4 5167.29	Srore 3	2 '****		734 6 6 Pringhor Unit 104000 C 104000 C
	9 - 1 - 95 62223	Pege Frod (3)fata Prod) / Arosenad Fed / (TO 3000) / (UA)i433, / PID 6453	6 Riel Je Fed C 3724 70 50 - * 20 4 8 7 8 M 25 GI			JISIA T Teratic. State and
	u, s.	U.S. Offer	U,S.	Stata Strata Prata Yates Pet.eta	Thyme-Fed - Cranden eil ² U.S. State	State(3)
29 29 6112 6 22455	Техосо нар 1884 г	3 · 1 · 2007 98192 160 ±	Strata Prod 05939	85540 37662	86925 Herdion April	W 5 0355 MBP 1047? 31664 ?
· • • P90		Strato Prod	Exxpn Sent Sw O Oil Corp.	• and - Amende for	1 Yates	7
	Concho Res. 8	Stratu Prod 9 droganga o ² pm i i i i i yeser Qi ⊕ ²	· IO Oil Carp. Fridance DAST Carp.	Triate Dr. Feb 64776 d	Burlington v. 1651 # 80 0538344	Concho Res.
sted" " ginu " Ted.	350 <u>00</u> * Tomcat-Fed.*	224 Fee	507070 0000 7000000 1000000		EXHIBIT	
· Sauger	Texoco (Mycoindetai)	"Tomeat' 9' Fed." U.S. 04	03 Strate And., 120300		ONE MILE RA	
	Gizella)	Concho Res. V·4340	64720 Farme	64729	POGO PRODUC RED TANK "26"	FEDERAL # 13
Ð.		TO AND AND	Concho Res. O TESO	9. (Qu#)	וואדי ייכיי	SECTION 26

•







- Briefing Areas
- Remote BOP Closing Unit
- Sign and Condition Flags

EXHIBIT "D" RIG LAY OUT PLAT

POGO PRODUCING COMPANY RED TANK "26" FEDERAL # 13 UNIT "C" SECTION 26



ARRANGEMENT SRRA

1500 Series 5000# Working Pressure

> EXHIBIT "E" 5,000 PSI SKETCH OF B.O.P. TO BE USED O

POGO PRODUCING COMPANY RED TANK "26" FEDERAL # 13



Page 2



EQUIPMENT Accumulators

FIGURE K6-1. The schematic sketch of an accumulator system shows required and optional components.



FIGURE K42. Typical choke manifold assembly for 5M rated working pressure service - surface installation.

EXHIBIT "E-1" 5000 PSI CHOKE MANIFOLD & CLOSING UNIT

POGO PRODUCING COMPANY RED TANK "26" FEDERAL # 13



DRILLING MANUAL

BLOWOUT PREVENTION EQUIPMENT IADC Recommended BOP Stacks

Sectic

Ρ



FIGURE KI-3. Recommended IADC Class 10 BOP stack arrangement SRSRRA, 10,000 psi WP. Lower drilling spool is optional with outlets on lower ram. Annular preventers 10,000 psi.

> EXHIBIT "F" 10,000PSI SKETCH OF B.O.P. TO BE USED C

POGO PRODUCING COMPANY RED TANK "26" FEDERAL # 13



.

FIGURE K6-1. The schematic sketch of an accumulator system shows required and optional components.

