Form 3160-5 (September 200 1)

UNITED STATES DEPARTMENT OF THE INTERIOR

FEB 19 2010

RECEIVED

FORM APPROVED OMB No. 1004-0135 Expires January 31, 2004

BUREAU OF LAND MANAGEMENT	4 4 MARTIN 12 14 14 74 15
SUNDRY NOTICES AND REPORTS ON WEL	^r rorponof
abandoned well. Use Form 3160-3 (APD) for such prop	osals.

SUNDR Do not use th abandoned we	Y NOTICES AND REPOR is form for proposals to c ell. Use Form 3160-3 (APD)	RTS ON WELLS Chrill or to re-enter a for such proposals.)Bt "	SSUCD	LC-0555 6. If Indias	46	ttee or Tribe Name
SUBMIT IN TR	IPLICATE - Other instru	ctions on reverse	side		7 If Unit o	r CA/	Agreement, Name and/or No.
Dodrett Schrett C	3/0 m.				8. Well N		,
2. Name of Operator Herman L. Loeb LLC	/				F. J. Wel		
3a. Address 3b. Phone No. (include area code) P O Box 838, Lawrenceville, IL 62439 (618) 943-2227		ode)	30-025-11458 I 0. Field and Pool, or Exploratory Area				
4. Location of Well (Footage, Sec., 1980' FSL 660' FWL Section	/	N	E OF		I 1. County	y or Pa nty, N	м /
TYPE OF SUBMISSION				ACTION		<u> </u>	
Notice of Intent Subsequent Report Final Abandonment Notice 13. Describe Proposed or Completed	Alter Casing Casing Repair Change Plans Convert to Injection	Deepen Fracture Treat New Construction Plug and Abandon Plug Back	0000	Production (Start/ Reclamation Recomplete Temporarily Abar Water Disposal	adon	O O	Water Shut-Off Well Integrity Other
If the proposal is to deepen dire. Attach the Bond under which the	ctionally or recomplete horizontally he work will be performed or prov olved operations. If the operation was a shall be to the shall be to th	y, give subsurface location ide the Bond No. on file v results in a multiple comp	ns and with B detion	measured and true LM/BIA. Require or recompletion is	e vertical dej d subseque: n a new inte	pins of nt repo rval. a	all pertinent markers and zones. orts shall be filed within 30 days Form 3160-4 shall be filed once

- 1. Set CIBP @ 2,970', load csg w/ 69 bbl fresh water, pressure test csg to 300#. RIH w/ tubing, tag plug @ 2970'. 7/14/09
- 2. Spot balanced plug of 11 bbl of 14.8 ppg cement on bridge plug. POH w/ 15 jts of tbg, end of tbg @ 2483', pump 30 bbl of 9.5 ppg gel spacer, POH w/ tbg. Perforate 1250-51' 2 spf. Est inj rate of 2 bpm @ 100#, pump 70 bbl of 14.8 ppg cement down csg, displace w/ 22.5 bbl of water, circulate 1 bbl of cement to sfc. SION. 7/15/09
- 3. RIH w/ tbg, tag cement @ 917, pump 16 bbl of 9.5 ppg gel spacer. POH w/ 21 jts, end of tbg @ 359', pump 9 bbl of 14.8 ppg cement down tbg, circulate 1 bbl of cement to pit, POH w/ tbg. Top off csg w/ 2 bbl of cement. 7/16/09
- 4. Cut off all csg strings 4' below ground level, 7" csg did not have cement to sfc, run 1 jt of 1" PVC pipe in 7" annulus, pump 2 bbl or 9 sk of 14.8 ppg cement down 1", circulate 1/2 bbl cement to sfc. Job witnessed by Andy Cortez USBLM. 7/18/09
- 5. Weld plate on easing, install dry hole marker. 7/23/09

BLM Bond # NM-2839

1		MW2/22/201
Title Petroleum Engineer		1. 2121
Date 9/17/09		
DERAL OR STATE OFFICE US	BE	
Title	Date	FEB 2 2 2010
of warrant or subject lease Office		
	Date 9/17/09 DERAL OR STATE OFFICE US Title	Date 9/17/09 DERAL OR STATE OFFICE USE Title Date

States any trace, richtion of franchent state dents of representations as make makerime for a try g