Form 3160-5 (August 2007) UNITED STAT DEPARTMENT OF TH BUREAU OF LAND MA	E INTERIOR NAGEMENT OCDALOBERS NAGEMENT OCDALOBERS Subscription OMB NO 1004-0137 Expires July 31, 2010 5 Lease Senal No.
SUNDRY NOTICES AND RE	PORTS ON WELLS FEB 2 2 7 min MMM 104049
Do not use this form for proposals abandoned well. Use Form 3160-3	s to drill or to re-enter an (APD) for such proposal SBSUCD
SUBMIT IN TRIPLICATE - Other	r instructions on page 2 7. If Unit or CA/Agreement, Name and/or No West Corbin Federal
1 Type of Well X Oil Well Gas Well Other	8. Well Name and No. West Corbin 5
2 Name of Operator	Federal
EOG Resources Inc.	9. API Well No. 3b. Phone No. (<i>include area code</i>)
P.O. Box 2267 Midland, Texas 79702	3b. Phone No. (include area code) 30-025-29298 432 686 3689 10 Field and Pool, or Exploratory Area
4 Location of Well (Footage, Sec., T, R., M., or Survey Description)	South Corbin South Cordin
2080' FNL & 560' FWL, Sec 17, T18S, R33E	Bone Spring / Wolfcomp 11 County or Paristy State Lea MM
12. CHECK APPROPRIATE BOX(ES	5) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION
	dize Deepen Production (Start/Resume) Water Shut-Off
X Subsequent Report	
	ng Repair New Construction X Recomplete Other
Final Abandonment Nouce	nge Plans Plug and Abandon Temporarily Abandon vert to Injection Plug Back Water Disposal
 following completion of the involved operations. If the operations testing has been completed. Final Abandonment Notices shall determined that the final site is ready for final inspection.) 11/10/09 MIRU. POOH w/ rods and 2-7/8" 11/11/09 RD bit and scraper. RIH and set 11/12/09 Run CBL and found TOC at 6330' RIH and perf squeeze holes at 6 11/13/09 Perform pump in test. RIH and 11/14/09 Pump 200 sx HAL/LIGHT cement, 1 11/16/09 Run CBL and found TOC at 5194'. RIH and set CICR at 5098'. 11/17/09 Pump 200 sx HAL/LIGHT cement 12 11/19/09 Run CBL and found TOC at 4973'. 11/20/09 Drill out to 6216'. Shut-in. 11/30/09 Continue cleaning out. Push pl 12/02/09 RIH w/ 2-7/8" production tubing 	<pre>behind 5-1/2" casing. 5200'. set CICR at 6145'. 12.5 ppg, then 400 sx HAL H cement, 15.6 ppg. Shut-in WOC. . RIH and perf squeeze holes at 5170'. Perform pump in test. 2.5 ppg, then 400 sx HAL H cement 15.6. . RIH w/ 4-3/4" milltooth bit, begin drilling out at 5102'. Prep to clean out. Hug remnants down to 10356'. h out hole. Shut-in.</pre>
14 II - I	
14. I hereby certify that the foregoing is true and correct Name (<i>Printed/Typed</i>)	
Signature	Date 2/1/10
Jan Wage	FOR FEDERAL OR STATE OFFICE USÉ
Approved by	
Conditions of approval, if any, are attached. Approval of this notice does not w	varrant or certify that Office Kat Alman
the applicant holds legal or equitable title to those rights in the subject lease wh entitle the applicant to conduct operations thereon.	
Title 18 U S C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crun fictitious or fraudulent statements or representations as to any matter within its	me for any person knowingly and willfully to make to any department or Ggenicy Of Jthe United Sides any file, : jurisdiction