Submit 3 Copies To Appropriate District Office	State of New Me		Form C-103 June 19, 2008
District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W Grand Ave., Artesia, NM 88210 District II			WELL API NO. 30 025 39404
District III 1220 South St. Enongia Dr.			5. Indicate Type of Lease STATE STATE
District IV 1220 South St. Francis Dr., Santa F. OBBSOCD 87505			6. State Oil & Gas Lease No. VB-1128
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A			7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			Moore Cowbell 27 State 8. Well Number #1H
2. Name of Operator			9. OGRID Number
Caza Operating, LLC, /         3. Address of Operator			249099 10. Pool name or Wildcat
200 N. Loraine, Suite 1550, Midland, Texas 79701         4. Well Location			Caprock Wolfcamp, East (9310)
4. Well Location Unit Letter <u>P</u> : <u>660</u> feet from the <u>South</u> line and <u>990</u> feet from the <u>East</u> line			
Section 27	Township 12 South	Range 32 East	NMPM Lea County
11. Elevation (Show whether DR, RKB, RT, GR, etc.)         4335 GR			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK 🔲 PLUG AND ABANDON 🔲 REMEDIAL WORK			
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRI			
PULL OR ALTER CASING	MULTIPLE COMPL	CASING/CEMENT	IOB L
OTHER: OTHER: Sqeeze lower Wolfcamp- Perf Wlfcmp -test			
<ol> <li>Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.</li> </ol>			
<ul> <li>2-4-2010 E&amp;P wireline shot squeeze holes 8740 &amp; 8400 (total 8 holes) 4 each position</li> <li>2-10-2010 Set cement Retainer @ 8650 ft. Test tubing. Okay. Suicide squeeze perfs w/ 85 sks "H" mixed 15.6 ppg. POH to 8100 ft &amp; reversed circulate 5 bbls gray water.</li> <li>2-13-2010 Drill out cmt retainer and cmt to 8785 ft.</li> <li>2-14-2010 E&amp;P wireline perforated Wolfcamp interval 8676 ft - 8693 ft (4spf) 90°phase .32" holes total (68) holes</li> <li>2-16-2010 Rising Star acidized perfs w/ 5000 gals 15% HCL NEFE. ISIP 5261 psi. 15min 4901 psi.</li> <li>2-(16-23)-2010 Swab load. Very poor entry. Final entry ± 1 bfph w/40% oil cut.</li> </ul>			
	•		
Spud Date: 11/28/2009	Rig Release Da	ate: 01/17/2010	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.			
SIGNATURE ALANA A CAMPANT TITLE Operations Manager DATE 02/23/2010			
Type or print name <u>Richard L. Wright</u> E-mail address: <u>rwright@cazapetro.com</u> PHONE: <u>432 682 7424</u> For State Use Only			
APPROVED BY:			