

RECEIVED

FEB 03 2010

HOBBSD

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO. /

30-025-39491

5. Indicate Type of Lease

STATE ☐ FEE ☒ /

6. State Oil &amp; Gas Lease No.

NA

7. Lease Name or Unit Agreement Name

Cone A

8. Well Number 2 /

9. OGRID Number /

873

10. Pool name or Wildcat /

House; Blinebry/Tubb/Drinkard

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: ☒ Oil Well ☐ Gas Well ☐ Other: /

2. Name of Operator /

Apache Corporation

3. Address of Operator

6120 S Yale Ave, Suite 1500 Tulsa, OK 74136

4. Well Location

Unit Letter F : 2310 feet from the North line and 1650 feet from the West line  
Section 12 Township 20S Range 38E NMPM County Lea /

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3565' GR

## 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐OTHER: ☐OTHER: New Completion ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Apache completed this well via the following procedure:

1/5/2010 Perf Drinkard @ 6996-7000, 7020-24, 7036-40, 7088-92 w/2 JSPF, 36 holes.

1/6/2010 Acidize w/2k gals 15% HCl.

1/7/2010 Frac w/55k gals gel &amp; 70k# 20/40 sd. RIH w/CBP @ 6950'. Perf Tubb @ 6758-62, 6786-90, 6852-56, 6880-84 w/2 JSPF, 36 holes. Acidize w/2200 gals 15% HCl. Frac w/35k gals gel &amp; 50k# 20/40 sd.

1/8/2010 RIH w/CBP @ 6610'. Perf lower Blinebry @ 6466-70, 6486-90, 6550-54 w/2 JSPF. 27 holes. Acidize w/3200 gals 15% HCl. Frac w/22k gals gel &amp; 22k# 20/40 sd. Set CBP @ 6250'. Perf upper Blinebry @ 6060-64, 6110-14, 6152-56 w/2 JSPF. 27 holes. Acidize w/1800 gals 15% HCl. Frac w/29k gals gel &amp; 30k# 20/40 sd.

1/11/2010 DO CBP's and wash sand to PBTD @ 7240'.

1/12/2010 RIH w/tbg @ 7115'.

1/13/2010 RIH w/pmp and rods.

1/14/2010 Set 640 pumping unit

1/15/2010 Start prod to battery from Blinebry/Tubb/Drinkard.

Spud Date:

11/22/2009

Rig Release Date:

12/06/2009

DHC- HOB- 350

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Amber Cooke

TITLE Engineering Tech

DATE 01/26/2010

Type or print name Amber Cooke

E-mail address: amber.cooke@apachecorp.com

PHONE: 918.491.4968

For State Use Only

APPROVED BY:

[Signature]

TITLE

PETROLEUM ENGINEER

DATE

MAR 01 2010

Conditions of Approval (if any):