

May 27, 2004

Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 88201

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

RECEIVED
MAR 18 2010
HOBBSOCD

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.

30-025-27540

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Lea 407 State

8. Well Number

6

9. OGRID Number

6137

10. Pool name or Wildcat

San Simon Yates, North (Association)

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☒

2. Name of Operator

DEVON ENERGY PRODUCTION COMPANY, LP

3. Address of Operator

20 North Broadway, Ste 1500, Oklahoma City, OK 73102

405-552-4615

4. Well Location

Unit Letter C : 660' feet from the North line and 1980' feet from the West lineSection 33 Township 21S Range 35E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3636 KB; 3625' GL

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ P AND A ☒CASING/CEMENT JOB ☐OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. 3/1/10: MIRU. POOH w/rod pump assembly and 2-3/8" production tubing.

2. Circulate wellbore w/10 ppg mud.

3. Set CIBP at 3750'. Spot 25 sx cement from 3750' to 3504'. (Yates open perms from 3787' to 3895')

4. Spot 25 sx cement from 1927' to 1681'. Tagged TOC @ 1722'. (8-5/8" shoe @ 1877')

5. 3/5/10: Perf sqz hole @ 240'. Pumped 60 sx cement circulating to surface out 8-5/8" X 5-1/2" annulus, leaving 240' surface plug.6. 3/16/10: Set dry hole marker. Wellbore plugged & abandoned.Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 (Subsequent Report of Well Plugging)
which may be found at OCD Web Page under
Forms: www.emnrd.state.nm.us/oed.I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.SIGNATURE Ronnie Slack TITLE Operations Technician DATE 3-17-10Type or print name Ronnie SlackE-mail address: Ronnie.Slack@dvn.comTelephone No. 405-552-4615

For State Use Only

APPROVED BY: [Signature] TITLE STAFF MGR DATE 3-22-10

Conditions of Approval (if any):

DEVON ENERGY PRODUCTION COMPANY LP

Well Name: LEA 407 STATE #6

Field: SAN SIMON YATES NORTH

Location: 660' FNL & 1980' FWL; SEC 33-T21S-R35E	County: LEA
--	-------------

County: LEA	State: NM
-------------	-----------

Elevation: 3636' KB; 3625' GL

Spud Date: 8/31/81	Compl Date: 11/4/81
--------------------	---------------------

API#: 30-025-27540	Prepared by: Ronnie Slack	Date: 3/17/10
--------------------	---------------------------	---------------

Date: 3/17/10	Rev:
---------------	------

ACTUAL PLUG & ABANDONMENT

14" Conductor pipe @ 30'

2 yds redi mix to surf

8-5/8", 24#, K55, @ 1,877'

Cmt'd w/785 sx, circ to surf

3787', 3792', 3797', 3800', 3808', 3813

**3816', 3820', 3844', 3859', 3863', 3868',
3879', 3888', 3892', 3895'**

acid/frac w/2000 gals 15%, 88K# sar

acid/frac w/2000 gals 15%, 88K# sand IP 30 bopd, 3 bw

3956' - 4084' (sqzd w/400 sx)

4139' - 4195' (sqzd w/150 sx)

5-1/2", 15.5#, K55, @ 4,226'

Cmt'd w/850 sx, circ to surface

United States and, one to Canada

2. Perfed sqz hole @ 240'. Pumped 60 sx cmt.

Circulated cement out 8-5/8" X 5-1/2" annulus,
leaving 240' surface plug. (3/5/10).

3. Set dry hole marker. (3/16/10)

2. Tagged TOC @ 1722'. (3/4/10)

2. Page 100 @ 1121 (b. 10)

2. Spot 25 sx cmt from 3750'

Cement retainer @ 3948' (10/16/81)

Cement retainer @ 4127' (10/12/81)

10 ppg mud

10 ppg mud

4,226' TD