

State of New Mexico
Energy, Minerals and Natural Resources

RECEIVED

OIL CONSERVATION DIVISION

MAR 22 2010

HOBBS

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.

30-025-25429

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
Woolworth

8. Well Number #2

9. OGRID Number 264953

10. Pool name or Wildcat
Jalmat (SR, T, Y)

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

Herman Loeb LLC.

3. Address of Operator

PO Box 838, Lawrenceville, Ill. 62439

4. Well Location

Unit Letter K : 1980 feet from the South line and 1,650 feet from the West lineSection 33 Township 24S Range 37E NMPM County Lea11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3,258' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
 PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
 DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
 COMMENCE DRILLING OPNS. ☐ P AND A ☐
 CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. RIH w/sandline & confirm CIBP @ 2,884'. If there PT csg to 500 psi. If not there set CIBP @ 2,884' & PT csg to 500 psi. If csg leaks TIH w/pkr & locate leak. Contact OCD for orders. If csg tests spot 40 sks cmt on top of CIBP (would leave cmt plug fr/2,884' to 2,500' to cover base of salt @ 2,700'). Spot 29 bbl salt gel spacer fr/2,500'-1,300'. Perf 1,300'-1,301' (2 spf). Attempt to estb circ up 5-1/2" csg annulus. If circ is estb pmp cmt until good cmt to surface in 5-1/2" csg annulus. If unable to estb circ TIH w/pkr & set @ 950'. Cmt w/100 sks & displace to 1,050'.

Perf @ 1230 59 355x cmt
woc-1749

2. If plugged w/pkr TIH & tag cmt plug. Spot 13 bbl salt gel spacer. Perf 400'-401'. Estb circ up 5-1/2" csg annulus & cmt until good cmt is to surface.

3. Cut off all csg 4' below GL. Top off as necessary. Cap well & install dry hole marker.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Michael Polley TITLE Agent for Herman Loeb LLC. DATE 3/17/2010Type or print name Michael Polley E-mail address: polleyms@gmail.com PHONE: 719-342-5600

For State Use Only

APPROVED BY: [Signature] TITLE STAFF MGR DATE 3-24-10

Conditions of Approval (if any):

Conditions of Approval: the operator
shall give 24 hour notice the the appropriate
District office before work begins.

COMPANY: Herman Loeb LLCWELL NAME: Woolworth #2LEGAL: Sec 33/24S/37EUnit Letter KAPI # 30-025-25429COMPLETION, WORKOVER
AND
DRILLING SUPERVISION

PHONE: 719-846-3434

MOBILE: 719-342-5600

polleym@gmail.com

VOL. BETWEEN PIPE & HOLE CAP.

	BBL/FT	FT/BBL	CF/LF
4 1/2 - 7 7/8	.0406	24.65	2278
5 1/2 - 7 7/8	.0309	32.41	1733
8 5/8 - 12 1/4	.0735	13.61	.4127
9 5/8 - 12 1/4	.0558	17.93	.3132
13 3/8 - 17 1/2	.1924	8.08	8946

TUBING & CASING SIZE & CAP.

	WT.	BBL/FT	FT/BBL
2 3/8	4.6	.0039	258.65
2 7/8	6.5	.0058	172.76
3 1/2	9.3	.0087	114.99
4 1/2	10.5	.0159	62.70
4 1/2	11.6	.0155	64.34
5 1/2	15.5	.0238	42.01
5 1/2	17.0	.0232	43.02
5 1/2	20.0	.0222	45.09
5 1/2	23.0	.0212	47.20
8 5/8	32.0	.0609	16.41
9 5/8	36.0	.0773	12.94

D.P. SIZE _____ TUBING SIZE: _____ CASING SIZE: _____

HOLE SIZE: _____ PERFS: _____

PACKER SETTING: _____ BP SETTING: _____ MAX RATE: _____

MAX PSI: _____ BHST: _____ FORM: _____ TAIL PIPE: _____

VOL. BETWEEN PIPE & PIPE CAP.

	WT.	BBL/FT	FT/BBL	CF/LF
2 3/8 - 4 1/2	11.8	.0101	99.37	0565
2 3/8 - 5 1/2	17.0	.0178	56.28	0990
2 7/8 - 5 1/2	17.0	.0152	65.71	0854
2 7/8 - 7	23.0	.0313	31.91	.1760

