

June 19, 2008

District I
1625 N French Dr, Hobbs, NM 87240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87401
District IV
1220 S St. Francis Dr, Santa Fe, NM 87505

RECEIVED
CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505
MAR 29 2010
HOBBS

WELL API NO. 30-025-39633 ✓
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: Horse 29 State ✓
8. Well Number 1H ✓
9. OGRID Number 7377 ✓
10. Pool name or Wildcat Red Hills; Bone Spring ✓
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3319' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	2. Name of Operator EOG Resources, Inc.	3. Address of Operator: P.O. Box 2267 Midland, TX 79702	4. Well Location Unit Letter D : 330 feet from the North line and 430 feet from the West line Section 29 Township 25S Range 34E NMPM County Lea
12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data			

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: **kick-off plugs** ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

3/10/10 TD pilot hole @ 12550'.

3/17/10 RIH and set 1st cement plug @ 12550', 335 sx Class H, 18.0 ppg, 0.904 yield.

2nd cement plug @ 10550', 50 sx Class H, 18.0 ppg, 0.904 yield.

3rd cement plug (kick-off) @ 8800' to 9400', 325 sx Class H, 18.0 ppg, 0.904 yield. KOP @ 9100'.

Resumed drilling 8-3/4" hole.

Spud Date:

2/12/10

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

Regulatory Analyst

DATE

3/25/10

Type or print name **Stan Wagner**

E-mail address:

PHONE **432-686-3689**

For State Use Only

APPROVED BY

TITLE

PETROLEUM ENGINEER

DATE

MAR 29 2010

Conditions of Approval (if any):