

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-36164
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		7. Lease Name or Unit Agreement Name: Liberty 4
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other	8. Well No. 3	
2. Name of Operator Read & Stevens, Inc.	9. Pool name or Wildcat Wildcat Bone Spring	
3. Address of Operator P. O. Box 1518 Roswell, NM 88202		
4. Well Location Unit Letter E : 2310 feet from the North line and 660 feet from the West line Section 4 Township 20S Range 36E NMPM County Lea		
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,630' GL		

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: **Spud, Csg, Cmt** ☒

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

02/26/03 MIRU Patterson rig #1.

02/27/03 Spud well @ 6:30 AM 2/27/03. Drill 17 1/2" hole to 445' TD. Ran 13 3/8" 48# H-40 STC csg, set @ 445'. Cmt w/ 175 sx Halliburton Light + additives, tail w/ 200 sx Premium Plus 2% CaCl. Circ to pit. WOC 8 hrs. Continue drlg operations.

03/03/03 Drill 11" hole to 3,110' TD. Ran 8 5/8" 32# J-55 csg, set @ 3,110'. Lead w/ 600 sx Interfill C, .25% flocelo, tail w/ 200 sx Premium Plus + 2% CRF-3. Circ cmt to surface. WOC 8 hrs. Continue drlg operations.

03/13/03 Drill 7 7/8" hole to 7,200' TD. Ran 5 1/2" 17# J-55 LT&C csg, set @ 7,200'. Lead w/ 500 gal Super Flush 102 + 500 sx Interfill H, tail w/ 350 sx Premium Plus Super H, 5% LAP-1, 0.4% CRF-3, 2.5# salt. Released rig @ 3:00PM 3/15/03 MST.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE TITLE **Operations Manager** DATE **4-8-03**

Type or print name **John C. Maxey, Jr.** Telephone No. **505/622-3770**
(This space for State use)

APPROVED BY TITLE **PETROLEUM ENGINEER**
Conditions of approval, if any:

DATE **APR 15 2003**