

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised June 10, 2003

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-025-36524

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
Karen 1 State

8. Well Number
002

9. OGRID Number
023230

10. Pool name or Wildcat
Skaggs; Drinkard (57000)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
Tom Brown, Inc.

3. Address of Operator
P O Box 2608, Midland, TX 79702

4. Well Location
Unit Letter K : 2310 feet from the South line and 1650 feet from the West line
Section 1 Township 20S Range 37E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3585 GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒


OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1/19/04 Notified OCD. Spud well @ 21:30 CST

1/21/04 Drill 12-1/4" hole to 1470'. Run 35 jts of 8-5/8" csg 24#, J-55 (total length 1474.41, Set @ 1470'). Ann w/ 400 sx of Haliburton Light Premium Plus + 1/4 pps flocele + 2% CaCl2, 12.5 ppg, 1.95 yld. Tail in w/ 2048 Premium Plus + 2% CaCl2. Displace w/ 89 bbls of brine water. Landed plug w/ 400 psi over, check float, close valves. Let sit for 3 hrs. Circ 114 sx to pit.

1/22/04 Cut off conductor & 8-5/8" csg. Install csg head. NU BOP. Total WOC 13-3/4 hrs



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Diane Kuykendall TITLE Operations Asst / Tech DATE 1/27/04

Type or print name Diane Kuykendall E-mail address: dkuykendall@tombrown.com Telephone No. 432-688-9773

(This space for State use)

APPROVED BY Gary W. Wink TITLE OC FIELD REPRESENTATIVE II/STAFF MANAGER DATE JAN 30 2004

Conditions of approval, if any