

District I

1625 N. French Dr., Hobbs, NM 88201

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

87505

RECEIVED**APR 19 2010****HOBBSOCD**

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO. 30-025-39622	✓
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>	✓
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name Ramsland	✓
8. Well Number 1	✓
9. OGRID Number 010155	✓
10. Pool name or Wildcat Garrett, Drinkard, East	✓

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	
2. Name of Operator Harvard Petroleum Company, LLC	✓
3. Address of Operator PO Box 936, Roswell, NM 88202-0936	
4. Well Location Unit Letter <u>A</u> : <u>330</u> feet from the <u>North</u> line and <u>500</u> feet from the <u>East</u> line Section <u>27</u> Township <u>16S</u> Range <u>38E</u> NMPM <u>Lea</u> County	✓
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3705 GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
 PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
 DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
 COMMENCE DRILLING OPNS. ☒ P AND A ☐
 CASING/CEMENT JOB ☒

OTHER: ☐OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Commenced Drilling a 12.25" hole at 9:15 pm, 2/18/10

Drilled 12 1/4" hole to 2160' and ran 53 jts 9 5/8" 36# and 2 joints 9 5/8" 40# Casing, landed at 2180'. The casing was equipped with a guide shoe Float Collar and centralizers spaced every 4ft joint. The casing was cemented with Lead: 355 sx 50:50:10: POZ, Gel 5%, salt, .125#/sk CF and Tail: 250 sx C Neat w/ 1% CaCl. The plug was displaced with fresh water and 46 sacks of cement were circulated to surface. Plug down at 9:07 PM 2/21/10

Drilled a 8 3/4" hole to 8800' and ran 50 jts 7" 26# N-80, 147 jts 7" J-55 and 9 jts 7" N-80 casing, landed at 8800'. The 7" casing was equipped with a float shoe float collar and 7 centralizers. The casing was cemented with Lead: 1500 sx 50:50:10:POZ:C:Gel+.4% FL-52A+5%NaCl+.13#CF, Tail: 450 sx 15:81:11:POZ C:CSE-2+5%NaCl+3#LCM1+5%FL-25+.2H2O. The plug was displaced with Fresh water and 312 sx of cement were circulated to surface. Plug down at 9:23 PM 3/10/10.

Spud Date:

Feb 18, 2010

Rig Release Date:

March 23, 2010

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Consultant

DATE 4/15/2010

Type or print name Phelps White

E-mail address: pwiv@zianet.com

PHONE: 575 626 7660

For State Use Only

APPROVED BY:

TITLE

DATE

Conditions of Approval (if any):

PETROLEUM ENGINEER**APR 19 2010**

ch 4-2010