

Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies District I 1625 N French Dr., Hobbs, NM 88201 District II 1301 W Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources RECEIVED MAR 16 2010 HOBBSOCD Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505		Form C-105 Revised June 10, 2003			
		WELL API NO. 30-025-36693		5. Indicate Type of Lease STATE ☐ FEE ☒			
				State Oil & Gas Lease No.			
WELL COMPLETION OR RECOMPLETION REPORT AND LOG							
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____				7. Lease Name or Unit Agreement Name Scharbauer			
b. Type of Completion: NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. WELL OVER ☐ BACK RESVR. ☐ OTHER							
2. Name of Operator Seely Oil Company				8. Well No. 3			
3. Address of Operator 815 W. 10 th St. Ft. Worth, TX 76102				9. Pool name or Wildcat EK Delaware <i>YATES-7 RULS-QUEEN</i>			
4. Well Location Unit Letter: N 330 Feet From The South Line and 1980 Feet From The West Line Section 20 Township 18S Range 34E NMPM Lea County, NM							
10. Date Spudded 6/3/04	11. Date T.D. Reached 6/21/04	12. Date Compl. (Ready to Prod.) 9/23/04	13. Elevations (DF& RKB, RT, GR, etc.) 6049' RKB	14. Elev. Casinghead 3983'			
15. Total Depth 6050'	16. Plug Back T.D.	17. If Multiple Compl. How Many Zones?	18. Intervals Drilled By	Rotary Tools yes	Cable Tools		
19. Producing Interval(s), of this completion - Top, Bottom, Name none					20. Was Directional Survey Made yes		
21. Type Electric and Other Logs Run CBL/GR/CCL				22. Was Well Cored no			
23. CASING RECORD (Report all strings set in well)							
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED		
8 5/8"	24 lb/ft	1682'		375 sxs Pozmix			
				125 sxs Class C			
5 1/2"	17 lb/ft	6049'		500 sxs Interfill C			
				700 sxs 50/50			
				Premium Pozmix			
24. LINER RECORD			25. TUBING RECORD				
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2 3/8"	5503	
26. Perforation record (interval, size, and number)				27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.			
5804-06', 5809-16', 5821-30' (CIBP @ 5750')				DEPTH INTERVAL			
5536, 5543, 5562-68' (CIBP @ 5450')				AMOUNT AND KIND MATERIAL USED			
4482-4492'				5804 - 30 A/750 gals			
				5536 - 68 F/23000 gals & 28580 lbs sand			
				4482 - 4492 F/8500 gals & 8000 lbs 16/30 sand			
28. PRODUCTION							
Date First Production 9/24/04		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping 1 3/4" x 1 1/2" x 12' insert pump			Well Status (Prod. or Shut-in) Not producing		
Date of Test None	Hours Tested	Choke Size	Prod'n For Test Period	Oil - Bbl	Gas - MCF	Water - Bbl.	
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.)	
29. Disposition of Gas (Sold, used for fuel, vented, etc.)						Test Witnessed By	
30. List Attachments							
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief							
Signature <i>David L. Henderson</i>			Name: David L. Henderson		Title: Exec. V-P	Date: 3/12/2010	
E-mail Address dhenderson@seelyoil.com							

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy 1750	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt 1868	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt 3090	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 3296	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 3560	T. Devonian	T. Menefee	T. Madison
T. Queen 4470	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Delaware Sand	T. Todilto	T.
T. Drinkard	T. Bone Springs	T. Entrada	T.
T. Abo	T.	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from 4480 to 4492

No. 3, from.....to.....

No. 2, from.....to.....

No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....

No. 2, from.....to.....feet.....

No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology	From	To	Thickness In Feet	Lithology
0	1750	1750'	Red bed, anhydrite				
1751	1868	118'	Anhydrite				
1869	3090	1221'	Salt				
3091	3296	205'	Anhydrite				
3297	4040	743'	Anhydrite, sand				
4041	4470	429'	Dolomite, anhydrite				
4471	4550	79'	Sand				
4551	4940	489'	Anhydrite				
4941	6050	1109'	Dolomite, Sand				