

JAN 14 1935
ROSWELL, NEW MEXICO

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

U.S. Land Office Las Cruces
New Mexico
Serial Number 029321
Lease or Permit Permit

30-025-00930

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	☒	SUBSEQUENT RECORD OF SHOOTING.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		RECORD OF PERFORATING CASING.....	
NOTICE OF DATE FOR TEST OF WATER SHUT-OFF.....		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING.....	
REPORT ON RESULT OF TEST OF WATER SHUT-OFF.....		NOTICE OF INTENTION TO ABANDON WELL.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO SHOOT.....		SUPPLEMENTARY WELL HISTORY.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Fort Worth, Texas, January 11, 1935.

Following is a notice of intention to do work on land under permit described as follows:

New Mexico (State or Territory) Lea (County or Subdivision) No designated field (Field)
Well No. 1 NE 1/4 Sec. 6, 20 S., 32 E., N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

The well is located 750 ft. N of S line and 990 ft. E of W line of sec. 6
The elevation of the derrick floor above sea level is 3525 ft. (approximately)

DETAILS OF PLAN OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work.)

Well will be drilled entirely with cable tools. Following horizons expected at approximate depths indicated:

Top Anhydrite 750'
Top Salt 900'
Base Salt 2450'
Top Brown Lime 2500'
Top White " 3000'
Probable Total Depth 3100'

(See Reverse Side for Casing Program)

See attached sheet for conditions of approval.

Approved January 16, 1935 (Date)
Supervisor, Oil & Gas Operations By J. R. Bohagan
Title Thomas G. Taylor, Engineer Title Vice-President
Address Roswell, New Mexico Address 1005 Ft. Worth Natl. Bank Bldg.
Fort Worth, Texas.

NOTE.—Reports on this form to be submitted in triplicate to the Supervisor for approval.

We plan to use following sizes and approximate amounts of casing, the exact amount to be determined as drilling progresses:

- 650' of 10" 40# Second Hand. Thru Red Bed Water.
- 1000' of 8" 32# New Lapweld. Cemented approximately 40 sacks which calculate will cement nearly up to 10" string.
- 2950' of 7" OD24#. New. To be cemented if get production.

(1) 1000' of 8" 32# New Lapweld. Cemented approximately 40 sacks which calculate will cement nearly up to 10" string.

1000' of 8" 32# New Lapweld. Cemented approximately 40 sacks which calculate will cement nearly up to 10" string.

The elevation of the ground surface at the well site is 1000 feet above sea level. The elevation of the casing head is 1000 feet above sea level. The elevation of the casing shoe is 1000 feet above sea level.

The well is located in the 1000' of 8" 32# New Lapweld. Cemented approximately 40 sacks which calculate will cement nearly up to 10" string.

The well is located in the 1000' of 8" 32# New Lapweld. Cemented approximately 40 sacks which calculate will cement nearly up to 10" string.

1000' of 8" 32# New Lapweld. Cemented approximately 40 sacks which calculate will cement nearly up to 10" string.	1000' of 8" 32# New Lapweld. Cemented approximately 40 sacks which calculate will cement nearly up to 10" string.
1000' of 8" 32# New Lapweld. Cemented approximately 40 sacks which calculate will cement nearly up to 10" string.	1000' of 8" 32# New Lapweld. Cemented approximately 40 sacks which calculate will cement nearly up to 10" string.
1000' of 8" 32# New Lapweld. Cemented approximately 40 sacks which calculate will cement nearly up to 10" string.	1000' of 8" 32# New Lapweld. Cemented approximately 40 sacks which calculate will cement nearly up to 10" string.
1000' of 8" 32# New Lapweld. Cemented approximately 40 sacks which calculate will cement nearly up to 10" string.	1000' of 8" 32# New Lapweld. Cemented approximately 40 sacks which calculate will cement nearly up to 10" string.
1000' of 8" 32# New Lapweld. Cemented approximately 40 sacks which calculate will cement nearly up to 10" string.	1000' of 8" 32# New Lapweld. Cemented approximately 40 sacks which calculate will cement nearly up to 10" string.
1000' of 8" 32# New Lapweld. Cemented approximately 40 sacks which calculate will cement nearly up to 10" string.	1000' of 8" 32# New Lapweld. Cemented approximately 40 sacks which calculate will cement nearly up to 10" string.

RECEIVED BY THE BUREAU OF MINES

GEOLOGICAL SURVEY
DEPARTMENT OF THE INTERIOR

RECEIVED BY THE BUREAU OF MINES
DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY
BUREAU OF LAND MINERALS

APPROVAL TO DRILL is given as outlined above with the understanding that the following general and special requirements be strictly complied with:

GENERAL

1. All water to be confined to its original horizon and test made for water shut-off before drilling ahead. Casing shall be cemented if necessary to shut off water.
2. All showings of oil or gas to be tested for their commercial possibilities in a dry hole before drilling ahead. Each showing to be properly protected to prevent migration.
3. To prevent waste of, or damage to, and to provide the U. S. Geological Survey with carefully taken samples of, other minerals drilled through, i. e., coal, salt, potash, beds, etc.
4. The permittee shall permanently mark all rigs or wells in a conspicuous place with his name or the name of the actual operator and the number and description of the well, and shall take all necessary precautions to preserve these markings.
5. Notify the U. S. Geological Survey office, P. O. Box 591, Roswell, New Mexico, on form 9-331a, of mudding, cementing, and water shut-off tests a sufficient time in advance in order that an engineer of the Survey may be present.
6. Lessee's monthly report, in triplicate on form 9-329, must be filled out each calendar month and forwarded to the Roswell office not later than the 6th day of the following month.

SPECIAL

1. Any change of drilling plan, or the conditions of approval, must have the written approval of the District Engineer before the change is made.
2. Carefully taken samples of drill cuttings must be taken at least every ten feet from 200 feet from surface to bottom of hole, and submitted through approved agent or directly to the U. S. Geological Survey, Roswell, New Mexico office.
3. Approval conditioned on mudding the 10-inch casing to the surface and circulating the 8-1/4-inch casing with heavy mud before cementing with 40 sacks.