New Mexico Energy, Minerals and Natural Resources Department

Bill Richardson Governor

Joanna Prukóp Cabinet Secretary Reese Fullerton Deputy Cabinet Secretary Mark Fesmire Division Director Oil Conservation Division



Administrative Order WFX-850

January 27, 2009

Tony Beilman Melrose Operating Company 1000 W. Wilshire, Suite 223 Oklahoma City, OK 73116

# ADMINISTRATIVE ORDER OF THE OIL CONSERVATION DIVISION

Under the provisions of Division Order R-2243, Melrose Operating Company (OGRID No. 184860) has made application to the Division for permission to add five water injection wells to its Jalmat Field Yates Sand Unit Waterflood Project located within the Jalmat;Tansill-Yates-SevenRivers Oil Pool (33820) in Lea County, New Mexico.

## THE DIVISION DIRECTOR FINDS THAT:

The application was filed in due form. No objections have been filed within the waiting period prescribed by Division Rule 26.8C.(2). The proposed injection wells are eligible for conversion to injection under the terms of Rule 26.8. The operator is in compliance with Rule 5.9.

The proposed expansion of the above-referenced waterflood project, will prevent waste, is in the best interests of conservation, will not impair correlative rights, and should be approved.

### IT IS THEREFORE ORDERED THAT:

Melrose Operating Company is hereby authorized to inject water into the unitized interval, through plastic-lined tubing set in packers located within 100 feet of the top of the injection intervals in the following-described wells for purposes of secondary recovery:

Oil Conservation Division \* 1220 South St. Francis Drive \* Santa Fe, New Mexico 87505 \* Phone: (505) 476-3440 \* Fax (505) 476-3462\* <u>http://www.emnrd.state.nm.us</u>

#### Administrative Order WFX-850 Mélrose Operating Company January 27, 2009 Page 2 of 3

									•	
API	Well Num	Unit	Sec	<u> </u>	Rge	Top Perf	Bot Perf		Pressure	<u>Comments</u>
30-025-08595	106	c	11	_22S	,35E	3874	4035	2-3/8	775	
30-025-33679	167	ļ,Ą,	11	225	.35É	3806	3913	2-3/8	761	
30-025-37492	223_	.0	11	22S	35E	3854	3997	2-3/8	<u>7</u> 71	
30-025-37498	224	Ρ.	11	.22S	35E_	3832	3972,	2-3/8	766,	·
30-025-38921	107	В	11	22S	35E	3850	. 4075	2-3/8*	<u>7</u> 70 .	
30-025-38922	249	. 1	. 11	22S	35E	. 37,00	. 4200	.2-3/8	740	Est Perfs
30-025-38923	Î 68	M	12,	225.	35E	3808	<b></b>	2*3/8	762 1	<u> </u>
30-025-38924	178	, N	. 12	22S	35E	3724	,3852	2-3/8	745	
30-025-38926	233	0	2	22S	_35E	3811	,4034	2-3/8	7,62	<u></u>
30-025-38927	234	Р	2	228	.35Ë	3818	3992	. 2-3/8	764 .	
30-025-38928	235	A	11.		.35E	3808	4098 _	.2-3/8	762	<u></u>
30-025-38929	236	E	12	22S	35È	3700	4200	2-3/8	740	Ëst Perfs
30-025-38930	237	L	.12	, 22S	35E	3806	4072	_ 2-3/8	761	
30-025-38932	_ 240	N	2	22S.	35E	3834	4041	2-3/8	767	• •
30-025-38933	241	М	. 2	22S	35E	3835	4052	,2-3/8	7,67	
30-025-38934	243	Ê	1,1	225	35E	3700	.4200 .	.2-3/8	740	Est Perfs
30-025-38941	242	D	11.	225	35E	3795	3890	2-3/8	759	· · ·

#### IT IS FURTHER ORDERED THAT:

The operator shall take all steps necessary to ensure that the injected water enters only the proposed injection interval and is not permitted to escape to other formations or onto the surface.

Prior to commencing injection operations into these wells, the casing shall be pressure tested from the surface to the packer setting depth to assure casing integrity.

The casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge at the surface or left open to the atmosphere to facilitate detection of leakage in the casing, tubing or packer.

The injection wells or injection system shall be equipped with pressure limiting devices which will limit the wellhead pressure to the maximum surface injection pressure described above.

The Director of the Division may authorize increases in injection pressure upon a proper showing by the operator that higher pressure will not result in migration of the injected fluid from the permitted injection interval or harmful formation fracturing. Such proper showing shall consist of valid step-rate tests and possibly injection profiles or pressure transient testing run in accordance with and acceptable to this office.

The operator shall notify the supervisor of the District Office of the date and time of the installation of injection equipment and of all mechanical integrity tests so that the same may be inspected and witnessed.

.

Administrative Order WFX-850 Melrose Operating Company January 27, 2009 Page 3 of 3

The operator shall immediately notify the supervisor of the District Office of the failure of the tubing, casing or packer in said wells and shall take such steps as may be timely and necessary to correct such failure or leakage.

The subject wells shall be governed by all provisions of Division Order No. R-2243, and Rules 26.9 through 26.13 not inconsistent herewith.

<u>PROVIDED FURTHER THAT</u>, jurisdiction is retained by the Division for the entry of such further ofders as may be necessary for the prevention of waste and/or protection of correlative rights or upon failure of the operator to conduct operations (1) to protect fresh water or (2) consistent with the requirements in this order, whereupon the Division may, after notice and hearing, terminate the injection authority granted herein.

The injection authority granted herein shall terminate one year after the effective date of this order if the operator has not commenced injection operations into at least one of the subject wells, provided however, the Division, upon written request by the operator received prior to the one year deadline, may grant an extension thereof for good cause shown.

<sup>2</sup> MARK E. FESMIRE, P.E. Director

MEF/wvjj

cc: Oil Conservation Division – Hobbs