Submit 3 Copies To Appropriate District Office State of New Mexico	Form C-103
<u>District I</u> Energy, Minerals and Natural Re	sources May 27, 2004 WELL API NO.
1625 N. French Dr., Hobbs, NM 88240 District II	20.005.00656
District II 1301 W. Grand Ave., Artesia, NM 88210 District III 1000 Rio Prazza Rd. Artes. NM 87410	SION
1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S St. Francis Dr., Santa Fe, NM	5. Indicate Type of Lease STATE X FEE
07505	6. State Oil & Gas Lease No. B-11223-2
HOBBSOUD	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BAC DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	
PROPOSALS.) 1. Type of Well: Oil Well X Gas Well Other	8. Well Number #802
2. Name of Operator	9. OGRID Number 184860 /
Melrose Operating 3. Address of Operator	10. Pool name or Wildcat
1000 W. Wilshire, Suite 223 Oklahoma City OK 73116	Jalmat, Tansil, Yates, 7-Rivers
4. Well Location	
	ne and660feet from theWestline
Section 25 Township 22S Rang	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3576' GL Pit or Below-grade Tank Application or Closure	
Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water	
Pit Liner Thickness: mil Below-Grade Tank: Volume	bbls; Construction Material
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
	EDIAL WORK
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DRILLING OPNS.☐ P AND A ☐	
PULL OR ALTER CASING	
OTHER: OTHE	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion	
or recompletion.	
Proposal to Plug & Abandon: CJYPU #802	
0.5 /0" C+ 20.6' TOC o+ Surface	
8 5/8" Csg at 306' TOC at Surface The Oil Conservation Division Must be notified 24 hours prior to the beginning of plugging operations	
5 ½" Csg at 3965' TOC at 470' 24 hours prior to the beginning of plugging operations. Perfed: 3753'-3862'	
Top of Salt 1750' Bottom of Salt 3606'	
Top of Yates 3744'	
<i>10-29-09</i>	
Propose to Plug Well: (1) SET CIPB AT 3703', Spot 40sx "C" Cement @14.8/1.32 on top of CIBP	
(2) Spot 50sx Plug "C" CEMENT @14.8#/1.32 @ 1700'	
(3) Perf. @ 356' & Circ "C" CEMENT @14.8# / 1.32yield TO SURFACE, cut off wellheads, weld	
on dry hole marker, cut off guy line ancho	ors & clean up location!
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan .	
SIGNATURE Oct. 29, 2009	
Type or print name Cam Robbins E-mail address: max For State Use Only	ximum@valornet.com Telephone No.575-390-4666
APPROVED BY:	944 MGZ DATE 5-26-10