

Submit 3 Copies To Appropriate District Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
May 27, 2004

RECEIVED  
MAY 26 2010  
HOBBSOCD

CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-025-23977 ✓
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/> ✓
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Vivian ✓
8. Well Number 3 ✓
9. OGRID Number 246289 ✓
10. Pool name or Wildcat Brunson; Drinkard-ABO, South 07900 ✓

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/>	
2. Name of Operator RKI Exploration and Production, LLC. ✓	
3. Address of Operator 3817 NW Expressway, Suite 950, Oklahoma City, OK. 73112	
4. Well Location Unit Letter <u>D</u> : <u>660'</u> feet from the <u>South</u> line and <u>1980'</u> feet from the <u>West</u> line Section <u>30</u> Township <u>22S</u> Range <u>38E</u> NMPM <u>Lea</u> County ✓	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,329' GR	
Pit or Below-grade Tank Application <input type="checkbox"/> or Closure <input type="checkbox"/>	
Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____	
Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☒  
CASING/CEMENT JOB ☐  
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

5-3-10 to 5-17-10 Per GS

5-17-10

Do to casing failure 4279' was as close as we could get to the 1<sup>st</sup> perf depth of 6318' as requested by OCD to P&A this well.

RIH WITH 3 5/8" TAPERED MILL, 122 JTS TBG TAG @ 3977'. SIT 4 PTS FALL THROUGH TIGHT SPOT. 4 PTS TO PULL BACK THROUGH IT. RIG UP POWER SWIVEL AND CIRC. EQUIP. ROTATE MILL THROUGH TIGHT SPOT UNTIL FREE. CONT IN HOLE ROTATE/MILL TIGHT SPOTS. TAG AT TOP AND BOTTOM OF EACH JT. ROTATE 1/2 TURN AND FALL THROUGH. WITH SWIVEL. IF ROTATING TBG NO DRAG. WHEN PULLING AND RUNNING THROUGH TIGHT SPOTS. IF NO ROTATION TAKE 6-8 PTS TO PULL THROUGH TIGHT SPOTS. TAG SOLID @ 4279'. RIH 102 JTS TBG (ABOVE BAD CASING) SHUT WELL IN. SDFN. NDP: WILL RIH 10 STANDS TO A DEPTH OF 4279 AND START CEMENTING PROCEDURE.

PUMP 182 SX (43 BBLs) C NEAT CEMENT. NO PRESSURE. VACUUM. POOH TBG. DISPLACE CEMENT TO 2300' WITH 35 BBLs H2O. WOC 5 HRS. RIH TBG TO BOTTOM. DID NOT TAG CEMENT. RIG UP AND PUMP 182 SX C NEAT CEMENT WITH 1% CALCIUM CHLORIDE. POOH TBG. DISPLACE TO 2300' WITH 35 BBLs H2O. SHUT WELL IN. SDFN  
NDP: RIH TAG BOTTOM AND PUMP CEMENT AS PER OCD. PUMP 164 SX (38 BBLs) C NEAT CEMENT WITH 1% CALCIUM CHLORIDE. 400 PSI. POOH TBG. DISPLACE CEMENT TO 2300' WITH 12.4 BBLs H2O. NO PRESSURE. WOC 2 HRS. RIH TBG/MULESHOE TAG @ 3015'. PUMP 50 SX (12.7 BBLs) 3% CALCIUM CHLORIDE 400 PSI. POOH TBG. WOC 1 HR. RIH TBG/MULESHOE TAG @ 2531'. PUMP 21 SX (7 BBLs) C NEAT CEMENT. POOH TBG. SHUT WELL IN. SDFN.  
599 TOTAL SX CEMENT PUMPED. TBG. TAG @ 2416'. LOAD WELL WITH 2 BBLs H2O. PRESSURE TEST TO 500 PSI. HELD OK PUMP 26 SX (6.6 BBLs) C NEAT CEMENT 3% CALCIUM CHLORIDE 400 PSI. POOH TBG. RIH TBG TAG @ 2110'. (OCD REQUESTED 2300') LAY DOWN 93 JTS TBG. RIG UP GRAY WIRE LINE. SHOOT 4 CIRCULATING HOLES AT 1210'. RIG DOWN GRAY WIRE LINE. PUMP 5 BBLs IN 4 1/2" LOAD AND PRESSURE TO 500 PSI. HELD 500 PSI. RIH 39 JTS TBG TO 1268' PUMP 25X (5.8 BBLs) C NEAT CEMENT 3% CALCIUM CHLORIDE. POOH LAY DOWN TBG. RIG UP GRAY WIRELINE. TAG PLUG @ 920'. SHOOT 4 CIRCULATING HOLE AT 392'. RIG DOWN GRAY WIRE LINE. BREAK CIRCULATION WITH 2 BBLs H2O. ND BOP AND FLANGE UP WELLHEAD. CIRCULATE 106 SX (25 BBLs) WITH C NEAT CEMENT TO SURFACE DOWN 4 1/2" CASING UP THE 8 5/8" CSG. RIG-DOWN CEMENTING EQUIPMENT.  
756 SX TOTAL CEMENT PUMPED.

7.m.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Gene Simer TITLE SUPERINTENDENT DATE 5/20/10

Type or print name GENE SIMER E-mail address: gsimer@rkixp.com Telephone No. 505-885-1313  
**For State Use Only**

APPROVED BY: [Signature] TITLE State Mgr DATE 5-26-10  
Conditions of Approval (if any):