•			
BUREA	UNITED STATES TIMENT OF THE INTERIOR U OF LAND MANAGEMENT	FIDENTIAL	FORM APROVED OMB NO. 1004-0135 EXPIRES: March 31, 2007 Lease Serial No.
	m for proposals to drill or to re-enter an		. Lease Serial No. 7706- NMNM-68094
	e Form 3160-3 (APD) for such proposals	I IULNIIAL 6	. If Indian, Allottee or Tribe Name
SI	UBMIT IN TRIPLICATE	7	. Unit or CA Agreement Name and No.
a. Type of Well 🔽 Oil Well 🔲 Ga	as Well Other	/	. Unit of CA Agreement Name and No.
		8	Well Name and No.
			Mesa Verde 6 Federal 11
DEVON ENERGY PRODUCTION COMPANY, LP 3. Address and Telephone No.			30-025-39585
20 North Broadway, Oklahoma City, OK 73102-8260 405-552-8198			0. Field and Pool, or Exploratory
I. Location of Well (Report location clearly and in accordance with Federal requirements)*			Mesa Verde; Bone Springs
660 FSL 660 FEL P 6 24S 32E			1. County or Parish State
			Lea NM
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION			
	Acidize Deepen		(Start/Resume) Water Shut-Off
Notice of Intent	Alter Casing	reat 🗌 Reclamation	n Well Integrity
Subsequent Report	Casing Repair New Cons		
Final Abandonment Notice	Convert to Injection Plug Back		
eclamation, have been completed, and I/29/2010 MIRU PU. ND wellhead and I/30/2010 Tag DV tool at 6940' - pressu 3803'. Circulate hole clean. POOH with 2/01/2010 RIH with tubing bit and scrap 2/02/2010 RIH and perforate Bone Sprin 2/03/2010 RU and pump 1500 gallons o 2/08/2010 RIH with composite plug and	rre test casing to 2,000 psi - held. Drill out DV to tubing. er. Displace hole with 2% KCl. POOH with tubings from 9690'-9712', 2 spf, 120 degree phasing f 7 1/2" HCl acid. Frac with 22,262# 16/30 Sibe guns. Set composite plug at 9020'. Perforate to RIH with packer and tubing. Set packer at 892 .5% HCl acid. Swab well. 20'.	dy for final inspection) ool and RIH to 6976'. Test o ing, bit and scraper. ND BC g, 0.38 EHD holes; total 44 I prProp sand. Flow well back from 8970'-8976', 4 spf, 90 o 23'. Load casing and pressu	casing to 2,000 psi - held. RIH with tubing to DP and NU Frac valve. holes. RD. c. degree phasing, 0.41 EHD holes; total 28 holes
		[] (OBBSOCD
14 Thereby certify that the foregoing is	true and correct		
Signed 2		orvella Adams ngineering Technician	ACCEAPTED FOR PROFECORD
(This space for Federal or State Office u	se)		
Approved by Conditions of approval, if any:	Title		Date MAY 2 2 2010
The 18 USC. Secult Tout, makes it a chime for an	וין person knowingly and wiliduity to make any department or ag within its jurisdict		inclinous or fraudulem statements of representations to any matter
	*See Instruction on		BUREAU OF LAND MANAGEMENT
		Ka	

· · · · ·