

AMMENDMENT TO
04/08/10 APPROVED
C-144 CLOS PLAN

R. T. HICKS CONSULTANTS, LTD.

901 Rio Grande Blvd NW ▲ Suite F-142 ▲ Albuquerque, NM 87104 ▲ 505.266.5004 ▲ Fax: 505.266-0745

June 8, 2010

Mr. Geoffrey Leking
NMOCD District I
1625 French Drive
Hobbs, NM 88240
Via E-Mail

RECEIVED

JUN 08 2010

HOBBSOCD

RE: Lusk 31 Federal #3, Lynx Petroleum Consultants

Dear Geoffrey:

This submission is a new modification of our previously-approved permit. Lynx Petroleum Consultants requests approval for trench burial in full compliance with the mandates of NMOCD Rules and withdraws the request for an exception to NMOCD Rules. In order to assure that this submission represents a complete application, we include:

1. A C-144 form for the modification of the existing permit – signed by the operator
2. The previously-approved C-144
3. Documents required by item 11 of the C-144:
 - a. Hydrogeologic data (see also the previously-approved C-144)
 - b. Siting Criteria Compliance Demonstrations (see also the approved C-144)
 - c. Design Plan (attached)
 - d. Operating and Maintenance Plan (attached)
 - e. Closure Plan (attached)
4. Documents required by item 18 of the C-144
 - a. Siting Criteria Compliance Demonstration (see also the previously approved C-144)
 - b. Proof of Surface Owner Notice (see attached approved APD)
 - c. Construction/design Plan of Burial Trench (see attached)
 - d. Protocols and procedures (see attached)
 - e. Confirmation Sampling Plan (see attached)
 - f. Waste Material Sampling Plan (see attached)
 - g. Disposal Facility Name and Permit Number
 - h. Soil Cover Design (see attached)
 - i. Re-vegetation Plan (see attached)
 - j. Site Reclamation Plan (see attached)

We believe this submission will show that the pit design meets all of the criteria specified in NMOCD Rules. The NMOCD Artesia Office approved a similar design. If Lynx elects to request an exception to NMOCD Rules in the future, we will submit the request to the Environmental Bureau with a copy to your office.

Sincerely,
R.T. Hicks Consultants



Randall Hicks

Copy: Lynx Petroleum Consultants
Bureau of Land Management

AMENDMENT TO THE
64108110 APPROVED
C-144

Form C-144
July 21, 2008

District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

RECEIVED
JUN 08 2010
HOBBSOCD

State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

For temporary pits, closed-loop systems, and below-grade tanks, submit to the appropriate NMOCD District Office.
For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Closed-Loop System, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application

Type of action: ☐ Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method
☐ Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method
☒ Modification to an existing permit
☐ Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system, below-grade tank, or proposed alternative method

Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request

Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.

1.
Operator: Lynx Petroleum Consultants, OGRID #: 013645
Address: PO Box 1708, Hobbs NM 88241
Facility or well name: Lusk 31 Federal #3
API Number: 30-025-39593 OCD Permit Number: P1-01553
U/L or Qtr/Qtr NW/SE Section 31 Township 18S Range 32E County: Lea
Center of Proposed Design: Latitude 32 42 07.04 Longitude -103 48 13.75 NAD: ☐ 1927 ☒ 1983
Surface Owner: ☒ Federal ☐ State ☐ Private ☐ Tribal Trust or Indian Allotment

2.
☒ **Pit:** Subsection F or G of 19.15.17.11 NMAC
Temporary: ☒ Drilling ☐ Workover
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A
☒ Lined ☐ Unlined Liner type: Thickness 20 mil ☒ LLDPE ☐ HDPE ☐ PVC ☐ Other _____
☒ String-Reinforced
Liner Seams: ☒ Welded ☒ Factory ☐ Other _____ Volume: 13000 bbl Dimensions: L 130 x W 90 x D 9

3.
☐ **Closed-loop System:** Subsection H of 19.15.17.11 NMAC
Type of Operation: ☐ P&A ☐ Drilling a new well ☐ Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent)
☐ Drying Pad ☐ Above Ground Steel Tanks ☐ Haul-off Bins ☐ Other _____
☐ Lined ☐ Unlined Liner type: Thickness _____ mil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other _____
Liner Seams: ☐ Welded ☐ Factory ☐ Other _____

4.
☐ **Below-grade tank:** Subsection I of 19.15.17.11 NMAC
Volume: _____ bbl Type of fluid: _____
Tank Construction material: _____
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other _____
Liner type: Thickness _____ mil ☐ HDPE ☐ PVC ☐ Other _____

5.
☐ **Alternative Method:**
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

6.	<p>Fencing: Subsection D of 19.15.17.11 NMAC (<i>Applies to permanent pits, temporary pits, and below-grade tanks</i>)</p> <p><input type="checkbox"/> Chain link, six feet in height, two strands of barbed wire at top (<i>Required if located within 1000 feet of a permanent residence, school, hospital, institution or church</i>)</p> <p><input checked="" type="checkbox"/> Four foot height, four strands of barbed wire evenly spaced between one and four feet</p> <p><input type="checkbox"/> Alternate. Please specify _____</p>																				
7.	<p>Netting: Subsection E of 19.15.17.11 NMAC (<i>Applies to permanent pits and permanent open top tanks</i>)</p> <p><input type="checkbox"/> Screen <input type="checkbox"/> Netting <input type="checkbox"/> Other _____ Not Applicable _____</p> <p><input type="checkbox"/> Monthly inspections (If netting or screening is not physically feasible)</p>																				
8.	<p>Signs: Subsection C of 19.15.17.11 NMAC</p> <p><input type="checkbox"/> 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers</p> <p><input checked="" type="checkbox"/> Signed in compliance with 19.15.3.103 NMAC</p>																				
9.	<p>Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.</p> <p>Please check a box if one or more of the following is requested, if not leave blank:</p> <p><input checked="" type="checkbox"/> Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval.</p> <p><input type="checkbox"/> Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.</p>																				
10.	<p>Siting Criteria (regarding permitting): 19.15.17.10 NMAC</p> <p>Instructions: <i>The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above-grade tanks associated with a closed-loop system.</i></p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 80%; padding: 5px;"> Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells SEE FIGURE </td> <td style="width: 20%; text-align: center; vertical-align: top;"> <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No </td> </tr> <tr> <td style="padding: 5px;"> Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site SEE FIGURE </td> <td style="text-align: center; vertical-align: top;"> <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No </td> </tr> <tr> <td style="padding: 5px;"> Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (<i>Applies to temporary, emergency, or cavitation pits and below-grade tanks</i>) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image SEE Figure </td> <td style="text-align: center; vertical-align: top;"> <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> NA </td> </tr> <tr> <td style="padding: 5px;"> Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (<i>Applies to permanent pits</i>) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image SEE figure </td> <td style="text-align: center; vertical-align: top;"> <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> NA </td> </tr> <tr> <td style="padding: 5px;"> Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Figure </td> <td style="text-align: center; vertical-align: top;"> <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No </td> </tr> <tr> <td style="padding: 5px;"> Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. SEE FIGURE - Written confirmation or verification from the municipality; Written approval obtained from the municipality </td> <td style="text-align: center; vertical-align: top;"> <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No </td> </tr> <tr> <td style="padding: 5px;"> Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Figure </td> <td style="text-align: center; vertical-align: top;"> <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No </td> </tr> <tr> <td style="padding: 5px;"> Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division SEE FIGURE </td> <td style="text-align: center; vertical-align: top;"> <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No </td> </tr> <tr> <td style="padding: 5px;"> Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map SEE EXPLANATION and Figure </td> <td style="text-align: center; vertical-align: top;"> <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No </td> </tr> <tr> <td style="padding: 5px;"> Within a 100-year floodplain. - FEMA map No FEMA Map exists, see explanation in text </td> <td style="text-align: center; vertical-align: top;"> <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No </td> </tr> </table>	Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells SEE FIGURE	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site SEE FIGURE	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (<i>Applies to temporary, emergency, or cavitation pits and below-grade tanks</i>) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image SEE Figure	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> NA	Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (<i>Applies to permanent pits</i>) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image SEE figure	<input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> NA	Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Figure	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. SEE FIGURE - Written confirmation or verification from the municipality; Written approval obtained from the municipality	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Figure	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division SEE FIGURE	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map SEE EXPLANATION and Figure	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Within a 100-year floodplain. - FEMA map No FEMA Map exists, see explanation in text	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells SEE FIGURE	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No																				
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site SEE FIGURE	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No																				
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (<i>Applies to temporary, emergency, or cavitation pits and below-grade tanks</i>) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image SEE Figure	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> NA																				
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (<i>Applies to permanent pits</i>) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image SEE figure	<input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> NA																				
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Figure	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No																				
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. SEE FIGURE - Written confirmation or verification from the municipality; Written approval obtained from the municipality	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No																				
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Figure	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No																				
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division SEE FIGURE	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No																				
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map SEE EXPLANATION and Figure	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No																				
Within a 100-year floodplain. - FEMA map No FEMA Map exists, see explanation in text	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No																				

11.
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.

- ☐ Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC
- ☒ Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC
- ☒ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC
- ☒ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
- ☒ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
- ☒ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
- ☐ Previously Approved Design (attach copy of design) API Number: _____ or Permit Number: _____

12.
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.

- ☐ Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9
- ☐ Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC
- ☐ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
- ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
- ☐ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
- ☐ Previously Approved Design (attach copy of design) API Number: _____
- ☐ Previously Approved Operating and Maintenance Plan API Number: _____ (Applies only to closed-loop system that use above ground steel tanks or haul-off bins and propose to implement waste removal for closure)

13.
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.

- ☐ Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC
- ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC
- ☐ Climatological Factors Assessment
- ☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC
- ☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC
- ☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC
- ☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC
- ☐ Quality Control/Quality Assurance Construction and Installation Plan
- ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
- ☐ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
- ☐ Nuisance or Hazardous Odors, including H₂S, Prevention Plan
- ☐ Emergency Response Plan
- ☐ Oil Field Waste Stream Characterization
- ☐ Monitoring and Inspection Plan
- ☐ Erosion Control Plan
- ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC

14.
Proposed Closure: 19.15.17.13 NMAC
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.

- Type: ☒ Drilling ☐ Workover ☐ Emergency ☐ Cavitation ☐ P&A ☐ Permanent Pit ☐ Below-grade Tank ☐ Closed-loop System
☐ Alternative
- Proposed Closure Method: ☐ Waste Excavation and Removal
☐ Waste Removal (Closed-loop systems only)
☒ On-site Closure Method (Only for temporary pits and closed-loop systems)
☐ In-place Burial ☒ On-site Trench Burial SEE EXPLANATION
☐ Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)

15.
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) **Instructions:** Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.

- ☐ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC
- ☐ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC
- ☐ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)
- ☐ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC
- ☐ Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC
- ☐ Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC

16.

Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: (19.15.17.13.D NMAC)

Instructions: Please identify the facility or facilities for the disposal of liquids, drilling fluids and drill cuttings. Use attachment if more than two facilities are required.

Disposal Facility Name: _____ Disposal Facility Permit Number: _____

Disposal Facility Name: _____ Disposal Facility Permit Number: _____

Will any of the proposed closed-loop system operations and associated activities occur on or in areas that *will not* be used for future service and operations?

☐ Yes (If yes, please provide the information below) ☐ No

Required for impacted areas which will not be used for future service and operations:

☐ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC

☐ Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC

☐ Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC

17.

Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC

Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.

Ground water is less than 50 feet below the bottom of the buried waste.

- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells

☐ Yes ☒ No
☐ NA

Ground water is between 50 and 100 feet below the bottom of the buried waste

- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells

☐ Yes ☒ No
☐ NA

Ground water is more than 100 feet below the bottom of the buried waste.

- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells

☒ Yes ☐ No
☐ NA

Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).

- Topographic map; Visual inspection (certification) of the proposed site

☐ Yes ☒ No

Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.

- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image

☐ Yes ☒ No

Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.

- NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site

☐ Yes ☒ No

Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.

- Written confirmation or verification from the municipality; Written approval obtained from the municipality

☐ Yes ☒ No

Within 500 feet of a wetland.

- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site

☐ Yes ☒ No

Within the area overlying a subsurface mine.

- Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division

☐ Yes ☒ No

Within an unstable area.

- Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map

☐ Yes ☒ No

Within a 100-year floodplain.

- FEMA map

☐ Yes ☒ No

18.

On-Site Closure Plan Checklist: (19.15.17.13 NMAC) **Instructions:** Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.

☒ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC

☒ Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC

☒ Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC

☐ Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.11 NMAC

☒ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC

☒ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC

☒ Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC

☒ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved)

☒ Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC

☒ Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC

☒ Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC

19.

Operator Application Certification:

I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.

Name (Print): Larry R. Scott Title: President

Signature: *Larry R. Scott* Date: June 8, 2010

e-mail address: lrscott@leaco.net Telephone: 575-392-6950

20.

OCD Approval: ☐ Permit Application (including closure plan) ☒ Closure Plan (only) ☐ OCD Conditions (see attachment)

AMENDED FROM 0410P110

OCD Representative Signature: *Jeffrey L. King* **Approval Date:** 06/16/10

Title: Environmental Engineer **OCD Permit Number:** P1-01553

21.

Closure Report (required within 60 days of closure completion): Subsection K of 19.15.17.13 NMAC

Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed.

☐ Closure Completion Date: _____

22.

Closure Method:

☐ Waste Excavation and Removal ☒ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-loop systems only)
☐ If different from approved plan, please explain.

23.

Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only:

Instructions: Please indentify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than two facilities were utilized.

Disposal Facility Name: _____ Disposal Facility Permit Number: _____

Disposal Facility Name: _____ Disposal Facility Permit Number: _____

Were the closed-loop system operations and associated activities performed on or in areas that *will not* be used for future service and operations?

☐ Yes (If yes, please demonstrate compliance to the items below) ☐ No

Required for impacted areas which will not be used for future service and operations.

- ☐ Site Reclamation (Photo Documentation)
☐ Soil Backfilling and Cover Installation
☐ Re-vegetation Application Rates and Seeding Technique

24.

Closure Report Attachment Checklist: *Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.*

- ☐ Proof of Closure Notice (surface owner and division)
☐ Proof of Deed Notice (required for on-site closure)
☐ Plot Plan (for on-site closures and temporary pits)
☐ Confirmation Sampling Analytical Results (if applicable)
☐ Waste Material Sampling Analytical Results (required for on-site closure)
☐ Disposal Facility Name and Permit Number
☐ Soil Backfilling and Cover Installation
☐ Re-vegetation Application Rates and Seeding Technique
☐ Site Reclamation (Photo Documentation)

On-site Closure Location: Latitude _____ Longitude _____ NAD: ☐ 1927 ☐ 1983

25.

Operator Closure Certification:

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.

Name (Print): _____ Title: _____

Signature: _____ Date: _____

e-mail address: _____ Telephone: _____

RECEIVED

Form C-144
July 21, 2008

District I
1625 N French Dr, Hobbs, NM 88240
District II
1301 W Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S St Francis Dr, Santa Fe, NM 87505

DEC 09 2009
State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

For temporary pits, closed-loop systems, and below-grade tanks, submit to the appropriate NMOCD District Office.
For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Closed-Loop System, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application

Type of action: ☒ Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method
☐ Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method
☐ Modification to an existing permit
☐ Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system, below-grade tank, or proposed alternative method

Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request

Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.

1. Operator: **Lynx Petroleum Consultants, Inc.** OGRID #: **013645**
Address: **P.O. Box 1708, Hobbs, NM 88241**
Facility or well name: **Lusk "31" Federal No. 3**
API Number: **30-025-39593** OCD Permit Number: **PI-01553**
U/L or Qtr/Qtr: **NW/4SE/4** Section **31** Township **18S** Range **32E** County **Lea**
Center of Proposed Design: Latitude **32°42'07.04" N** Longitude **103°48'13.75" W** NAD: ☐ 1927 ☒ 1983
Surface Owner: ☒ Federal ☐ State ☐ Private ☐ Tribal Trust or Indian Allotment

2. ☒ Pit: Subsection F or G of 19.15.17.11 NMAC
Temporary: ☒ Drilling ☐ Workover
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A
☒ Lined ☐ Unlined Liner type: Thickness **20** mil ☒ LLDPE ☐ HDPE ☐ PVC ☐ Other _____
☒ String-Reinforced
Liner Seams: ☒ Welded ☐ Factory ☐ Other _____ Volume: **15,500** bbl Dimensions: L **150** x W **150** x D **8**

3. ☐ Closed-loop System: Subsection H of 19.15.17.11 NMAC
Type of Operation ☐ P&A ☐ Drilling a new well ☐ Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent)
☐ Drying Pad ☐ Above Ground Steel Tanks ☐ Haul-off Bins ☐ Other _____
☐ Lined ☐ Unlined Liner type Thickness _____ mil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other _____
Liner Seams: ☐ Welded ☐ Factory ☐ Other _____

4. ☐ Below-grade tank: Subsection I of 19.15.17.11 NMAC
Volume: _____ bbl Type of fluid: _____
Tank Construction material: _____
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other _____
Liner type Thickness _____ mil ☐ HDPE ☐ PVC ☐ Other _____

5. ☐ Alternative Method:
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

6.
Fencing: Subsection D of 19.15.17.11 NMAC (*Applies to permanent pits, temporary pits, and below-grade tanks*)
☐ Chain link, six feet in height, two strands of barbed wire at top (*Required if located within 1000 feet of a permanent residence, school, hospital, institution or church*)
☒ Four foot height, four strands of barbed wire evenly spaced between one and four feet
☐ Alternate. Please specify _____

7.
Netting: Subsection E of 19.15.17.11 NMAC (*Applies to permanent pits and permanent open top tanks*)
☐ Screen ☐ Netting ☐ Other _____
☒ Monthly inspections (If netting or screening is not physically feasible)

8.
Signs: Subsection C of 19.15.17.11 NMAC
☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers
☒ Signed in compliance with 19.15.3.103 NMAC

9.
Administrative Approvals and Exceptions:
Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.
Please check a box if one or more of the following is requested, if not leave blank:
☐ Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval.
☐ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

10.
Siting Criteria (regarding permitting): 19.15.17.10 NMAC
Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above-grade tanks associated with a closed-loop system.

Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS, Data obtained from nearby wells	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark) - Topographic map, Visual inspection (certification) of the proposed site	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application (<i>Applies to temporary, emergency, or cavitation pits and below-grade tanks</i>) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> NA
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (<i>Applies to permanent pits</i>) - Visual inspection (certification) of the proposed site, Aerial photo, Satellite image	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> NA
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Within an unstable area. - Engineering measures incorporated into the design, NM Bureau of Geology & Mineral Resources. USGS, NM Geological Society; Topographic map	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Within a 100-year floodplain. - FEMA map	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No

11. **Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist:** Subsection B of 19.15.17.9 NMAC
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.

☐ Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC

☒ Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC

☒ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC

☒ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC

☒ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC

☒ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC

☐ Previously Approved Design (attach copy of design) API Number: _____ or Permit Number: _____

12. **Closed-loop Systems Permit Application Attachment Checklist:** Subsection B of 19.15.17.9 NMAC
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.

☐ Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9

☐ Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC

☐ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC

☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC

☐ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC

☐ Previously Approved Design (attach copy of design) API Number: _____

☐ Previously Approved Operating and Maintenance Plan API Number: _____ (Applies only to closed-loop system that use above ground steel tanks or haul-off bins and propose to implement waste removal for closure)

13. **Permanent Pits Permit Application Checklist:** Subsection B of 19.15.17.9 NMAC
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.

☐ Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC

☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC

☐ Climatological Factors Assessment

☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC

☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC

☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC

☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC

☐ Quality Control/Quality Assurance Construction and Installation Plan

☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC

☐ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC

☐ Nuisance or Hazardous Odors, including H₂S, Prevention Plan

☐ Emergency Response Plan

☐ Oil Field Waste Stream Characterization

☐ Monitoring and Inspection Plan

☐ Erosion Control Plan

☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC

14. **Proposed Closure:** 19.15.17.13 NMAC
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.

Type: ☒ Drilling ☐ Workover ☐ Emergency ☐ Cavitation ☐ P&A ☐ Permanent Pit ☐ Below-grade Tank ☐ Closed-loop System

☐ Alternative

Proposed Closure Method: ☐ Waste Excavation and Removal

☐ Waste Removal (Closed-loop systems only)

☒ On-site Closure Method (Only for temporary pits and closed-loop systems)

☒ In-place Burial ☐ On-site Trench Burial

☐ Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)

15. **Waste Excavation and Removal Closure Plan Checklist:** (19.15.17.13 NMAC) *Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.*

☐ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC

☐ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC

☐ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)

☐ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC

☐ Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC

☐ Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC

16. **Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only:** (19.15.17.13.D NMAC)
Instructions: Please identify the facility or facilities for the disposal of liquids, drilling fluids and drill cuttings. Use attachment if more than two facilities are required.

Disposal Facility Name: _____ Disposal Facility Permit Number: _____
 Disposal Facility Name: _____ Disposal Facility Permit Number: _____

Will any of the proposed closed-loop system operations and associated activities occur on or in areas that *will not* be used for future service and operations?
☐ Yes (If yes, please provide the information below) ☐ No

Required for impacted areas which will not be used for future service and operations

☐ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC
☐ Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC
☐ Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC

17. **Siting Criteria (regarding on-site closure methods only):** 19.15.17.10 NMAC
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.

Ground water is less than 50 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> NA
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	<input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> NA 375'
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Within a 100-year floodplain - FEMA map	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No

18. **On-Site Closure Plan Checklist:** (19.15.17.13 NMAC) *Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.*

☒ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC
☒ Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC
☐ Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC
☐ Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.11 NMAC
☒ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC
☒ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC
☐ Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC
☒ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved) **CRI**
☒ Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC **NM-01-0006**
☒ Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC
☐ Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC

19. **Operator Application Certification:**
 I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.

Name (Print): Larry R. Scott Title: President

Signature: *Larry R. Scott* Date: October 1, 2009

e-mail address: lynxpet@leaco.net Telephone: 575-392-6950

20. **OCD Approval:** ☒ Permit Application (including closure plan) ☐ Closure Plan (only) ☐ OCD Conditions (see attachment)

OCD Representative Signature: *Jeffrey LeMay* Approval Date: 04/08/2010

Title: Environmental Engineer OCD Permit Number: PI-01553

21. **Closure Report (required within 60 days of closure completion):** Subsection K of 19.15.17.13 NMAC
Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed.

☐ Closure Completion Date: _____

22. **Closure Method:**

☐ Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-loop systems only)

☐ If different from approved plan, please explain.

23. **Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only:**
Instructions: Please identify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than two facilities were utilized.

Disposal Facility Name: _____ Disposal Facility Permit Number: _____

Disposal Facility Name: _____ Disposal Facility Permit Number: _____

Were the closed-loop system operations and associated activities performed on or in areas that *will not* be used for future service and operations?
☐ Yes (If yes, please demonstrate compliance to the items below) ☐ No

Required for impacted areas which will not be used for future service and operations:

☐ Site Reclamation (Photo Documentation)
☐ Soil Backfilling and Cover Installation
☐ Re-vegetation Application Rates and Seeding Technique

24. **Closure Report Attachment Checklist:** *Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.*

☐ Proof of Closure Notice (surface owner and division)
☐ Proof of Deed Notice (required for on-site closure)
☐ Plot Plan (for on-site closures and temporary pits)
☐ Confirmation Sampling Analytical Results (if applicable)
☐ Waste Material Sampling Analytical Results (required for on-site closure)
☐ Disposal Facility Name and Permit Number
☐ Soil Backfilling and Cover Installation
☐ Re-vegetation Application Rates and Seeding Technique
☐ Site Reclamation (Photo Documentation)

On-site Closure Location: Latitude _____ Longitude _____ NAD: ☐ 1927 ☐ 1983

25. **Operator Closure Certification:**
 I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.

Name (Print): _____ Title: _____

Signature: _____ Date: _____

e-mail address: _____ Telephone: _____

Lusk '31' Federal No. 3
C-144 Attachments

All maps submitted with this application were generated utilizing the Petroleum Recovery Research Center's "Pit Rule Mapping Portal".

Figure 1 is a topographic map at a 1"=2000' scale showing the area surrounding the proposed location.

Figure 2 was developed with the U.S.G.S. and O.S.E.S. layers turned on demonstrating that there are no ground water resources within several miles of the proposed location.


Figure 3 was developed with the surface water layer turned on demonstrating that there is no surface water with several miles of the proposed location.


Figure 4 is an aerial photograph demonstrating that there are no structures, municipal boundaries, wetlands, mines, or unstable areas within several miles of the proposed location. The area has not been mapped by FEMA as being within a 100 year floodplain.


We plan to push the topsoil to the north side of the location to be utilized for recover purposes at the conclusion of the drilling project. The pit will be constructed per the attached diagram and lined as per specifications. The three open sides will be fenced with four strands of barbed wire per specifications. The fourth side (rig side) will be left open until the drilling equipment has been removed from location at which time this will also be fenced.

We anticipate that the inner horseshoe will contain 10.0 ppg (saturated) brine water to be used for the drilling of the salt section. The outer horseshoe will initially contain fresh water but will "brine up" during the drilling of the production hole to a concentration of 60,000-100,000 ppm. Both inner and outer horseshoes will be dewatered immediately following drilling operations.

With the pit dry, we plan to cover the drill cuttings with 20 mil LLDPE plastic and then push the previously located topsoil back over the area to cover. Finally, the area will be reseeded with a mixture of seed required by the Bureau of Land Management with their APD approval.








**Petroleum Recovery
Research Center**

No Surface Water Present


Lynx Petroleum Cons., Inc./Lusk '31' Fed. No. 3

Figure: 3

Sep 28, 2009



0 1000 2000ft




Petroleum Recovery
Research Center


No Structures/Urban Areas Present

Lynx Petroleum Cons., Inc./Lusk '31' Fed. No. 3

Figure: 4

Sep 28, 2009






Scale: None

Lusk '31' Federal No. 3
Plan Layout

Loc: 1880'FSL & 2080'FEL
Sec.31, T-18S, R-32E
1:10,000 Scale, NAD83

PROPOSED SAMPLING LOCATIONS FOR 5-PT COMPOSITE SAMPLING





SAMPLE OF ANALYSES
TO BE PERFORMED ON
5-PT COMPOSITE

PHONE (575) 393-2328 • 101 E. MARLAND • HOBBS, NM 88240

ANALYTICAL RESULTS FOR
CAPITAN CHEMICAL, LLC
ATTN: LYNX PETROLEUM - LARRY SCOTT
P.O. BOX 1200
HOBBS, NM 88241
FAX TO: (575) 392-3889

Receiving Date: 12/17/08
Reporting Date: 12/19/08
Project Number: LUSK 33-2
Project Name: PIT CLOSURE
Project Location: LUSK FIELD

Sampling Date: NOT GIVEN
Sample Type: SOIL
Sample Condition: COOL & INTACT
Sample Received By: ML
Analyzed By: AB/HM

LAB NUMBER	SAMPLE ID	GRO	DRO	418.1	CI*
		(C ₈ -C ₁₀)	(C ₁₀ -C ₂₈)	TOTAL	
		(mg/kg)	(mg/kg)	(mg/kg)	(mg/kg)
ANALYSIS DATE		12/18/08	12/18/08	12/19/08	12/17/08
H16542-1	SW	108	240	2,780	34,000
H16542-2	SE	35.3	310	5,880	86,400
H16542-3	CENTER	41.2	330	7,530	43,200
H16542-4	NE	74.8	418	2,850	18,000
H16542-5	NW	120	137	1,420	20,000
Quality Control		599	514	323	500
True Value QC		500	500	300	500
% Recovery		120	103	108	100
Relative Percent Difference		8.1	4.7	0.3	2.0

METHODS: TPH GRO & DRO: EPA SW-846 8015 M; EPA 418.1; CI: Std. Methods 4500-Cl-B
*Analyses performed on 1:4 w:v aqueous extracts.

Chemist

Date

H16452 TPH2CL CC

PLEASE NOTE: Liability and Damages: Cardinal's liability and client's exclusive remedy for any claim arising, whether based in contract or tort, shall be limited to the amount paid by client for analyses. All claims, including those for negligence and any other cause whatsoever shall be deemed waived unless made in writing and received by Cardinal within thirty (30) days after completion of the applicable service. In no event shall Cardinal be liable for incidental or consequential damages, including, without limitation, business interruptions, loss of use, or loss of profits incurred by client, its subsidiaries, affiliates or successors arising out of or related to the performance of services rendered by Cardinal, regardless of whether such claim is based upon any of the above-stated reasons or otherwise. Results relate only to the samples identified above. This report shall not be reproduced except in full with written approval of Cardinal Laboratories.



PHONE (575) 393-2326 • 101 E. MARLAND • HOBBS, NM 88240

ANALYTICAL RESULTS FOR
CAPITAN CHEMICAL, LLC
ATTN: LYNX PETROLEUM - LARRY SCOTT
P.O. BOX 1200
HOBBS, NM 88241
FAX TO: (575) 392-3689

Receiving Date: 12/17/08
Reporting Date: 12/19/08
Project Number: LUSK 33-2
Project Name: PIT CLOSURE
Project Location: LUSK FIELD

Sampling Date: NOT GIVEN
Sample Type: SOIL
Sample Condition: COOL & INTACT
Sample Received By: ML
Analyzed By: ZL

LAB NUMBER	SAMPLE ID	BENZENE (mg/kg)	TOLUENE (mg/kg)	ETHYL BENZENE (mg/kg)	TOTAL XYLENES (mg/kg)
ANALYSIS DATE		12/19/08	12/19/08	12/19/08	12/19/08
H18542-1	SW	0.458	4.41	4.48	7.53
H18542-2	SE	0.730	1.98	1.40	2.59
H18542-3	CENTER	0.719	2.49	2.25	3.84
H18542-4	NE	0.304	0.711	1.64	3.20
H18542-5	NW	0.229	0.928	1.12	2.01
Quality Control		0.043	0.044	0.048	0.137
True Value QC		0.050	0.050	0.050	0.150
% Recovery		86.0	88.0	92.0	91.3
Relative Percent Difference		1.2	1.4	6.9	3.8

METHOD: EPA SW-846 8021B

TEXAS NELAP CERTIFICATION T104704398-08-TX FOR BENZENE, TOLUENE, ETHYL BENZENE,
AND TOTAL XYLENES.

Chemist

Date

PLEASE NOTE: Liability and Damages. Cardinal's liability and client's exclusive remedy for any claim arising, whether based in contract or tort, shall be limited to the amount paid by client for analysis. All claims, including those for negligence and any other cause whatsoever shall be deemed waived unless made in writing and received by Cardinal within thirty (30) days after completion of the applicable service. In no event shall Cardinal be liable for incidental or consequential damages, including, without limitation, business interruptions, loss of use, or loss of profits incurred by client, its subsidiaries, affiliates or successors arising out of or related to the performance of services hereunder by Cardinal, regardless of whether such claim is based upon any of the above-stated reasons or otherwise. Results relate only to the samples identified above. This report shall not be reproduced except in full with written approval of Cardinal Laboratories.



101 East Marland, Hobbs, NM 88240

(575) 393-2326 Fax (575) 393-2476

[illegible]

† Cardinal cannot accept verbal changes. Please fax written changes to 575-393-2476.

6. SOURCE OF CONSTRUCTION MATERIAL :

- A. Caliche will be hauled from the nearest approved pit.

7. METHODS OF HANDLING WASTE DISPOSAL :

- A. Drill cuttings will be disposed of in the drill pit.
- B. Drilling fluids will be recovered from the drilling pits upon conclusion of drilling/completion operations.
- C. Water produced during testing will be disposed of in the drill pits. Oil produced during testing will be stored in the test tanks until sold.
- D. Current laws and regulations pertaining to the disposal of human waste will be complied with.
- E. Trash, waste paper and garbage will be contained in a fenced trash trailer and disposed of in an approved landfill.

8. ANCILLARY FACILITIES :

- A. None required.

9. WELLSITE LAYOUT :

- A. The attached rig layout plat indicates the relative location and dimensions of the well pad, mud pits, reserve pit and major rig equipment.
- B. The reserve pit will be lined with plastic to prevent loss of water and contain the drilling mud.

10. PLANS FOR RESTORATION OF THE SURFACE :

- A. After completion of drilling and/or completion operations all equipment and other material not needed for producing operations will be removed. Pits will be filled and the location cleaned of all trash and junk to leave the wellsite in as aesthetically pleasing condition as possible
- B. Any unguarded pits containing fluids will be fenced until they are backfilled.

- C. If the well is non-productive, the disturbed area will be rehabilitated to Federal Agency requirements, and will be accomplished as expeditiously as possible.

11. OTHER INFORMATION :

- A. Terrain : Low rolling hills.
- B. Soil : Sandy.
- C. Vegetation : Mesquite, creosote, and grasses.
- D. Surface Use : Grazing.
- E. Ponds and Streams : None within 1.0 mile.
- F. Water Wells : None within 1.0 mile.
- G. Residences and Buildings : None within 1.0 mile.
- H. Arroyos, Canyons, Etc. : None within 1.0 mile.
- I. Well Sign : A sign identifying and locating the well will be maintained at the wellsite.
- J. Archeological, Historical and Other Cultural Sites : An archeological survey of the well pad has been ordered from Boone Archeological Services. They will furnish a report and recommendation to the B. L. M. in Carlsbad, NM.
- K. Surface Ownership : The access road and wellsite are located on Public surface.

12. OPERATOR'S REPRESENTATIVE :

Larry R. Scott
P. O. Box 1708
Hobbs, NM 88241
Phone - (575) 392-6950 Fax - (575) 392-7886

I. GENERAL PROVISIONS

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

II. PERMIT EXPIRATION

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

IV. NOXIOUS WEEDS

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

V. SPECIAL REQUIREMENT(S)

Timing Limitation Stipulation/Condition of Approval for Lesser Prairie-Chicken: Oil and gas activities including 3-D geophysical exploration, and drilling will not be allowed in lesser prairie-chicken habitat during the period from March 1st through June 15th annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, geophysical exploration other than 3-D operations, and pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Additionally, no new drilling will be allowed within up to 200 meters of leks known at the time of permitting. Normal vehicle use on existing roads will not be restricted. Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 ft. from the source of the noise.

Ground-level Abandoned Well Marker to avoid raptor perching: Upon the plugging and subsequent abandonment of the well, the well marker will be installed at ground level on a plate containing the pertinent information for the plugged well. For more installation details, contact the Carlsbad Field Office at 575-234-5972.

VI. CONSTRUCTION

A. NOTIFICATION

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Hobbs Field Station at (575) 393-3612 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

B. TOPSOIL

The operator shall stockpile the topsoil of the well pad. The topsoil shall not be used to backfill the reserve pit and will be used for interim and final reclamation.

C. RESERVE PITTS

The reserve pit shall be constructed and closed in accordance with the NMOCD rules.

The reserve pit shall be constructed 150' X 150' on the North side of the well pad.

The reserve pit shall be constructed, so that upon completion of drilling operations, the dried pit contents shall be buried a minimum depth of three feet below ground level. Should the pit content level not meet the three foot minimum depth requirement, the excess contents shall be removed until the required minimum depth of three feet below ground level has been met. The operator shall properly dispose of the excess contents at an authorized disposal site.

The reserve pit shall be constructed and maintained so that runoff water from outside the location is not allowed to enter the pit. The berms surrounding the entire perimeter of the pit shall extend a minimum of two (2) feet above ground level. At no time will standing fluids in the pit be allowed to rise above ground level.

The reserve pit shall be fenced on three (3) sides during drilling operations. The fourth side shall be fenced immediately upon rig release.

D. FEDERAL MINERAL MATERIALS PIT

If the operator elects to surface the access road and/or well pad, mineral materials extracted during construction of the reserve pit may be used for surfacing the well pad and access road and other facilities on the lease.

Payment shall be made to the BLM prior to removal of any additional federal mineral materials from any site other than the reserve pit. Call the Carlsbad Field Office at (575) 234-5972.

E. WELL PAD SURFACING

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation.

The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

F. ON LEASE ACCESS ROADS

Road Width

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed thirty (30) feet.

Surfacing

Painting Requirement

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color
Shale Green, Munsell Soil Color Chart # 5Y 4/2

IX. INTERIM RECLAMATION & RESERVE PIT CLOSURE**A. INTERIM RECLAMATION**

If the well is a producer, interim reclamation shall be conducted on the well site in accordance with the orders of the Authorized Officer. The operator shall submit a Sundry Notices and Reports on Wells (Notice of Intent), Form 3160-5, prior to conducting interim reclamation.

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

At the time reserve pits are to be reclaimed, operators should work with BLM surface management specialists to devise the best strategies to reduce the size of the location. Any reductions should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

B. RESERVE PIT CLOSURE

The reserve pit, when dried and closed, shall be recontoured, all trash removed, and reseeded as follows:

Seed Mixture for LPC Sand/Shinnery Sites

The holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)* per acre. There shall be no primary or secondary noxious weeds in the seed mixture. Seed will be tested and the viability testing of seed will be done in accordance with State law(s) and within nine (9) months prior to purchase. Commercial seed will be either

certified or registered seed. The seed container will be tagged in accordance with State law(s) and available for inspection by the authorized officer.

Seed will be planted using a drill equipped with a depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture will be evenly and uniformly planted over the disturbed area (smaller/heavier seeds have a tendency to drop the bottom of the drill and are planted first). The holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed will be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre are to be doubled. The seeding will be repeated until a satisfactory stand is established as determined by the authorized officer. Evaluation of growth will not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed* per acre:

<u>Species</u>	<u>lb/acre</u>
Plains Bristlegrass	5lbs/A
Sand Bluestem	5lbs/A
Little Bluestem	3lbs/A
Big Bluestem	6lbs/A
Plains Coreopsis	2lbs/A
Sand Dropseed	1lbs/A

**Four-winged Saltbush 5lbs/A

* This can be used around well pads and other areas where caliche cannot be removed.

*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed

X. FINAL ABANDONMENT & REHABILITATION REQUIREMENTS

Upon abandonment of the well and/or when the access road is no longer in service the Authorized Officer shall issue instructions and/or orders for surface reclamation and restoration of all disturbed areas.

On private surface/federal mineral estate land the reclamation procedures on the road and well pad shall be accomplished in accordance with the private surface land owner agreement.

Ground-level Abandoned Well Marker to avoid raptor perching: Upon the plugging and subsequent abandonment of the well, the well marker will be installed at ground level on a plate containing the pertinent information for the plugged well. For more installation details, contact the Carlsbad Field Office at 575-234-5972.

C-144 Modification Supplemental Documentation
Lusk 31 Federal #3 API # 30-025-39593

Approved APD- Proof of Surface Owner Notification

OCD-HOBBS

RECEIVED

DEC 09 2009

HOBBSOCD

ATS-10-53

FORM APPROVED
OMB No 1004-0137
Expires July 31, 2010

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT


APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. NM 23006
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name
2. Name of Operator Lynx Petroleum Consultants, Inc.		7. If Unit or CA Agreement, Name and No.
3a. Address P.O. Box 1708 Hobbs, NM 88241		8. Lease Name and Well No. Lusk '31' Federal No. 3
3b. Phone No. (include area code) 575-392-6950		9. API Well No. 30-025-39593
4. Location of Well (Report location clearly and in accordance with any State requirements *) At surface 1880' FSL & 2080' FEL Unit J At proposed prod. zone 1880' FSL & 2080' FEL		10. Field and Pool, or Exploratory Lusk North Bone Spring/Wolfcamp North
11. Sec., T. R. M. or Blk. and Survey or Area Sec.31, T-18S, R-32E		12. County or Parish Lea
13. State NM		14. Distance in miles and direction from nearest town or post office* 11 miles SSW of Maljamar, NM
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 480'	16. No. of acres in lease 321.27	17. Spacing Unit dedicated to this well 40 acres
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 325'	19. Proposed Depth 11,200'	20. BLM/BIA Bond No. on file NM-1694 (BO2099)
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3676' GL	22. Approximate date work will start* 12/01/2009	23. Estimated duration 26 days

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, must be attached to this form:

- | | |
|---|---|
| 1. Well plat certified by a registered surveyor. | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan. | 5. Operator certification |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office) | 6. Such other site specific information and/or plans as may be required by the BLM. |

25. Signature 	Name (Printed/Typed) Larry R. Scott	Date 10/01/2009
--	--	--------------------

Approved by (Signature) /s/ Don Peterson	Name (Printed/Typed) CARLSBAD FIELD OFFICE	Date DEC 09 2009
Title FIELD MANAGER	Office	

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon
Conditions of approval, if any, are attached.

APPROVAL FOR TWO YEARS

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

Capitan Controlled Water Basin

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

APPROVAL SUBJECT TO
GENERAL REQUIREMENTS
AND SPECIAL STIPULATIONS
ATTACHED

DISTRICT I
1625 N. French Dr., Hobbs, NM 88240
DISTRICT II
1501 W. Grand Avenue, Artesia, NM 88210
DISTRICT III
1000 Rio Brazos Ed., Artesia, NM 87410
DISTRICT IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-102
Revised October 12, 2006
Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, New Mexico 87505

RECEIVED
DEC 09 2009
HOBBSOCD

WELL LOCATION AND ACREAGE DEDICATION PLAT

☐ AMENDED REPORT

API Number 30-025-38593	Pool Code 41450 / 41608	Pool Name Lusk Lusk North Bone Spring/Wolfcamp North
Property Code 37315	Property Name LUSK "31" FEDERAL	Well Number 3
OGED No. 013645	Operator Name LYNX PETROLEUM CONSULTANTS, INC.	Elevation 3676'

Surface Location

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
J	31	18 S	32 E		1880	SOUTH	2080	EAST	LEA

Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
Dedicated Acres 40/40	Joint or Infill	Consolidation Code	Order No.						

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

	OPERATOR CERTIFICATION <i>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.</i> Signature: <i>Larry R. Scott</i> Date: 10-01-09 Printed Name: Larry R. Scott
	SURVEYOR CERTIFICATION <i>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</i> Date Surveyed: SEPTEMBER 2009 Signature & Seal of Professional Surveyor:
	Certificate No. Gary L. Jones 7977
	Basin Surveys

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OCD-HOBBS

RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-
abandoned well. Use Form 3160-3 (APD) for such proposals.

FORM APPROVED

Budget Bureau No 1004-0137

Expires: March 31, 2007

5. Lease Serial No
NM 23006

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement, Name and/or No

8. Well Name and No

Lusk '31' Federal No. 3

9. API Well No

10. Field and Pool, or Exploratory Area
Lusk North Bone Spring/Wolfcamp

11. County or Parish, State
Lea, New Mexico

SUBMIT IN TRIPLICATE - Other instructions on reverse side.

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
Lynx Petroleum Consultants, Inc.

3a. Address
P.O. Box 1708, Hobbs, NM 88241

3b. Phone No (include area code)
575-392-6950

4. Location of Well (Footage, Sec., T, R., M., or Survey Description)
1880' FSL & 2080' FEL, Section 31, T-18S, R-32E

12 CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other <u>Refurbish Roadbeds</u>
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13 Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be Filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

Propose to refurbish roadbeds into the plugged and abandoned Federal CST Nos. 1 and 2 to the south side of the well pad.
Total length will be 1295'. See attached map.

14 I hereby certify that the foregoing is true and correct
Name (Printed/Typed)
Larry R. Scott

Title
PRESIDENT

Signature

Date 10-01-09

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by /s/ Don Peterson

Title



Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

DEC 04 2009
CARLSBAD FIELD OFFICE

SECTION 31, TOWNSHIP 18 SOUTH, RANGE 32 EAST, N.M.P.M.,
LEA COUNTY, NEW MEXICO.



Directions to Location:

FROM THE JUNCTION OF LUSK PLANT ROAD AND MALJAMAR ROAD, GO NORTH 3.4 MILES ON MALJAMAR TO LEASE ROAD, ON LEASE ROAD GO WEST 0.1 MILES THENCE WINDING SOUTHWEST 0.2 MILES TO LEASE ROAD, ON LEASE ROAD GO NORTHWEST 0.1 MILES TO PROPOSED LEASE ROAD.

LYNX PETROLEUM CONSULTANTS, INC.

REF: LUSK "31" FEDERAL #3 / WELL PAD TOPO

THE LUSK "31" FEDERAL #3 LOCATED 1880'
FROM THE SOUTH LINE AND 2080' FROM THE EAST LINE OF
SECTION 31, TOWNSHIP 18 SOUTH, RANGE 32 EAST,
N.M.P.M., LEA COUNTY, NEW MEXICO.

BASIN SURVEYS P.O. BOX 1786-HOBBS, NEW MEXICO

W.O. Number: 21748	Drawn By: J. SMALL
Date: 09-18-2009	Disk: JMS 21748
Survey Date: 09-17-2009	Sheet 1 of 1 Sheets

STATEMENT ACCEPTING RESPONSIBILITY FOR OPERATIONS

Application for Permit to Drill
Lusk '31' Federal No. 3
1880' FSL & 2080' FEL
Section 31, T-18S, R-32E
Lea County, New Mexico

The undersigned accepts all applicable terms, conditions, stipulations, and restrictions concerning operations conducted on the leased land or portion thereof, as described below:

Lease No. : NM 23006

Location Legal Description: NW/4 SE/4 Section 31, T-18S, R-32E
Lea County, New Mexico

Proration Unit: NW/4 SE/4 Section 31, T-18S, R-32E
Lea County, New Mexico

Formation : Surface to base of Wolfcamp

Bond Coverage : \$25,000 Statewide

BLM Bond File No. : NM-1694 (BO2099)



Operator : LYNX PETROLEUM CONSULTANTS, INC.

Authorized Signature : 

Title : President

Date : 10/1/2009

SECTION 31, TOWNSHIP 18 SOUTH, RANGE 32 EAST, N.M.P.M.,
LEA COUNTY, NEW MEXICO.



Directions to Location:

FROM THE JUNCTION OF LUSK PLANT ROAD AND
MALJAMAR ROAD, GO NORTH 3.4 MILES ON MALJAMAR
TO LEASE ROAD, ON LEASE ROAD GO WEST 0.1
MILES THENCE WINDING SOUTHWEST 0.2 MILES TO
LEASE ROAD, ON LEASE ROAD GO NORTHWEST 0.1
MILES TO PROPOSED LEASE ROAD.

LYNX PETROLEUM CONSULTANTS, INC.

REF: LUSK "31" FEDERAL #3 / WELL PAD TOPO


THE LUSK "31" FEDERAL #3 LOCATED 1880'
FROM THE SOUTH LINE AND 2080' FROM THE EAST LINE OF
SECTION 31, TOWNSHIP 18 SOUTH, RANGE 32 EAST,
N.M.P.M., LEA COUNTY, NEW MEXICO.

BASIN SURVEYS P.O. BOX 1786-HOBBS, NEW MEXICO

W.O. Number: 21748 Drawn By: J. SMALL

Date: 09-18-2009 Disk: JMS 21748

Survey Date: 09-17-2009 Sheet 1 of 1 Sheets



LUSK "31" FEDERAL #3

Located 1880' FSL and 2080' FEL

Section 31, Township 18 South, Range 32 East,
N.M.P.M., Lea County, New Mexico.



focused on excellence
in the oilfield

P.O. Box 1786
1120 N. West County Rd.
Hobbs, New Mexico 88241
(575) 393-7316 - Office
(575) 392-2206 - Fax
basinsurveys.com


W.O. Number: JMS 21748

Survey Date: 09-17-2009

Scale. 1" = 2000'


Date: 09-18-2009

**LYNX PETROLEUM
CONSULTANTS,
INC.**



LUSK "31" FEDERAL #3

Located 1880' FSL and 2080' FEL
 Section 31, Township 18 South, Range 32 East,
 N.M.P.M., Lea County, New Mexico.



P.O. Box 1786
 1120 N. West County Rd.
 Hobbs, New Mexico 88241
 (575) 393-7316 - Office
 (575) 392-2206 - Fax
 basinsurveys.com


W.O. Number. JMS 21748

Survey Date: 09-17-2009


Scale: 1" = 2 Miles

Date: 09-18-2009

**LYNX PETROLEUM
 CONSULTANTS,
 INC.**



LUSK "31" FEDERAL #3
Located 1880' FSL and 2080' FEL
Section 31, Township 18 South, Range 32 East,
N.M.P.M., Lea County, New Mexico.



P.O. Box 1786
1120 N. West County Rd.
Hobbs, New Mexico 88241
(575) 393-7316 - Office
(575) 392-2206 - Fax
basinsurveys.com

W.O. Number: JMS 21748

Scale: 1" = 2000'

YELLOW TINT - USA LAND
BLUE TINT - STATE LAND
NATURAL COLOR - FEE LAND

LYNX PETROLEUM
CONSULTANTS,
INC.

DRILLING PROGRAM

Lynx Petroleum Consultants, Inc.
Lusk '31' Federal No. 3
1880' FSL & 2080' FWL
Section 31, T-18S, R-32E
Lea County, NM

The following items supplement Form 3160-3 in accordance with instructions contained in Onshore Oil and Gas Orders #1 and #2, and all other applicable federal and state regulations.

1. SURFACE FORMATION : Sandy Soil of Quaternary Age
2. ESTIMATED TOPS OF GEOLOGICAL MARKERS :

Top of Salt 1190'	Rustler	-	1050'
Base " " 2470'	Yates	-	2780'
	Queen	-	3650'
	Delaware	-	5025'
	Bone Spring	-	6800'
	Bone Spring 1 st Sd	-	8100'
	Bone Spring 3 rd Sd	-	9750'
	Wolfcamp	-	10,110'

3. ESTIMATED DEPTHS TO WATER, OIL OR GAS FORMATIONS :

Fresh Water	-	None in measurable quantity
Oil, Gas, & Water	-	Yates, Grayburg, Delaware, Bone Spring, Wolfcamp

* Productive horizons to be protected by 5 1/2" casing and cement.

4. PROPOSED CASING PROGRAM :

per operator									
Hole Size									
17 1/2"	13 3/8"	0' -	500'	48.0#	H-40	ST&C	See COA		
12 1/4" or 11"	8 5/8"	0' -	2750'	32.0#	J-55	ST&C			
7 7/8"	5 1/2"	0' -	11,200'	17.0#	N-80	LT&C			
	Casing Safety Factors								
		B.S.F.	C.S.F.	J.S.F.	Y.S.F.				
	13-3/8"	1.4	3.3	14.9	22.7				
	8-5/8"	2.2	2.0	4.7	6.4				
	5-1/2"	1.5	1.2	2.0	2.0				

DRILLING PROGRAM
Lusk '31' Federal No. 3

5. PROPOSED CEMENT PROGRAM: ← See COA

20" Conductor - Cemented with ready mix to surface.

See COA → 13 3/8" Surface - 300 sxs Class "C" + 4% Gel + 2% CaCl₂ (507 ft³) followed by 250 sxs Class "C" + 2% CaCl₂ (330 ft³). T.O.C. @ surface. 1.69 ft³/sx
1.32 ft³/sx

8 5/8" Intermediate - 800 sxs Class "C" Poz followed by 200 sxs Class "C" (1884 ft³ total). T.O.C. @ surface.

5 1/2" Production - First stage 700 sxs Class "C". Second stage 500 sx. Class "H" Poz followed by 100 sxs Class "HC". TOC @ 2600'. 2550'

1st stage 1.6 cf/sx
2nd stage 2.12 cf/sx
per operator
DV Tool 6800'
R6H
11/12/09

See COA → 6. PRESSURE CONTROL EQUIPMENT: A blowout preventer stack for the intermediate hole will consist of at least an annular preventer rated to 2000 psi working pressure. The blowout preventer stack for the production hole will consist of at least a double-ram blowout preventer and an annular preventer rated to 5000 psi working pressure. A sketch of the B.O.P.'s and Choke Manifold are attached.

See COA

7. CIRCULATING MEDIUMS: Fresh water spud mud 0' - 500'. Brine water 500' - 2650'. Cut brine mud system 8.8 - 9.3 ppg with 29 viscosity will be used 2650' - 9800'.

8. AUXILIARY EQUIPMENT: Full opening Kelly cock valve to fit the drill string in use, will be kept on the rig floor at all times.


9. TESTING, LOGGING, AND CORING PROGRAM:

See COA → Samples - 2750' - TD
D.S.T.'s - No D.S.T.'s are planned
Logging - Gamma Ray - CNL - FDC - DLL
Coring - No coring is planned

10. ABNORMAL PRESSURES AND TEMPERATURES: None anticipated.


BHT - 143°F
BHP - 4851 psi
per operator

11. ANTICIPATED STARTING DATE: Drilling will commence about January 1, 2010. Drilling should be complete within 27 days. Completion operations (perforations and stimulation) will follow drilling operations.




Scale: None	Lusk '31' Federal No. 3	Loc: 1880'FSL & 2080'FEL
Date: 9/29/09	Rig Layout	Sec.31, T-18S, R-32E
		Lea County, NM

INTERMEDIATE HOLE SECTION



2000 PSI WORKING PRESSURE



2000 PSI WORKING PRESSURE


TEST CASING AND ANNULAR PREVENTOR TO 600 psig (see COA)

Location: NW/4 SE/4
Sec. 31, T-18S, R-32E
Lea County, NM

Lusk '31' Federal No. 3
BLOWOUT PREVENTER AND CHOKE MANIFOLD

Scale: None

9/28/09




Location: NW/4 SE/4
Sec. 31, T-18S, R-32E
Lea County, NM

Lusk '31' Federal No. 3
BLOWOUT PREVENTER AND CHOKE MANIFOLD

Scale: None

9/28/09



LYNX PETROLEUM CONSULTANTS, INC.
HYDROGEN SULFIDE DRILLING OPERATIONS
LUSK '31' FEDERAL NO. 3

I. HYDROGEN SULFIDE TRAINING

All personnel, whether regularly assigned, contracted, or employed on an unscheduled basis, will receive training from a qualified instructor in the following areas prior to commencing drilling operations on this well:

1. The hazards and characteristics of hydrogen sulfide (H₂S).
2. The proper use and maintenance of personal protective equipment and life support systems.
3. The proper use of H₂S detectors, alarms, warning systems, briefing areas, evacuation procedures, and prevailing winds.
4. The proper techniques for first aid and rescue procedures.

In addition, supervisory personnel will be trained in the following areas:

1. The effects of H₂S on metal components. If high tensile tubulars are to be used, personnel will be trained in their special maintenance requirements.
2. Corrective action and shut-in procedures when drilling or reworking a well and blowout prevention and well control procedures.
3. The contents and requirements of the H₂S Drilling Operations Plan and the Public Protection Plan.

There will be an initial training session just prior to encountering a known or probable H₂S zone (within 3 days or 500 feet) and weekly H₂S Drilling Operations Plan and the Public Protection Plan. This plan shall be available at the well site.

II. H₂S SAFETY EQUIPMENT AND SYSTEMS


Note : All H₂S safety equipment and systems will be installed, tested, and operational when drilling reaches a depth of 500 feet above, or three days prior to penetrating the first zone containing or reasonably expected to contain H₂S.

DRILLING OPERATIONS
Lusk '31' Federal No. 3

1. Well Control Equipment :
 - A. Choke manifold with a minimum of one remote choke.
 - B. Blind rams and pipe rams to accommodate all pipe sizes with properly sized closing unit.
 - C. Auxiliary equipment to include : annular preventer
2. Protective equipment for essential personnel :
 - A. 30-minute air units located in the dog house and at briefing areas, as indicated on well site diagram.
3. H₂S detection and monitoring equipment :
 - A. 2 – portable H₂S monitors positioned on location for best coverage and response. These units have warning lights and audible sirens when H₂S levels of 20 ppm are reached.
 - B. 1 – portable SO₂ monitor positioned near flare line.
4. Visual warning systems :
 - A. Wind direction indicators as shown on well site diagram.
 - B. Caution/Danger signs shall be posted on roads providing direct access to location. Signs will be painted a high visibility yellow with black lettering of sufficient size to be readable at a reasonable distance from the immediate location. Bilingual signs will be used when appropriate. See example on page 3.
5. Mud program :
 - A. The mud program has been designed to minimize the volume of H₂S circulated to the surface. Proper mud weight, safe drilling practices, and the use of H₂S scavengers will minimize hazards when penetrating H₂S bearing zones.
 - B. A mud-gas separator will be utilized if needed.
6. Metallurgy :

DRILLING OPERATIONS
Lusk '31' Federal No. 3

- A. All drill strings, casings, tubing, wellhead, blowout preventers, drilling spool, kill lines, choke manifold and lines, and valves shall be suitable for H₂S service.
 - B. All elastomers used for packing and seals shall be H₂S trim.
7. Communication :
- A. Communications in company vehicles are provided by cellular telephones.
Cell1: 575-390-9063 Cell2: 575-390-9065
 - B. Land line (telephone) communications at Hobbs office.
Phone: 575-392-6950
 - C: Emergency Numbers
911
Carlsbad Sheriff's Dept.: 575-887-1888
Carlsbad Hospital: 575-887-4100
Carlsbad Fire Dept.: 575-885-3125
Maljamar Fire Dept.: 575-676-4100
Hobbs Hospital: 575-492-5000
New Mexico State Police: 575-392-5588
8. Well testing :
- A. Drill stem testing will be preformed with a minimum number of personnel in the immediate vicinity which are necessary to safely and adequately conduct the test. All drill stem testing operations conducted in an H₂S environment will use the closed chamber method of testing.



13. CERTIFICATION :

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drill site and access route ; that I am familiar with the conditions which presently exist ; that the statements made in this plan are, to the best of my knowledge, true and correct ; that the work associated with the operations proposed herein will be performed by LYNX PETROLEUM CONSULTANTS, INC. and its sub-contractors in conformity with this plan and the terms and conditions under which it is approved.

10-1-2007
DATE

Larry R. Scott
LARRY R. SCOTT - PRESIDENT

PECOS DISTRICT CONDITIONS OF APPROVAL

OPERATOR'S NAME:	Lynx Petroleum Consultants
LEASE NO.:	NM23006
WELL NAME & NO.:	3 Lusk 31 Federal
SURFACE HOLE FOOTAGE:	1880' FS & 2080' FEL
BOTTOM HOLE FOOTAGE:	Same
LOCATION:	Section 31, T. 18 S., R. 32 E., NMPM
COUNTY:	Lea County, New Mexico

TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

- ☐ **General Provisions**
- ☐ **Permit Expiration**
- ☐ **Archaeology, Paleontology, and Historical Sites**
- ☐ **Noxious Weeds**
- ☒ **Special Requirements**
 - Lesser Prairie Chicken
- ☐ **Construction**
 - Notification
 - Topsoil
 - Reserve Pit
 - Federal Mineral Material Pits
 - Well Pads
 - Roads
- ☐ **Road Section Diagram**
- ☒ **Drilling**
 - H2S – Onshore Order 6 requirements
 - Logging requirements
- ☐ **Production (Post Drilling)**
- ☐ **Reserve Pit Closure/Interim Reclamation**
- ☐ **Final Abandonment/Reclamation**

I. GENERAL PROVISIONS

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

II. PERMIT EXPIRATION

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

IV. NOXIOUS WEEDS

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

V. SPECIAL REQUIREMENT(S)

Timing Limitation Stipulation/Condition of Approval for Lesser Prairie-Chicken: Oil and gas activities including 3-D geophysical exploration, and drilling will not be allowed in lesser prairie-chicken habitat during the period from March 1st through June 15th annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, geophysical exploration other than 3-D operations, and pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Additionally, no new drilling will be allowed within up to 200 meters of leks known at the time of permitting. Normal vehicle use on existing roads will not be restricted. Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 ft. from the source of the noise.

Ground-level Abandoned Well Marker to avoid raptor perching: Upon the plugging and subsequent abandonment of the well, the well marker will be installed at ground level on a plate containing the pertinent information for the plugged well. For more installation details, contact the Carlsbad Field Office at 575-234-5972.

VI. CONSTRUCTION

A. NOTIFICATION

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Hobbs Field Station at (575) 393-3612 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

B. TOPSOIL

The operator shall stockpile the topsoil of the well pad. The topsoil shall not be used to backfill the reserve pit and will be used for interim and final reclamation.

C. RESERVE PITS

The reserve pit shall be constructed and closed in accordance with the NMOCD rules.

The reserve pit shall be constructed 150' X 150' on the North side of the well pad.

The reserve pit shall be constructed, so that upon completion of drilling operations, the dried pit contents shall be buried a minimum depth of three feet below ground level. Should the pit content level not meet the three foot minimum depth requirement, the excess contents shall be removed until the required minimum depth of three feet below ground level has been met. The operator shall properly dispose of the excess contents at an authorized disposal site.

The reserve pit shall be constructed and maintained so that runoff water from outside the location is not allowed to enter the pit. The berms surrounding the entire perimeter of the pit shall extend a minimum of two (2) feet above ground level. At no time will standing fluids in the pit be allowed to rise above ground level.

The reserve pit shall be fenced on three (3) sides during drilling operations. The fourth side shall be fenced immediately upon rig release.

D. FEDERAL MINERAL MATERIALS PIT

If the operator elects to surface the access road and/or well pad, mineral materials extracted during construction of the reserve pit may be used for surfacing the well pad and access road and other facilities on the lease.

Payment shall be made to the BLM prior to removal of any additional federal mineral materials from any site other than the reserve pit. Call the Carlsbad Field Office at (575) 234-5972.

E. WELL PAD SURFACING

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation.

The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

F. ON LEASE ACCESS ROADS

Road Width

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed thirty (30) feet.

Surfacing

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

Crowning


Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

Ditching

Ditching shall be required on both sides of the road.

Turnouts


Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall be constructed on all blind curves. Turnouts shall conform to the following diagram:



Drainage

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill outslowing and insloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

Formula for Spacing Interval of Lead-off Ditches

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

$$400 \text{ foot road with } 4\% \text{ road slope: } \frac{400'}{4\%} + 100' = 200' \text{ lead-off ditch interval}$$

Culvert Installations

Appropriately sized culvert(s) shall be installed at the deep waterway channel flow crossing.

Cattleguards

An appropriately sized cattleguard(s) sufficient to carry out the project shall be installed and maintained at fence crossing(s).

Any existing cattleguard(s) on the access road shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattleguard(s) that are in place and are utilized during lease operations.

A gate shall be constructed and fastened securely to H-braces.

Fence Requirement


Where entry is required across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting.

The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fence(s).

Public Access

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.

Figure 1 – Cross Sections and Plans For Typical Road Sections



VII. DRILLING

A. DRILLING OPERATIONS REQUIREMENTS

The BLM is to be notified a minimum of 4 hours in advance for a representative to witness:

- a. Spudding well.
- b. Setting and/or Cementing of all casing strings
- c. BOPE tests

☒ **Lea County**

Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240,
(575) 393-3612

1. A Hydrogen Sulfide (H₂S) Drilling Plan should be activated 500 feet prior to drilling into the Yates formation. **As a result, the Hydrogen Sulfide area must meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, please provide measured values and formations to the BLM.**
2. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
3. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works is located, this does not include the dog house or stairway area.
4. **The record of the drilling rate along with the CAL/GR/N well log run from TD to surface will be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.**

B. CASING

Changes to the approved APD casing and cement program require submitting a sundry and receiving approval prior to work. Failure to obtain approval prior to work will result in an Incident of Non-Compliance being issued.

Centralizers required on surface casing per Onshore Order 2.III.B.1.f.

Wait on cement (WOC) time for a primary cement job will be a minimum 18 hours for a water basin, 24 hours in the potash area, or 500 pounds compressive strength, whichever is greater for all casing strings. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. See individual casing strings for details regarding lead cement slurry requirements.

No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.

Possible water and brine flows in the Salado and Artesia Groups.

Possible high pressures in the Wolfcamp and Pennsylvanian Group.

1. **The 13-3/8 inch surface casing shall be set at approximately 1100 feet (a minimum of 25 feet into the Rustler Anhydrite and above the salt) and cemented to the surface. Fresh water mud to be used to setting depth. Due to the additional casing length, the proposed cement calculates an excess of 3%, therefore more cement may be required to circulate to surface.**
 - a. **If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement.**
 - b. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry.**
 - c. **Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.**
 - d. **If cement falls back, remedial cementing will be done prior to drilling out that string.**
2. **The minimum required fill of cement behind the 8-5/8 inch intermediate casing is:**

- ☒ **Cement to surface. If cement does not circulate see B.1.a, c-d above.
Casing is to set in the Tansill formation.**

Formation below the 8-5/8" shoe to be tested according to Onshore Order 2.III.B.1.i. Test to be done as a mud equivalency test using the mud weight necessary for the pore pressure of the formation below the shoe (not the mud weight required to prevent dissolving the salt formation) and the mud weight for the bottom of the hole. Report results to BLM office.

3. The minimum required fill of cement behind the 5-1/2 inch production casing is:
 - a. First stage to DV tool, cement shall:
 - ☒ Cement to circulate. If cement does not circulate, contact the appropriate BLM office before proceeding with second stage cement job.
 - b. Second stage above DV tool, cement shall:
 - ☒ Cement should tie-back at least 200 feet into previous casing string. Operator shall provide method of verification.
4. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.

C. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **2000 (2M) psi**.
3. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the 8-5/8 inch intermediate casing shoe shall be **5000 (5M) psi. 5M system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.**
4. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - a. The tests shall be done by an independent service company.
 - b. The results of the test shall be reported to the appropriate BLM office.
 - c. All tests are required to be recorded on a calibrated test chart. **A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.**

- d. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug.
- e. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the **Wolfcamp** formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.
- f. **Effective November 1, 2008, no variances will be granted on reduced pressure tests on the surface casing and BOP/BOPE. Onshore Order 2 requirements will be in effect.**

D. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the **Wolfcamp** formation, and shall be used until production casing is run and cemented.

Proposed mud weight may not be adequate for drilling through Wolfcamp.

E. DRILL STEM TEST

If drill stem tests are performed, Onshore Order 2.III.D shall be followed.

RGH 111009

VIII. PRODUCTION (POST DRILLING)

A. WELL STRUCTURES & FACILITIES

Placement of Production Facilities

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

Containment Structures

The containment structure shall be constructed to hold the capacity of the entire contents of the largest tank, plus 24 hour production, unless more stringent protective requirements are deemed necessary by the Authorized Officer.

Painting Requirement

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color Shale Green, Munsell Soil Color Chart # 5Y 4/2

IX. INTERIM RECLAMATION & RESERVE PIT CLOSURE**A. INTERIM RECLAMATION**

If the well is a producer, interim reclamation shall be conducted on the well site in accordance with the orders of the Authorized Officer. The operator shall submit a Sundry Notices and Reports on Wells (Notice of Intent), Form 3160-5, prior to conducting interim reclamation.

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

At the time reserve pits are to be reclaimed, operators should work with BLM surface management specialists to devise the best strategies to reduce the size of the location. Any reductions should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

B. RESERVE PIT CLOSURE

The reserve pit, when dried and closed, shall be recontoured, all trash removed, and reseeded as follows:

Seed Mixture for LPC Sand/Shinnery Sites

The holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)* per acre. There shall be no primary or secondary noxious weeds in the seed mixture. Seed will be tested and the viability testing of seed will be done in accordance with State law(s) and within nine (9) months prior to purchase. Commercial seed will be either

certified or registered seed. The seed container will be tagged in accordance with State law(s) and available for inspection by the authorized officer.

Seed will be planted using a drill equipped with a depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture will be evenly and uniformly planted over the disturbed area (smaller/heavier seeds have a tendency to drop the bottom of the drill and are planted first). The holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed will be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre are to be doubled. The seeding will be repeated until a satisfactory stand is established as determined by the authorized officer. Evaluation of growth will not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed* per acre:

<u>Species</u>	<u>lb/acre</u>
Plains Bristlegrass	5lbs/A
Sand Bluestem	5lbs/A
Little Bluestem	3lbs/A
Big Bluestem	6lbs/A
Plains Coreopsis	2lbs/A
Sand Dropseed	1lbs/A

**Four-winged Saltbush 5lbs/A

* This can be used around well pads and other areas where caliche cannot be removed.

*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed

X. FINAL ABANDONMENT & REHABILITATION REQUIREMENTS

Upon abandonment of the well and/or when the access road is no longer in service the Authorized Officer shall issue instructions and/or orders for surface reclamation and restoration of all disturbed areas.

On private surface/federal mineral estate land the reclamation procedures on the road and well pad shall be accomplished in accordance with the private surface land owner agreement.

Ground-level Abandoned Well Marker to avoid raptor perching: Upon the plugging and subsequent abandonment of the well, the well marker will be installed at ground level on a plate containing the pertinent information for the plugged well. For more installation details, contact the Carlsbad Field Office at 575-234-5972.

C-144 Modification Supplemental Documentation

Lusk 31 Federal #3 API # 30-025-39593

Introduction

Lynx Petroleum Consultants, Inc. (Lynx) requests administrative approval to construct the temporary drilling pit with 1.5H:1V slopes for certain sides of the drilling pit as shown in the design drawings. Lynx will adhere to all other prescriptive mandates of NMOCD Rules. If any statements in this submission inadvertently suggest that Lynx will not adhere to all other mandates in NMOCD Rules, Lynx will adhere to the Rules, not the text in this submission. If NMOCD finds any such language, please bring it to our attention so we may correct it.

Hydrogeologic Data

The information identified in item 10, "Siting Criteria" of the C-144 is attached. These are:

1. Figure 1 –presents data from the Office of the State Engineer (OSE) database and USGS database. This figure shows the location of the nearest registered water supply wells and available depth to ground water data.
2. Figure 2- USGS topographic map of the area. These maps show locations of any significant watercourse the locations of windmills and other wells that may not be registered with the OSE
3. Figure 3 – recent aerial photograph showing the presence of structures, which in this area are oil wells and tank batteries
4. Figure 4 - is a street map that also shows the location of the nearest incorporated municipal boundary
5. Figure 5 – shows the no wetlands are identified in the area directly surrounding the site
6. Figure 6 – shows the location of the nearest identified subsurface mine
7. Figure 7 – shows the area in relation to identified unstable areas

A FEMA floodplain map of the area does not yet exist. However, Figure 2 and our site visit confirm that this sand dune area is not within a floodplain. There is no evidence of flooding at or near the site that would endanger the temporary pit or burial trench. Our analysis agrees with the evaluation of NMOCD through the approved permit for the pit and in-place burial.

Siting Criteria Compliance Demonstration

As designated in the C-144 the location of the pit and burial trench meet the criteria of NMOCD Rules. We believe the data presented in Figures 1-7 demonstrate that:

Ground water is GREATER than 100 feet below the bottom of the temporary pit and proposed burial trench

Figure 1 shows all wells in the OSE database, wells with depth to water data from the USGS database and information on well depths and aquifers from the

C-144 Modification Supplemental Documentation
Lusk 31 Federal #3 API # 30-025-39593

Petroleum Recovery Research Center (PRRC). The map confirms information typically employed by NMOCD to determine the depth to water.

The map indicates that nearby wells obtain ground water from the Santa Rosa Sandstone (the base of the Chinle) or from the Chinle (based upon our evaluation of recorded total depths and the independent evaluation by the PRRC). Ground water in the Chinle (and Santa Rosa) is generally under pressure (confined) and therefore cannot be impaired by surface releases. Moreover, wells south of the site that draw water from the Chinle and Santa Rosa show depth to water measurements in excess of 100 feet. Note that some wells in the OSE database do not have data for depth to water or total depth (e.g. TD = 0) and these registered wells might be applications for wells that were not drilled, wells drilled prior to requirements to submit information to the OSE or drilled wells where the applicant did not submit data.

The pit, excavated material and burial trench is NOT within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).

The approved permit for in-place burial, Figure 2-3 and Appendix A confirm this statement.

The pit and burial trench is NOT within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.

The approved permit, Figure 2-3 and Appendix A confirm this statement.

The pit and burial trench is NOT within 500 feet of a private, domestic fresh water well or spring used by less than five households for domestic or stock watering purposes, it is NOT within 1,000 feet of any other fresh water well or spring.

The approved permit, Figures 1-3 and Appendix A support this statement.

The pit and burial trench is NOT within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.

The approved permit for in-place burial and Figure 4 confirm this statement.

The pit and burial trench is NOT within 500 feet of a wetland.

The approved permit for in-place burial, Figure 5 and Appendix A confirm this statement.

The pit, excavated material and burial trench is NOT within an area overlying a subsurface mine.

**C-144 Modification Supplemental Documentation
Lusk 31 Federal #3 API # 30-025-39593**

The approved permit for in-place burial and Figure 6 confirm this statement. The closest underground mine is shown in the southeast corner of Figure 6, many miles south of the site.

The pit and burial trench is NOT within an unstable area.

Our inquiry confirms the opinion suggested by the approved permit for in-place burial, that the pit (and proposed burial trench) is not in an unstable area. Figure 7 shows that the area is not within any karst area, which is a strong indicator of unstable areas. Our site visit and our examination of the geology of the area (see Figure 1) allow us to provide a professional opinion that the site is not in an unstable area.

The pit, excavated material and burial trench is NOT within a 100-year floodplain.

The approved permit for in-place burial, Figure 2 and our site visit confirm this statement. The location of the pit is not in or near an active watercourse. No FEMA map has been created for this area, so our professional judgment is based on observations of the site location and other available data.

Design Plan

Figures 8 through 10 present the design plan for the proposed drilling pit. The plan consists of the following protocols, which are derived from NMOCD Rules. The purpose of the pit is to contain liquids and solids, prevent contamination of fresh water and protect public health and the environment. The design proposes appropriate engineering principles and practices and will follow applicable liner manufacturers' requirements. Lynx will:

- I. Prior to constructing the pit the operator will strip and stockpile the topsoil for use as the final cover or fill at the time of closure.
- II. The operator will post an upright sign not less than 12 inches by 24 inches with lettering not less than two inches in height in a conspicuous place on the fence surrounding the pit, unless the pit is located on a site where there is an existing well signed in compliance with 19.15.16.8 NMAC, that is operated by the same operator. The operator will post the sign in a manner and location such that a person can easily read the legend. The sign will provide the following information: the operator's name; the location of the site by quarter-quarter or unit letter, section, township and range; and emergency telephone numbers.
- III. The operator will fence or enclose the pit in a manner that prevents unauthorized access and will maintain the fences in good repair.
- IV. The operator will fence the pit to exclude livestock with a four foot fence that has at least four strands of barbed wire evenly spaced in the interval between one foot and four feet above ground level.

With respect to the design and construction of the temporary pit:

C-144 Modification Supplemental Documentation
Lusk 31 Federal #3 API # 30-025-39593

- A. The operator will design and construct a temporary pit to ensure the confinement of liquids to prevent unauthorized releases.
- B. The temporary pit will have a properly constructed foundation and interior slopes consisting of a firm, unyielding base, smooth and free of rocks, debris, sharp edges or irregularities to prevent the liner's rupture or tear.
- C. The operator will construct a temporary pit so that the slopes are no steeper than two horizontal feet to one vertical foot (2H:1V). However, this application requests that the appropriate division district office approve an alternative to the slope requirement as shown in the design diagram in Figure 10, some slopes will be 1.5H:1V. NMOCD's approval of similar requests provides the demonstration that the operator can construct and operate the temporary pit in a safe manner to prevent contamination of fresh water and protect public health and the environment.
- D. The temporary pit uses a geomembrane liner consisting of 20-mil string reinforced LLDPE that the appropriate division district office has approved in the past. The geomembrane liner is composed of an impervious, synthetic material that is resistant to petroleum hydrocarbons, salts and acidic and alkaline solutions. The liner material is resistant to ultraviolet light. Liner compatibility complies with EPA SW-846 method 9090A.
- E. The operator will minimize liner seams and orient them up and down, not across a slope. The operator will use factory welded seams where possible. Prior to field seaming, the operator will overlap liners four to six inches and orient seams parallel to the line of maximum slope, *i.e.*, oriented along, not across, the slope. The operator will minimize the number of field seams in corners and irregularly shaped areas.
- F. Qualified personnel will perform field seaming. The operator will weld field liner seams.
- G. Construction will avoid excessive stress-strain on the liner.
- H. Geotextile will be placed under the liner where needed to reduce localized stress-strain or protuberances that may otherwise compromise the liner's integrity.
- I. The operator will anchor the edges of all liners in the bottom of a compacted earth-filled trench. The anchor trench will be at least 18 inches deep.
- J. The operator will ensure that the liner is protected from any fluid force or mechanical damage at any point of discharge into or suction from the lined temporary pit through the placement of a layer of protective felt over the liner and the placement of pipes at these locations as shown in the design drawings.
- K. The operator will design and construct a temporary pit to prevent run-on of surface water. A berm, ditch, proper sloping or other

C-144 Modification Supplemental Documentation

Lusk 31 Federal #3 API # 30-025-39593

diversion will surround a temporary pit to prevent run-on of surface water as shown on the design drawings.

- L. The volume of a temporary pit does not exceed 10 acre-feet, including freeboard.

Additionally:

- If practical, the contractor will separate coarser material from finer-grained material excavated from the pit for use in constructing the soil cover over the buried waste when operations of the drilling pit cease.
- Below the liner, the contractor will install the leak detection system described in the design drawings.
- Above the liner, a drain system composed of perforated pipe will allow removal of brine and associated constituents of concern from the residual solid materials.

Operations Plan

As stated earlier, the operator will operate and maintain the temporary pit to contain liquids and solids and maintain the integrity of the liner, liner system or secondary containment system, prevent contamination of fresh water and protect public health and the environment. Specifically:

1. The operator will dispose of all drilling fluids in a manner, approved by division rules, that prevents the contamination of fresh water and protects public health and the environment.
2. The operator will not discharge into or store any hazardous waste in the temporary pit.
3. If the pit liner's integrity is compromised, or if any penetration of the liner occurs above the liquid's surface, then the operator will notify the appropriate division district office within 48 hours of the discovery and repair the damage or replace the liner.
4. If the pit develops a leak, or if any penetration of the pit liner occurs below the liquid's surface, then the operator will remove all liquid above the damage or leak line within 48 hours, notify the appropriate division district office within 48 hours of the discovery and repair the damage or replace the pit liner.
5. The injection or withdrawal of liquids from the pit will be accomplished through a header, diverter or other hardware that prevents damage to the liner by erosion, fluid jets or impact from installation and removal of hoses or pipes.
6. The operator will operate and install the pit to prevent the collection of surface water run-on.
7. The operator will install, or maintain on site, an oil absorbent boom or other device to contain and remove oil from the pit's surface.

The operator will maintain and operate a temporary pit in accordance with the following additional protocols.

C-144 Modification Supplemental Documentation
Lusk 31 Federal #3 API # 30-025-39593

- a. Only fluids used or generated during the drilling process will be discharged into a temporary pit.
- b. The operator will maintain the temporary pit free of miscellaneous solid waste or debris.
- c. The operator shall use a tank made of steel or other material, which the appropriate division district office approves, to contain hydrocarbon-based drilling fluids. The operator does not plan on using hydrocarbon-based drilling fluids.
- d. Immediately after cessation of a drilling operation, the operator will remove any visible or measurable layer of oil from the surface of the drilling pit.
- e. The operator will maintain at least two feet of freeboard for a temporary pit.
- f. The operator will inspect a temporary pit containing drilling fluids at least daily while the drilling rig is on-site.
- g. Thereafter, the operator will inspect the temporary pit weekly so long as liquids remain in the temporary pit.
- h. The operator will maintain a log of such inspections and make the log available for the appropriate division district office's review upon request. The operator will file a copy of the log with the appropriate division district office when the operator closes the temporary pit.
- i. The operator will remove all free liquids from a temporary pit within 30 days from the date that the operator releases the drilling rig. The operator will note the date of the drilling or workover rig's release on form C-105 or C-103 upon well completion.

In addition to the specifications outlined above, Lynx will:

- Use steel pit and lined outer horse shoe reserve pit to circulate mud and drill surface casing with fresh water.
- Use steel pit and lined inner horse shoe reserve pit to circulate mud and drill intermediate casing with saturated brine.
- Transfer sufficient brine fluid from inner pit to outer horse shoe pit to create appropriate salinity/weight of drilling fluid for drilling to total depth.
- Use steel pit and lined outer horse shoe reserve pit to circulate mud and drill to total depth with cut brine.
- When possible, add fresh water to inner pit to create brine/cut brine and transfer fluid to outer pit as necessary to accommodate for fluid loss during drilling.
- During drilling the liner leak detection system is checked routinely and weekly during drying and closure.
- After 10-40 days of drainage pumping and solids drying, the solids will be sampled as described below.

Closure Plan

Siting Criteria Compliance Demonstration

As described above, the site meets all of the siting criteria for on-site trench burial.

Proof of Surface Owner Notification

The Federal government is the surface landowner and their representative, the BLM, has approved the APD with the provision for on-site burial of cuttings. The approved APD is proof of surface owner notification.

Construction/Design of Burial Trench

Lynx proposes to close the pit using an on-site trench adjacent to the temporary pit. The operator will design and construct an on-site trench for closure as specified in Paragraph (2) of Subsection B of 19.15.17.13 NMAC. Specifically:

1. The operator will excavate to an appropriate depth that allows for the installation of the geomembrane bottom liner, geomembrane liner cover and the division-prescribed soil cover required pursuant to Subsection H of 19.15.17.13 NMAC.
2. The on-site trench will have a properly constructed foundation and side walls consisting of a firm, unyielding base, smooth and free of rocks, debris, sharp edges or irregularities to prevent the liner's rupture or tear.
3. Geotextile will be placed under the liner where needed to reduce localized stress-strain or protuberances that may otherwise compromise the liner's integrity.
4. The on-site trench will be constructed with a geomembrane liner that consists of a 20-mil string reinforced LLDPE liner
5. The geomembrane liner will be composed of an impervious, synthetic material that is resistant to petroleum hydrocarbons, salts and acidic and alkaline solutions. The liner material will be resistant to ultraviolet light. Liner compatibility will comply with EPA SW-846 method 9090A.
6. The operator will minimize liner seams and orient them up and down, not across a slope and the operator will use factory welded seams where possible. Prior to field seaming, the operator will overlap liners four to six inches and orient liner seams parallel to the line of maximum slope, *i.e.*, oriented along, not across, the slope. The operator will minimize the number of field seams in corners and irregularly shaped areas.
7. Qualified personnel will perform field seaming. The operator will weld field liner seams.

**C-144 Modification Supplemental Documentation
Lusk 31 Federal #3 API # 30-025-39593**

8. The operator will install sufficient liner material to reduce stress-strain on the liner.
9. The operator will ensure that the outer edges of all liners are secured for the placement of the excavated waste material into the trench.
10. The operator will fold the outer edges of the trench liner to overlap the waste material in the trench prior to the installation of the geomembrane cover.
11. The operator will install a geomembrane cover over the waste material in the lined trench. The operator will install the geomembrane cover in a manner that prevents the collection of infiltration water in the lined trench and on the geomembrane cover after the soil cover is in place.
12. The geomembrane cover will consist of a 20-mil string reinforced LLDPE liner. The geomembrane cover will be composed of an impervious, synthetic material that is resistant to petroleum hydrocarbons, salts and acidic and alkaline solutions. Cover compatibility will comply with EPA SW-846 method 9090A.

Protocols and Procedures

The operator will remove all liquids from the temporary pit prior to closure and dispose of the liquids in a division-approved facility or recycle, reuse or reclaim the liquids in a manner that the appropriate division district office approves.

Prior to placing the contents from the temporary pit into the trench, the operator will stabilize or solidify the contents to a bearing capacity sufficient to support the final cover of the trench burial. The operator will not mix the contents with soil or other material at a mixing ratio of greater than 3:1, soil or other material to contents.

The operator will place a steel marker at the center of an on-site burial. The steel marker will be not less than four inches in diameter and will be cemented in a three-foot deep hole at a minimum. The steel marker will extend at least four feet above mean ground level and at least three feet below ground level. The operator name, lease name and well number and location, including unit letter, section, township and range, and that the marker designates an on-site burial location will be welded, stamped or otherwise permanently engraved into the metal of the steel marker.

The operator will report the exact location of the on-site burial on form C-105 filed with the division.

The operator will file a notice with the BLM identifying the exact location of the on-site burial as there is no deed associated with this location

C-144 Modification Supplemental Documentation

Lusk 31 Federal #3 API # 30-025-39593

Confirmation Sampling Plan

Because ground water is more than 100 feet below the bottom of the temporary pit, the operator will collect, at a minimum, a five point, composite sample; collect individual grab samples from any area that is wet, discolored or showing other evidence of a release; and analyze for benzene, total BTEX, TPH, the GRO and DRO combined fraction and chlorides to demonstrate that benzene, as determined by EPA SW-846 method 8021B or 8260B or other EPA method that the division approves, does not exceed 0.2 mg/kg; total BTEX, as determined by EPA SW-846 method 8021B or 8260B or other method that the division approves, does not exceed 50 mg/kg; the GRO and DRO combined fraction, as determined by EPA SW-846 method 8015M, does not exceed 500 mg/kg; the TPH, as determined by EPA method 418.1 or other EPA method that the division approves, does not exceed 2500 mg/kg; and chlorides, as determined by EPA method 300.1, do not exceed 1000 mg/kg or the background concentration, whichever is greater. The operator will notify the division of its results on form C-141.

If the operator or the division determines that a release has occurred, then the operator will comply with 19.15.29 NMAC and 19.15.30 NMAC, as appropriate.

If the sampling program demonstrates that a release has not occurred or that any release does not exceed the concentrations specified in Subparagraph (c) of Paragraph (3) of Subsection F of 19.15.17.13 NMAC, as the operator has certified to the division that it has given written notice to the surface owner that it intends to do so. The operator will use a separate on-site trench for closure of the temporary pit. The operator will backfill the temporary pit excavation with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover; recontour and re-vegetate the site. The division-prescribed soil cover, recontouring and re-vegetation requirements will comply with Subsections G, H and I of 19.15.17.13 NMAC.

Waste Material Sampling Plan

The operator will collect at a minimum, a five point, composite sample of the contents of the temporary pit to demonstrate that the TPH concentration, as determined by EPA method 418.1 or other EPA method that the division approves, does not exceed 2500 mg/kg. Using EPA SW-846 method 1312 or other EPA leaching procedure that the division approves, the operator will demonstrate that (i) the chloride concentration, as determined by EPA method 300.1 or other EPA method that the division approves, does not exceed 3000 mg/l or the background concentration, whichever is greater, (ii) the concentrations of the inorganic water contaminants specified in Subsection A of 20.6.2.3103 NMAC as determined by appropriate EPA methods do not exceed the standards specified in Subsection A of 20.6.2.3103 NMAC or the background concentration, whichever is greater, and (iii) the concentrations of the organic water contaminants specified in Subsection A of 20.6.2.3103 NMAC as

C-144 Modification Supplemental Documentation

Lusk 31 Federal #3 API # 30-025-39593

determined by appropriate EPA methods do not exceed the standards specified in Subsection A of 20.6.2.3103 NMAC, unless otherwise specified above. The operator may collect the composite sample prior to treatment or stabilization to demonstrate that the contents do not exceed these concentrations. However, if the contents collected prior to treatment or stabilization exceed the specified concentrations the operator will collect a second five point, composite sample of the contents after treatment or stabilization to demonstrate that the contents do not exceed these concentrations.

Soil Cover Design

After the operator has removed the pit contents to the burial trench, the soil cover will consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater.

The soil cover for trench burial will consist of a minimum of four feet of compacted, non-waste containing, earthen material. The soil cover will include either the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater.

The operator will construct the soil cover to the site's existing grade and prevent ponding of water and erosion of the cover material.

Re-vegetation Plan

The first growing season after the operator closes the pit and trench, the operator will seed or plant the disturbed areas.

The operator will accomplish seeding by a division-approved method. The operator will notify the NMOCD District Office of the proposed protocol at least 30-days prior to implementing the re-vegetation plan.

The operator will obtain vegetative cover that equals 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons.

During the two growing seasons that prove viability, there will be no artificial irrigation of the vegetation.

The operator will repeat seeding or planting until it successfully achieves the required vegetative cover.

When conditions are not favorable for the establishment of vegetation, such as periods of drought, the operator may request to delay seeding or planting until soil moisture conditions become favorable or may require the operator to use

C-144 Modification Supplemental Documentation Lusk 31 Federal #3 API # 30-025-39593

additional techniques such as mulching, fertilizing, irrigating, fencing or other practices.

The operator will notify the division when it has seeded or planted and when it successfully achieves re-vegetation.

Site Reclamation Plan

After closure of the pit and trench, the operator will reclaim the pit location and trench location and all areas associated with the pit and trench including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. The operator will substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC (described in this submittal), recontour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC (as described herein).

Alternative Closure Plan

In the event that the proposed closure method does not satisfy the on-site closure standards specified in Subsection F of 19.15.17.13 NMAC or, if applicable, other on-site closure standards that the environmental bureau in the division's Santa Fe office approves, the operator will close the temporary pit by excavating all contents and, if applicable, synthetic pit liners and transferring those materials to a division-approved facility.

Disposal Facility Names and Permit Numbers

Lea Land, LLC	NM-01-0035
Controlled Recovery, Inc.	NM-01-0006

Closure Notice and Reporting to NMOCD

The operator will notify the appropriate division district office verbally or by other means at least 72 hours, but not more than one week, prior to any closure operation. The notice will include the operator's name and the location to be closed by unit letter, section, township and range, well's name, number and API number.

Within 60 days of closure completion, the operator will submit a closure report on form C-144, with necessary attachments to document all closure activities including sampling results; information required by 19.15.17 NMAC; a plot plan; and details on back-filling, capping and covering, where applicable.

In the closure report, the operator will certify that all information in the report and attachments is correct and that the operator has complied with all applicable closure requirements and conditions specified in the approved closure plan. If the operator used a temporary pit, the operator shall provide a plat of the pit location on form C-105 within 60 days of closing the temporary pit.


Appendix A

Figure A-1: View North to the location, Lusk 31 Federal #2 on horizon at left.




Figure A-2: View east to location, Lusk 31 Federal #1





0 1
Miles




R.T. Hicks Consultants, Ltd
901 Rio Grande Blvd NW Suite F-142
Albuquerque, NM 87104
Ph: 505.266.5004

Geology and Depth to Ground Water (feet bgs)


Figure 1

Lynx Petroleum- Lusk 31 Federal #2

June 2010



0 1000 2000ft




Petroleum Recovery
Research Center

Topographic Map


Figure: 2

Lynx Petroleum Lusk 31 Federal #3

Jun 04, 2010



0 1000 2000ft



Petroleum Recovery
Research Center

Recent Air Photo

Figure: 3

Lynx - Lusk 31 Federal #3

Jun 04, 2010






Figure 5 Wetlands Around Site



Legend

- Interstate
- Major Roads
- Other Road
- Interstate
- State highway
- US highway
- Roads
- Cities
- USGS Quad Index 24K
- Lower 48 Wetland Polygons
- Estuarine and Marine Deepwater
- Estuarine and Marine Wetland
- Freshwater Emergent Wetland
- Freshwater Forested/Shrub Wetland
- Freshwater Pond
- Lake
- Other
- Riverine
- Lower 48 Available Wetland Data
- Non-Digital
- Digital
- No Data
- Scan
- NHD Streams
- Counties 100K
- Urban Areas 300K
- States 100K
- South America
- North America





Scale: 1:81,707



Map center: 32° 42' 7" N, 103° 48' 14" W

This map is a user generated static output from an Internet mapping site and is for general reference only. Data layers that appear on this map may or may not be accurate, current, or otherwise reliable. THIS MAP IS NOT TO BE USED FOR NAVIGATION.

Notes. Lynx Petroleum
LUSK 31 Fed #3








Patent Pending


R.T. Hicks Consultants, Ltd.	Pit Liner Schematics	Figure 8
	Lynx Petroleum Consultants - Lusk 31 Fed #3	May 2010

Soil Moisture Corporation Gypsum Block Model 5201F placed over 20-mil liner panel (dashed rectangles). Six inches of permeable material (e.g. soil or sand) placed between liner panel and primary pit liner. Poly pipe conduit protects electrical leads from block to surface. Sloped liner panel directs any seepage to moisture sensor



Patent Pending

R.T. Hicks Consultants, Ltd.	Leak Detection System Schematic	Figure 9
	Lynx Petroleum Consultants - Lust 31 Fed #3	May 2010



R.T. Hicks Consultants, Ltd.	Depth of Pit Below Grade and Dimensions	Figure 10
	Lynx Petroleum Consultants - Lust 31 Fed #3	May 2010

C-144 Modification Supplemental Documentation
Lusk 31 Federal #3 API # 30-025-39593

Previously Approved C-144