RECEIVED

Form 3160-5 (April 2004)

OCHUMBED 2010 **UNITED STATES**

DEPARTMENT OF THE INTERIOR HOBBSOCD BUREAU OF LAND MANAGEMENT

FORM APPROVED
OM B No 1004-0137
Expires: March 31, 2007

5. Lease Serial No. LC-066126-C

SUNDRY NOTICES AND REPORTS ON WELLS

	DC 000120 C
,	If Indian, Allottee or Tribe Name

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.					6 If Indian, Allottee or Tribe Name		
SUBMIT IN TRIPLICATE- Other instructions on reverse side.					7 If Unit or CA/Agreement, Name and/or No 8. Well Name and No. CRUCES FEDERAL #3 9. API Well No. 30-025-02459		
1. Type of Well Oil Well O Gas Well D Other INJECTION							
2. Name of Operator BURK ROYALTY CO., LTD.							
3a. Address P.O. BOX 94903, WICHITA FALLS, TX 76308		3b. Phone No. (mclude area code) 940-397-8638		10 Field and	Pool, or Exploratory Area		
4 Location of Well (Footage, Sec., T., R., M., or Survey Description) 330' FSL, 1655 FWL, SEC 26, T20S, R34E					1. YNCH YATES SEVEN RIVERS 11 County or Parish, State LEA COUNTY, NM		
12. CHECK A	PPROPRIATE BOX(ES) TO	O INDICATE NATUR	E OF NOTICE, R	EPORT, OR	OTHER DATA	_	
TYPE OF SUBMISSION	TYPE OF ACTION						
Notice of Intent Subsequent Report Final Abandonment Notice	Acidize Alter Casing Casing Repair Change Plans Convert to Injection	Deepen Fracture Treat New Construction Plug and Abandon Plug Back	Production (Statement Reclamation Recomplete Temporarily Ab Water Disposal	, 	Water Shut-Off Well Integrity Other RUN LINER		
13. Describe Proposed or Complete	ed Operation (clearly state all per					_	

If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

WELL HAD A CASING LEAK. SQUEEZED WELL WITH 350 SX CEMENT ON JUNE 15,2010, PAUL SWARTZ WITH THE BLM INDICATED WE SHOULD RUN A LINER. BURK WILL RUN A 4" LINER TO 3475' AND CIRCULATE CEMENT TO THE SURFACE:

1. RUN CAST IRON BRIDGE PLUG INSIDE 5-1/2" CASING AND SET AT 3490'-3492'.

2. RUN 4" OD 9.11# FLUSH JOINT J-55 LINER AND SET AT 3475' INSIDE THE 14# 5-1/2" CASING (WITH 1D OF 5.0120 LEAVING TOTAL CLEARANCE OF 1.012 OR 0.506 ON EACH SIDE).

3. CEMENT WITH 170 SACKS CLASS H WITH A YIELD OF 1.18 CU FT/SACK SUFFICIENT TO FILL UP 4030 FEET OR 16% BUFFER.

4. DRILL OUT CEMENT AND BRIDGE PLUG.

5. RUN INJECTION STRING AND BAKER AD-1 PACKER. SET PACKER AT 3432' AND RETURN TO INJECTION.

PLEASE ADVISE IF ADDITIONAL INFORMATION IS REQUIRED.

SEE ATTACHED FOR CONDITIONS OF APPROVAT

	CONDITIO	NS OF AFTROVAL				
14 Thereby certify that the foregoing is true and correct Name (Printed/Typed)						
JON H. BEAR	Title ENGINEER	ARREOVED				
Signature John Sean	Date 06/25/2010	ALLINOVED				
THIS SPACE FOR FEDERAL						
Approved by	Title					
Conditions of approval, if any, are attached. Approval of this notice does not warrar certify that the applicant holds legal or equitable title to those rights in the subject leads which would entitle the applicant to conduct operations thereon.	. 1	WESLEY W. INGRAM PETROLEUM ENGINEER				
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.						

(Instructions on page 2)

2010

Cruces Federal #3 30-025-02459 Burk Royalty Co., Ltd. June 28, 2010 Condition of Approval

Operator to contact Paul Swartz at 575-200-7902 a minimum of 24 hours prior to installing liner/casing.

WWI 062810