

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
May 27, 2004

RECEIVED
JUL 08 2010
HOBBSOCD

WELL API NO. 30-025-08922 ✓
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> ✓
6. State Oil & Gas Lease No. A 2614
7. Lease Name or Unit Agreement Name: McDonald WN State ✓
8. Well Number 14 ✓
9. OGRID Number 00778 ✓
10. Pool name or Wildcat Jalmat Tansil Yates SRQ Gas ✓

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other <input checked="" type="checkbox"/>	7. Lease Name or Unit Agreement Name: McDonald WN State ✓
2. Name of Operator BP America Production Company ✓	8. Well Number 14 ✓
3. Address of Operator P.O. Box 1089 Eunice NM 88231	9. OGRID Number 00778 ✓
4. Well Location Unit Letter <u>G</u> : <u>1650</u> feet from the <u>N</u> line and <u>1650</u> feet from the <u>E</u> line Section <u>15</u> Township <u>22S</u> Range <u>36E</u> NMPM County <u>LEA</u> ✓	10. Pool name or Wildcat Jalmat Tansil Yates SRQ Gas ✓
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3550' GR	
Pit or Below-grade Tank Application <input type="checkbox"/> or Closure <input type="checkbox"/> Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____ Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____	

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give dates of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram or proposed completion or recompletion.

6/24/10: MIRU 6/28/10: ND/WH, NU BOPS. RIH TO 3200' TO START FREE POINTING. WORKED WAY DOWN TO 3345' WHERE WE TAGGED. PUMPED 16 BBLS FW TO CLEAR TBG. PU/RIH 1 11/16" CHEMICAL CUTTER TO 3330'. CUT PIPE. POH LD 5 JTS 2 3/8" TBG.
6/29/10: CHECK PRESS ON WELL. BOTH CSG & TBG ON VACUUM. POH/LD 113 JTS 2 3/8" J-55 TBG. TIH 100 JTS 2 3/8" J-55 W/ 5 1/2" BIT & SCRAPER. RAN TO 3117'. POH/LD BIT & SCRAPER. RIH CIBP & SET @ 3100' & PRESS TEST. SPOTTED 30 SACKS CLASS "C" CEMENT ON TOP OF PLUG. TOC IS +/-2800'. POH/LD 12 JTS TBG TO 2738' & CIRC 75 BBLS 9.5 PPG PLUG MUD. POH/LD TO 1700'.
Continued on page 2.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐ , a general permit ☐ or an (attached) alternative OCD-approved plan ☐

SIGNATURE Steve M. Pacheco TITLE Operations Team Lead - SENM DATE 7/7/10
E-mail address: steve.pacheco@bp.com
Type or print name Steve M. Pacheco Telephone No. 575-394-1648

For State Use Only

APPROVED BY [Signature] TITLE STAFF MGR DATE 7-12-10
Conditions of Approval, if any: km

Form C-103
McDonald WN State #14
30-025-08922
Continued from page 1

6/30/10: SPOTTED PLUG FROM 1800' TO 1400' W/ 30 SACKS CLASS "C" CEMENT W/ 2% CACL2. PUMPED AT 2 BBLS/MIN. POH/LD SCA SETTING TOOL. PICK UP AND RIH SLOTTED TO 1200'. WOC. RIH TAG CEMENT PLUG @ 1383'. POH/LD TO 400'. PUMP SURFACE PLUG FROM 400' TO SURFACE. POH/LD, TOP WELL OFF W/ CMT. PUMPED 60 SACKS CLASS "C" W/ 2% CACL2, TOTAL AT 2 BBLS/MIN. ND BOPS, RD PU.

7/1/10: DIG OUT AROUND WELLHEAD, CUT OFF ALL ANCHORS & WELLHEAD, WELD IN PLATE, 1" NIPPLE & VALVE, DRY HOLE MARKER, BACKFILL AND LEVEL LOCATION.