

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

OCD-HOBBS

JUL 08 2010

FORM APPROVED
OMB No. 1004-0137
Expires: March 31, 2007

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE- Other instructions on reverse side.

1. Type of Well <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other		5. Lease Serial No. LC 058418
2. Name of Operator Chevron Midcontinent, L.P.		6. If Indian, Allottee or Tribe Name
3a. Address 15 Smith Rd., Midland, TX 79705	3b. Phone No. (include area code) 432-561-8600	7. If Unit or CA/Agreement, Name and/or No.
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) UL E, Sec. 31-T16S-R37E 1745' FNL & 1275' FWL		8. Well Name and No. LOVINGTON PADDOCK UNIT #89
		9. API Well No. 30-025-31148
		10. Field and Pool, or Exploratory Area LOVINGTON PADDOCK
		11. County or Parish, State Lea, NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input checked="" type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

1. Notify BLM 24 hrs prior to MI and RU.
2. RIH set TAG PBTD at 5965', spot 25sx, plug from 5965'-5765'.
3. Displace hole w/MLF, 9.5# Brine w/25# gel P/BBL.
4. Perf 4 holes at 3225, sqz 75sx cement from 3225'-2950' (Yates/B.Salt). WOC&TAG.
5. Perf 4 holes at 2273', sqz 100sx cement plug from 2273'-1880' (T-Salt/shoe) WOC&TAG.
6. Perf 4 holes at 400', sqz 110sx cement plug from 400'-surface' (Shoe/Fr. Wtr./surface) WOC&TAG.
7. Install dry hole marker.

RECLAMATION PROCEDURE
ATTACHEDSEE ATTACHED FOR
CONDITIONS OF APPROVAL

14. I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

M. Lee Roark

Title Agent for Chevron USA, inc.

Signature

Date

06/24/2010

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Date

Office

Date

JUL 6 2010
/s/ Dustin Winkler

JUL 12 2010

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

BUREAU OF LAND MANAGEMENT
CARLSBAD FIELD OFFICE

Well: Lovington Paddock Unit #89

Field: Lovington

Reservoir: Paddock

Location:

1745' FNL & 1275' FWL
 Section: 31 (SW/4 NW/4)
 Township: 16S
 Range: 37E Unit: E
 County: Lea State: NM

Elevations:

GL: 3828
 KB: 3845
 DF: 3844


Log Formation Tops

Rustler	2020
Salt	2173
B/Salt	3071
Yates	3118
Seven Rivers	3354
Queen	3774
Grayburg	4447
San Andres	4651
Glorieta	6020
Paddock	6114

TUBING DETAIL -

This wellbore diagram is based on the most recent information regarding wellbore configuration and equipment that could be found in the Midland Office wellfiles and computer databases as of the update below. Verify what is in the hole with the wellfile in the Lovington Field Office. Discuss w/WEO Engineer, WO Rep, OS, ALS, & FS prior to rigging up on well regarding any hazards or unknown issues pertaining to the well

Current
Wellbore Diagram

**Well ID Info:**

Cheveno: ON7415
 API No: 30-025-31148
 L5/L6:
 Spud Date: 4/11/91
 TD Reached: 4/23/91
 Compl. Date: 6/22/91

Surface Csg: 8 5/8" 24#

Set. @ 1980 w/1350 SA cmt
 Hole Size: 12 1/4" TO 1980
 Circ: TOC:
 TOC By:

Initial Completion:

6/22/91 (Paddock) 6077, 6082, 6085, 6112, 6117, 6127, 6139, 6151, 6154, 6158, 6162, 6164, 6171, 6177, 6182, 6186, 6191, 6194, 6219, 6222, 6225, 6227, 6230, 6244, 6248, 6256, 6258, 6268, 6273, 6289, 6293, 6295, 6302 (2 JSPF), A/17000 gal 28% NEFE

Subsequent Work

6/15/2007 TA, set CIBP @ 6015 w/ 35' cmt on top

10/31/08 Drill out CIBP and return to production

1/7/2009 TA, set CIBP @ 6000' w/ 35' cmt on top

Perfs

Status

CIBP @ 6000 w/ 35' cmt on top


Prod. Csg: 5 1/2" 15 5#
 Set: 6350 w/1400 sx cmt
 Hole Size: 7 7/8" to 6350
 Circ: TOC:
 TOC By:

6077, 6082, 6085, 6112, 6117, 6127, 6139, 6151, 6154, (Paddock - CIBP
 6162, 6164, 6171, 6177, 6182, 6186, 6191, 6194, 6219, (Paddock - CIBP
 6227, 6230, 6244, 6248, 6251, 6261, 6256, 6268, 6273, (Paddock - CIBP
 6293, 6295, 6302 Paddock - CIBP

TD: 6350 COTD: PBTD: 5980

Updated: 4-12-10 by WAYN

By W P Johnson

PLUGGING & ABANDONMENT WORKSHEET (2 STRING CSNG)**OPERATOR** Chevron Midcontinent L.P.**LEASENAME** Lovington Paddock Unit**WELL #** 89**SECT** 31 **TWN** 16S **RNG** 37E**FROM** 1745' (N) S L 1275' E (W) L**TD:** 6350'**FORMATION @ TD****PBTD:** 5965**FORMATION @ PBTD**

5 1/2\"
@ 6350'
 TOC unknown

TD 6350'

	SIZE	SET @	TOC	TOC DETERMINED BY
SURFACE	8 5/8	1880	surface	calculation
INTMED 1				
INTMED 2				
PROD	5 1/2	6350	unknown	
	SIZE	TOP	BOT	TOC DETERMINED BY
LINER 1				
LINER 2				
	CUT & PULL @		TOP - BOTTOM	
INTMED 1			PERF	6077 - 6302
INTMED 2			OPENHOLE	
PROD				

***REQUIRED PLUGS DISTRICT I**

PLUG	TYPE	SACKS	DEPTH
PLUG	PLUG	CMT	
EXAMPLES			
PLUG #1	OH	35 SXS	6400'
PLUG #2	SHOE	50 SXS	3350'-5450'
PLUG #3	CIRP/35'		4800'
PLUG #4	CIRP	25 SXS	4800'
PLUG #5	STUB	50 SXS	3600'-3700'
PLUG #6	REINR SCZ	200 SXS	400'
PLUG #7	SURF	10 SXS	0-10'
PLUG #8	PB verify	25 Sx	5965-5765
PLUG #9	1/4c/Salt	75 Sx	3225-2950
PLUG #10	Salt/shoe	100 Sx	2273-1880
PLUG #11	shoe/Fr.	110 Sx	400'-0'
PLUG #12	wtr./surf		
PLUG #13			
PLUG #14			
PLUG #15			
PLUG #16			
PLUG #17			
PLUG #18			
PLUG #19			
PLUG #20			
PLUG #21			
PLUG #22			
PLUG #23			
PLUG #24			
PLUG #25			
PLUG #26			
PLUG #27			
PLUG #28			
PLUG #29			
PLUG #30			
PLUG #31			
PLUG #32			
PLUG #33			
PLUG #34			
PLUG #35			
PLUG #36			
PLUG #37			
PLUG #38			
PLUG #39			
PLUG #40			
PLUG #41			
PLUG #42			
PLUG #43			
PLUG #44			
PLUG #45			
PLUG #46			
PLUG #47			
PLUG #48			
PLUG #49			
PLUG #50			
PLUG #51			
PLUG #52			
PLUG #53			
PLUG #54			
PLUG #55			
PLUG #56			
PLUG #57			
PLUG #58			
PLUG #59			
PLUG #60			
PLUG #61			
PLUG #62			
PLUG #63			
PLUG #64			
PLUG #65			
PLUG #66			
PLUG #67			
PLUG #68			
PLUG #69			
PLUG #70			
PLUG #71			
PLUG #72			
PLUG #73			
PLUG #74			
PLUG #75			
PLUG #76			
PLUG #77			
PLUG #78			
PLUG #79			
PLUG #80			
PLUG #81			
PLUG #82			
PLUG #83			
PLUG #84			
PLUG #85			
PLUG #86			
PLUG #87			
PLUG #88			
PLUG #89			
PLUG #90			
PLUG #91			
PLUG #92			
PLUG #93			
PLUG #94			
PLUG #95			
PLUG #96			
PLUG #97			
PLUG #98			
PLUG #99			
PLUG #100			

MUTLER (ANNYD)

YATES 2020

QUEEN 3774

ORAYBURG 4447

SAN ANDRES 4451

Top Salt 2173

CAPTAN REEF

Base Salt 3071

DELAWARE

BELL CANYON

CREELEY CANYON

BURNET CANYON

BONE SPEDNO

FLORIDA 6020

GLINEBKY

TUBS

DRINKARD

ALBO

WC

PENNY

STRAWN

ATOKA

JACOBLOW

LMB

DEVORIAN

Chevron Midcontinent, L.P.
NMLC-058418: Lovington Paddock Unit #89
API: 30-025-31148
Lea County, New Mexico

RE: Plugging and Abandonment Requirements – Conditions of Approval

H₂S monitoring equipment to be on location.

1. OK
2. OK (Perfs)
3. OK
4. Tag at 2950' or shallower. If injection rate cannot be established, spot cement 50' below perforations – Otherwise OK (Yates – BOS)
5. Tag at 1880' or shallower. If injection rate cannot be established, spot cement 50' below perforations – Otherwise OK (TOS – Casing shoe)
6. If injection rate cannot be established, spot cement 50' below perforations – Otherwise OK (Surface)
7. OK – Verify cement to surface in all annuluses.
8. Submit a subsequent report to the BLM.

See attached standard COAs.

DHW 070610

Requirements for ground level dry hole markers
Well Identification Markers
Conditions of Approval (COA)

The BLM Carlsbad Field Office (CFO) Conditions of Approval (COA) Requires that ground level dry hole markers be placed on well within the Lesser Prairie Chicken habitat area. The dry hole markers will be to the following specifications. The operator will construct the markers as follows:

1. An 8 inch X 8 inch steel plate 1/8 to 3/16 of an inch thick is to be placed on the old dry hole marker stand pipe 2 inches from ground level, in the Lesser Prairie Chicken habitat area.
2. Steel plate may be welded or bolted approximately 2 inches from ground level on the stand pipes. If plates are bolted to the stand pipe, the person installing the plate will be required to weld a pipe collar on the plate and place a minimum of two set screws/bolt on each collar. Aluminum data plates may be bolted with minimum 1/4 inch bolt and locking nuts or self tapping fine threaded screws. A minimum of one in each corner is to be installed on each plate.
3. An 8 inch x 8 inch aluminum plate, which is 12 gauge or .080 sign material (1/8 inch aluminum plate may be used in place of the .080 plate) with the required information for that well stamped or engraved in a minimum 3/8 inch tall letter or number.
4. The following information will be stamped or engraved on the 8 inch X 8 inch aluminum plate in the following order.
 - a. First row: Operators name
 - b. Second row: Well name and number
 - c. Third row: Legal location to include 1/4 1/4, Section, Township, and range. If the legal location cannot be placed on one row it can be split into two rows with the 1/4 1/4 (example: 1980 FNL 1980 FWL) being on the top row.
 - d. Fourth row: Lease Number and API number.
 - i. Example marker plate: (attached)

NMOCD Order No. R-12965 also required the operator to notify NMOCD when this type of dry hole marker is used. This can be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a ground level dry hole marker was installed as required in the COA's from the BLM.

BUREAU OF LAND MANAGEMENT

**Carlsbad Field Office
620 East Greene Street
Carlsbad, New Mexico 88220
575-234-5972**

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within **ninety (90)** days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

2. **Notification:** Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.

3. **Blowout Preventers:** A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. **Mud Requirement:** Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.

5. **Cement Requirement:** Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. In lieu of a cement plug in a cased hole, a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Any plug that requires a tag will have a minimum WOC time of 4 hours.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). **The BLM is to be notified when the wellhead is cut off to verify that cement is to surface in the casing and all annuluses.** The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement. The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

7. Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**

8. Trash: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation procedure.

DHW 112309



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office
620 E. Greene St.
Carlsbad, New Mexico 88220-6292
www.blm.gov/nm



In Reply Refer To: 1310

Interim Reclamation Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses.

Interim reclamation consists of minimizing the footprint of disturbance by reclaiming all portions of the well site not needed for production operations. The portions of the cleared well site not needed for operational and safety purposes are recontoured to a final or intermediate contour that blends with the surrounding topography as much as possible. Sufficient level area remains for setup of a workover rig and to park equipment. Topsoil is respread over areas not needed for all-weather operations. Production facilities should be clustered to maximize the opportunity for interim reclamation. In order to inspect and operate the well or complete workover operations, it may be necessary to drive, park, and operate on restored, interim vegetation within the previously disturbed area. This is generally acceptable provided damage is repaired and reclaimed following use.

To reduce final reclamation costs; maintain healthy, biologically active topsoil; and to minimize habitat, visual, and forage loss during the life of the well, all salvaged topsoil should be spread over the area of interim reclamation, rather than stockpiled.

1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). Interim reclamation is to be completed within 6 months of well completion.

3. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with interim reclamation as per approved APD or Sundry Notice. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.
4. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
5. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos
Supervisory Environmental Protection Specialist
575-234-5909, 575-361-2648 (Cell)

Cody Layton
Natural Resource Specialist
575-234-5959

Terry Gregston
Environmental Protection Specialist
575-234-5958

Trishia Bad Bear
Natural Resource Specialist
575-393-3612

Bobby Ballard
Environmental Protection Specialist
575-234-2230

Todd Suter
Surface Protection Specialist
575-234-5987

Randy Rust
Environmental Protection Specialist
575-234-5943

Doug Hoag
Civil Engineering Technician
575-234-5979

Linda Denniston
Environmental Protection Specialist
575-234-5974

Jennifer Van Curen
Environmental Protection Specialist
575-234-5905

Justin Frye
Environmental Protection Specialist
575-234-5922