

DISTRICT I

1625 N. French Dr., Hobbs NM 88240

DISTRICT II

1301 W. Grand Avenue, Artesia NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec NM 87410

DISTRICT IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, New Mexico 87504-2088

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-01824
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Yates Petroleum Corporation		6. State Oil & Gas Lease No. VO-5606
3. Address of Operator 105 South 4th Str., Artesia, NM 88210		7. Lease Name or Unit Agreement Name Blitzen AUB State
4. Well Location Unit Letter M : 660 feet from the South line and 660 feet from the West line Section 16 Township 11S Range 34E NMPM County Lea		8. Well No. 1
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4184' GR		9. Pool Name or Wildcat Wildcat Atoka

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:


REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Recompletion ☒

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

12-5-03 to 1-6-04

Set 4-1/2" cement retainer @ 11650'. Squeezed Atoka perms w/100 sx "H" Neat and 50 sx "H" w/fluid loss. Squeezed w/5 bbls cement below retainer. Drilled cement and CIBP @ 12200'. Set 4-1/2" CIBP @ 12228'. Perforated 12131-37' (24), 12146-55' (36) and 12186-95' (36) - .42" holes. Acidized w/1500 gal 7-1/2% Morrow acid. Perforated Strawn 11208-16' (16), 11221-38' (34) and 11244-56' (24) - .42" holes. Spot 250 gal 20% NEFE acid @ 12260'. Perforated Wolfcamp 10090-100' (40) and 10112-114' (12) - .42" holes.

RECOMPLETION UNSUCCESSFUL



I hereby certify that the information above is a true and complete to the best of my knowledge and belief.

SIGNATURE Stormi Davis TITLE Regulatory Compliance Technician DATE 2/3/04

Type or print name Stormi Davis Telephone No. 505-748-1471

(This space for State use)
APPROVED BY Gary W. Wink TITLE OC FIELD REPRESENTATIVE II/STAFF MANAGER DATE FEB 10 2004

Conditions of approval, if any: