

State of New Mexico
Energy, Minerals and Natural Resources

RECEIVED

JUL 26 2010

HOBBSOCD

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.

30-025-36501

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

VO-5304

7. Lease Name or Unit Agreement Name

East Sand Springs BGA State

8. Well Number

4

9. OGRID Number

025575

10. Pool name or Wildcat

Eight Mile Draw; Permo Upper Penn (Oil)

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other ☒ P&A

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 South Fourth Street, Artesia NM 88210

4. Well Location

Unit Letter G: 1850 feet from the North line and 1980 feet from the East lineSection 13 Township 11S Range 34E NMPM Lea County ☒

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

4151' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

7/11/10 MIRU. NU BOP. TOH w/rods & pump.

7/12/10 Set CIBP @ 10,200'. Tested casing to 1000 psi - held good. Put 35' cement on top of CIBP.

7/13/10 Circulated hole w/mud. Spotted 25 sx cement @ 7263'. TOC @ 7121'. Spotted 30 sx cement @ 4261'.

7/14/10 Tagged plug @ 4065'. Spotted 25 sx cement @ 2169'. TOC @ 1979'. Did not have to tag. (Maxey Brown w/NMOCD approved.) Circulated 75 sx cement from 470' to surface. Topped well off w/cement.

7/18/10 Cut off wellhead, installed dry hole marker & cleaned location. **WELL IS PLUGGED & ABANDONED.**Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 (Subsequent Report of Well Plugging)
which may be found at OCD Web Page under
Forms, www.emnrd.state.nm.us/oed.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Allison Barton TITLE Regulatory Compliance Technician DATE 7/20/10Type or print name Allison Barton E-mail address: abarton@yatespetroleum.com PHONE: (575) 748-1471

For State Use Only

APPROVED BY: [Signature] TITLE STAFF MGR DATE 7-26-10

Conditions of Approval (if any):

7/26