

District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-025-36422

5. Indicate Type of Lease
STATE ☐ FEE ☒
State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:
OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____
b. Type of Completion:
NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF.
WELL OVER BACK RESVR. ☐ OTHER

2. Name of Operator
Amerada Hess Corporation

3. Address of Operator
P.O. Box 840 Seminole, TX 79360

4. Well Location
Unit Letter **B** : **660** Feet From The **North** Line and **1980** Feet From The **East** Line

Section	20	Township	20S	Range	38E	NMPM	Lea	County
10. Date Spudded	11. Date T.D. Reached	12. Date Compl. (Ready to Prod.)	13. Elevations (DF& RKB, RT, GR, etc.)			14. Elev. Casinghead		
10/16/2003	10/17/2003	12/06/2003	3553'					

15. Total Depth	16. Plug Back T.D.	17. If Multiple Compl. How Many Zones?	18. Intervals Drilled By	Rotary Tools	Cable Tools
7136'					

19. Producing Interval(s), of this completion - Top, Bottom, Name
6520'-6686.3' Tubb, 6715'-6940' Drinkard

20. Was Directional Survey Made
Yes

21. Type Electric and Other Logs Run
CBL, Gamma Ray/CCL, Micro-CFL/Gamma Ray

22. Was Well Cored
No

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24#	1488'	11"	650 sx Class C	
5 1/2"	17#	7136'	7 7/8"	970 sx Class C/450 sx Class H	

24. LINER RECORD				25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET
					2 7/8"	6800'
						6472'

26. Perforation record (interval, size, and number)
Skaggs Drinkard (57000) 6715'-6719.2', 6771'-6773.9',
6839'-6842', 6857'-6860', 6871'-6874', 6888'-6892', 6911'-6920',
6933'-6940', Warren Tubb (87080) 6520'-6523.7', 6533'-6535.5',
6661'-6666.4', 6684'-6686.7'

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.
DEPTH INTERVAL AMOUNT AND KIND OF MATERIAL USED
6839'-6941' 2200 gals HCl/15% acid
6939'-6940' 63,500 gals Spec 35# XL Borate/140,000# 20/40 sand
6715'-6524' 4000 gals NEFE HCl/15% acid

28. PRODUCTION 6520'-6774' 115,000 gals Spec 35# XL Borate/250,000# 20/40 sand

Date First Production
12/6/2003

Production Method (Flowing, gas lift, pumping - Size and type pump)
Flowing

Well Status (Prod. or Shut in)
Producing

Date of Test	Hours Tested	Choke Size	Prod'n For Test Period	Oil - Bbl	Gas - MCF	Water - Bbl.	Gas - Oil Ratio
12/18/2003	24	21/64ths		181	234		1293

Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.)
300						

29. Disposition of Gas (Sold, used for fuel, vented, etc.)
Sold

Test Witnessed By

30. List Attachments
C-102, C-103, C-104, Deviation Survey, Logs Note: Refer to Administrative Order R11363-~~005~~ No. 0067

31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief

Signature *Carol J. Moore* Printed cmoore@hess.com
Name Carol J. Moore Title Senior Advisor Date 1/14/2003

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depth shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	1469	T. Canyon	
T. Salt	1568	T. Strawn	
B. Salt	2572	T. Atoka	
T. Yates	2727	T. Miss	
T. 7 Rivers		T. Devonian	
T. Queen		T. Silurian	
T. Grayburg	3712	T. Montoya	
T. San Andres	4046	T. Simpson	
T. Glorieta	5397	T. McKee	
T. Paddock	5544	T. Ellenburger	
T. Blinebry	5885	T. Gr. Wash	
T. Tubb	6388	T. Delaware Sand	
T. Drinkard	6692	T. Bone Springs	
T. Abo	7005	T.	
T. Wolfcamp		T.	
T. Penn		T.	
T. Cisco (Bough C)		T.	

Northwestern New Mexico

T. Ojo Alamo	T. Penn. "B"
T. Kirtland-Fruitland	T. Penn. "C"
T. Pictured Cliffs	T. Penn. "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
Base Greenhorn	T. Granite
T. Dakota	T. _____
T. Morrison	T. _____
T. Todilto	T. _____
T. Entrada	T. _____
T. Wingate	T. _____
T. Chinle	T. _____
T. Permian	T. _____
T. Penn "A"	T. _____

OIL OR GAS SANDS
OR ZONES

No. 1, from.....to.....

No. 2, from.....to.....

No. 3, from.....to.....

No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

From	To	Thickness In Feet	Lithology

Clear