Form 3160-5 (September 2001)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

OCHOBBAED

FORM APPROVED OMB NO 1004-0135 Expires January 31, 2004

5. Lease Serial No

Do not use this form for proposals to drill or to re-enter abl 2 3 2010 abandoned well. Use Form 3160-3 (APD) for such proposals.

LC~034667					
		Allottee or	Tribe Name		

		H()BB	SOCO				
SUBMIT IN TRIPLICATE - Other instructions on reverse side					7. If Unit or CA/Agreement, Name and/or No 8. Well Name and No. EL PASO TOM #006 FEDERAL 9. API Well No.		
1 Type of Well X Oil Well Gas Well Other 2. Name of Operator CIMAREX ENERGY CO. OF COLORADO ATIN: ZENO FARRIS							
3a. Address	3b. Phone No. (include a	rea code)	30-025-118	· •			
600 N. MARIENFELD, STE. 600, MIDLAN	(432) 571-7800)		Pool, or Exploratory A	rea		
4 Location of Well (Footage, Sec., T., R., M., or Survey Description)					NSILL-YATES-7-1	R) /	
UNIT LETTER J							
1,650' FSL & 1,650' FEL /				11. County or	Parish, State	/	
SEC. 33, T-25-S, R-37-E				LEA COUNTY	. NM		
12. CHECK APPROPRIATE	BOX(ES) TO IN	DICATE NATURE OF	NOTICE, REF	PORT, OR OTI	HER DATA		
TYPE OF SUBMISSION		TY	PE OF ACTION	l	***************************************		
X Notice of Intent	Acidize	Deepen	Production	n (Start/Resume)	Water Shut-Off		
	Alter Casing	Fracture Treat	Reclamat	ion	Well Integrity		
Subsequent Report	Casing Repair	New Construction	Recomple	ete	Other		
Final Abandonment Notice	Change Plans	X Plug and Abandon	Тетрога	aly Abandon			
]	Convert to Injecti	on Plug Back	Water Dis	sposal			

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)


PROPOSED PLUGGING PROCEDURE:

- 1) POOH W/ RODS X TUBING.
- 2) SET A 5-1/2" CIBP @ 2,500'; FUMP A 25 SX. OMT. PLUG ON TOP OF CIBP @ 2,500'-2,300' (B/SALT); WOC X TAG.
- 3) CIRC. WELL W/ PXA MUD; MIX X PUMP A 50 SX. OMT. PLUG @ 1,200'-860' (T/SALT, T/ANHY.,8-5/8" CSG.SHOE); WOC X TAG TOP OF OMT. PLUG.
- 4) MIX X CIRCULATE TO SURFACE A 40 SX. OMT. PLUG @ 300'-3'.
- 5) DIG OUT X OUT OFF WELLHEAD 3' B.G.L.; WELD ON STEEL PLATE TO CASINGS X INSTALL DRY HOLE MARKER.

RECLAMATION PROCEDURE ATTACHED

SEE ATTACHED FOR CONDITIONS OF APPROVAL

	•				
14 I hereby certify that the foregoing is true and correct Name (Printed/Typed)	Title				
BAYID A. EYLER	ACENT				
Dans VI.	Date 06/26/10 ADDDOVED				
THIS SPACE FOR FEDER	AL OR STATE OFFICE USE				
Approved by	Title Date				
Conditions of approval, if any, are attached. Approval of this notice the mot warran certify that the applicant holds degal or equitable title to those rights in the subject I which would entitle the applicant to conduct operations thereon.	nt or Office				
Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowing of the United States and States facilities as foundation as for any person within the invitation of CARLSBAD FIELD OFFICE.					



Cimarex Energy Company of Colorado NMLC-054667: El Paso Tom Federal #6

API: 30-025-11868

Lea County, New Mexico

RE: Plugging and Abandonment Requirements, Conditions of Approval

- 1. OK
- 2. Set the CIBP at 2470' with 35' Otherwise OK (Perfs Yates BOS)
- 3. OK (TOS Casing shoe)
- 4. OK (Surface)
- 5. Verify that all annuluses have cement to surface and fill in as required Otherwise OK.
- 6. Submit a subsequent report to the BLM.

H2S equipment should be on location.

Ground Level Dry Hole Marker to be used for this location – Requirements attached. REMINDER: Operator is to send both a before and AFTER diagram attached to ALL four copies with P&A sundries.

See attached standard COAs.

DHW 071910

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. In lieu of a cement plug in a cased hole, a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Any plug that requires a tag will have a minimum WOC time of 4 hours.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

- 6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). **The BLM is to be notified when the wellhead is cut off to verify that cement is to surface in the casing and all annuluses.** The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement. The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).
- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash</u>: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation procedure.

DHW 112309



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Interim Reclamation Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses.

Interim reclamation consists of minimizing the footprint of disturbance by reclaiming all portions of the well site not needed for production operations. The portions of the cleared well site not needed for operational and safety purposes are recontoured to a final or intermediate contour that blends with the surrounding topography as much as possible. Sufficient level area remains for setup of a workover rig and to park equipment. Topsoil is respread over areas not needed for all-weather operations. Production facilities should be clustered to maximize the opportunity for interim reclamation. In order to inspect and operate the well or complete workover operations, it may be necessary to drive, park, and operate on restored, interim vegetation within the previously disturbed area. This is generally acceptable provided damage is repaired and reclaimed following use.

To reduce final reclamation costs; maintain healthy, biologically active topsoil; and to minimize habitat, visual, and forage loss during the life of the well, all salvaged topsoil should be spread over the area of interim reclamation, rather than stockpiled.

- 1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). Interim reclamation is to be completed within 6 months of well completion.

- 3. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with interim reclamation as per approved APD or Sundry Notice. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.
- 4. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 5. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos

Supervisory Environmental Protection Specialist 575-234-5909, 575-361-2648 (Cell)

Terry Gregston

Environmental Protection Specialist 575-234-5958

Bobby Ballard

Environmental Protection Specialist 575-234-2230

Randy Rust

Environmental Protection Specialist 575-234-5943

Linda Denniston Environmental Protection Specialist

575-234-5974

Jennifer Van Curen Environmental Protection Specialist 575-234-5905

Justin Frye Environmental Protection Specialist 575-234-5922 Cody Layton

Natural Resource Specialist

575-234-5959

Trishia Bad Bear

Natural Resource Specialist

575-393-3612

Todd Suter

Surface Protection Specialist

575-234-5987

Doug Hoag

Civil Engineering Technician

575-234-5979