

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO. 30-025-36165
Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
State Oil & Gas Lease No. A-1320
Lease Name or Unit Agreement Name Rocky 16 State
Well No. 1
Pool name or Wildcat Townsend Morrow / Atoka

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	
Name of Operator Mewbourne Oil Company 14744	
Address of Operator PO Box 5270, Hobbs, N.M. 88241	
Well Location Unit Letter <u>M</u> <u>660</u> Feet From The <u>South</u> Line and <u>990</u> Feet From The <u>West</u> Line Section <u>16</u> Township <u>16S</u> Range <u>35E</u> NMPM <u>Lea</u> County	
Elevation (Show whether DF, RKB, RT, GR, etc.) 4017' GL	

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐


SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Spud & Csg ☒

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

03/12/03...MI & Spud 17 1/2" hole. TD @ 465'. Ran 465' 13 3/8" 48# H-40 ST&C csg. Cemented w/ 198 sks 'C' Lite w/ additives. Mixed @ 12.5 #/g & 1.98 yd. Tailed w/ 200 sks 'C' w/ additives. Mixed @ 14.8 #/g & 1.34 yd. Circl 10 sks to pit. WOC 18 hrs. Test BOPE to 800 psi. OK. Drill out w/ 12 1/4" bit.

03/24/03...TD'ed 12 1/4" hole @ 4322'. Ran 4322' 8 5/8" 32# J-55 ST&C csg. Cemented w/ 1600 sks 'C' Lite w/ additives. Mixed @ 12.5 #/g & 1.97 yd. Tailed w/ 200 sks 'C' w/ additives. Mixed @ 14.8 #/g & 1.34 yd. Circl 114 sks to pit. WOC 18 hrs. Test BOPE to 1500 psi. OK. Drill out w/ 7 7/8" bit.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE N.M. Young TITLE District Manager DATE 04-16-03
TYPE OR PRINT NAME N.M. Young TELEPHONE NO. 505-393-5905

(This space for State Use)

APPROVED BY Gary W. Wink TITLE OC FIELD REPRESENTATIVE II/STAFF MANAGER DATE APR 21 2003
CONDITIONS OF APPROVAL, IF ANY: