

Submit 3 Copies To Appropriate District
Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Avenue, Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-025-25500

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

H.T. Mattern NCT (C)

8. Well No.

11

9. Pool name or Wildcat

Wildcat Paddock

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Chevron USA Inc

3. Address of Operator

15 Smith Rd, Midland, TX, 79705

4. Well Location

Unit Letter M : 410 feet from the South line and 660 feet from the West line

Section 8 Township 21-S Range 37-E NMPM Lea County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐


CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

1. Notify OCD 24 hrs prior to MI and RU.
2. RIH set 5 1/2" CIBP at 5175, spot 25sx, plug 5175-5000 (Paddock) WOC Tag.
3. Displace hole w/MLF, 9.5# brine w/25# gel P/BBL.
4. Spot 40sx, plug 3600-3100 (Queen, DV-Tool).
5. Spot 30sx, plug 2700-2400 (B-Salt, Yates) WOC Tag.
6. Spot 30sx, plug 1400-1100 (8 5/8 Shoe, T-Salt) WOC Tag.
7. Spot 25sx, plug 250-Surf (Surf).
8. Install dry hole marker.

THE COMMISSION MUST BE NOTIFIED 24
HOURS PRIOR TO THE BEGINNING OF
PLUGGING OPERATIONS FOR THE C-103
TO BE APPROVED.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE D.R. Bledsoe TITLE HES Specialist DATE 2/3/2004

Type or print name G.R. Bledsoe

Telephone No. (432) 687-7153

(This space for State use)

APPROVED BY Larry W. Wink TITLE OCD FIELD REPRESENTATIVE II/STAFF MANAGER

Conditions of approval, if any: DATE FEB 12 2004

PLUGGING & ABANDONMENT WORKSHEET

(2 STRING CSNG)

OPERATOR CHEVRON USA INC.

LEASE NAME H.T. MATTEEN NCT (C)

WELL # 11

SECT 8 TWN 21-S RNG 37-E

FROM 410 N/S/L 660 E/W/L

TD 7125 FORMATION @ TD Drinkard

PBTD FORMATION @ PBTD Paddock

	SIZE	SET @	TOC	TOC DETERMINED BY
SURFACE	8 5/8	1312	SURF	Circ.
INTMED 1				
INTMED 2				
PROD	5 1/2	6800	SURF	Circ

	SIZE	TOP	BOT	TOC	DETERMINED BY
LINER 1					
LINER 2					

	CUT & PULL	TOP - BOTTOM
INTMED 1	PERFS	5228-5294
INTMED 2	OPENHOLE	
PROD		

*REQUIRED PLUGS DISTRICT

	PLUG	TYPE PLUG	SACKS CEMENT	DEPTH
RUSTLER (ANHYD)	1	CIBP	25	5175
YATES	2	QUEEN	40	3500
QUEEN	3	B-SALT	30	2700
GRAYBURG	4	8 5/8 S	30	1400
SAN ANDRES	5	SURF	25	250
CAPTAN REEF				
DELAWARE				
BELL CANYON				
CHERRY CANYON				
BRUSHY CANYON				
BONE SPRING				
GLORIETA				
BLINBRY				
TUBB				
DRINKARD				
ABO				
WC				
PENN				
STRAWN				
ATOKA				
MORROW				
MISS				
DEVONIAN				

CIBP @ 5500' w/ 35' CMT

CIBP @ 5175

BLINEBRY
5526-5815
SQZ'D

@ 6800

TOC SURF

Drinkard
6566-6738
SQZ'D

CIBP @ 6775
w/ 35' CMT
(ABO)

TD 7125

MLF

8 5/8

@ 1312

TOC SURF

MLF

MLF

AV-Tool

MLF