

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Avenue, Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.
30-025-34281

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Theodore Anderson

8. Well No.

14

9. Pool name or Wildcat
Monument, ABO, SE

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Chevron USA Inc

3. Address of Operator
15 Smith Rd, Midland, TX, 79705

4. Well Location

Unit Letter A : 660 feet from the North line and 810 feet from the East line

Section 17 Township 20-S Range 37-E NMPM Lea County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐


CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

1. Notify OCD 24 hrs prior to MI and RU.
2. Set 5 1/2" CIBP at 6975, spot 25sx, plug 6975-6800 (ABO) WOC Tag.
3. Displace hole w/MLF, 9.5# brine w/25# gel P/BBL. → 12.5#
4. Spot 25sx, plug 5100-4900 (Glorieta).
5. Spot 25sx, plug 3600-3400 (Queen).
6. Cut 5 1/2" csg at 2525, L/D csg.
7. Spot 95sx, plug 2575-2300 (8 5/8 Shoe, B-Salt, Stub) WOC Tag.
8. Spot 50sx, plug 1300-1100 (T-Salt) ~~3000-2800~~.
9. Spot 50sx, plug 450-250 (11 3/4 Shoe) WOC Tag.
10. 10sx Surface, install dry hole marker.

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF PLUGGING OPERATIONS FOR THE C-103 TO BE APPROVED.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE G.R. Bledsoe TITLE HES Specialist

DATE 2/3/2004

Type or print name G.R. Bledsoe

Telephone No. (432) 687-7153

(This space for State use)

APPROVED BY Harry W. Wink TITLE

Conditions of approval, if any

OC FIELD REPRESENTATIVE II/STAFF MANAGER
DATE

FEB 12 2004

PLUGGING & ABANDONMENT WORKSHEET

(3 STRING CSNG)

OPERATOR CHEVRON USA Inc.

LEASE NAME THEODORE ANDERSON

WELL # 14

SECT 17 TWN 20-S RNG 37-E

FROM 660 N S L 810 E W L

TD 7317 FORMATION @ TD ABO

PBTD FORMATION @ PBTD

	SIZE	SET @	TOC	TOC DETERMINED BY
SURFACE	11 3/4	395	SURF	Circ
INTMED 1	8 5/8	2475	SURF	Circ
INTMED 2				
PROD	5 1/2	7030	1600	CALC

	SIZE	TOP	BOT	TOC	DETERMINED BY
LINER 1					
LINER 2					

	CUT & PULL	TOP - BOTTOM
INTMED 1	PERFS	
INTMED 2	OPENHOLE	7030 - 7317
PROD	2525	

*REQUIRED PLUGS DISTRICT

	PLUG	TYPE PLUG	SACKS CEMENT	DEPTH
RUSTLER (ANHYD)	1	CIAP	25	6975
YATES	2	GLORIETA	25	5100
QUEEN	3	QUEEN	25	3600
GRAYBURG	4	8 5/8 SHOE	45	2575
SAN ANDRES	5	T-SALT	50	1300
	6	11 3/4 SHOE	50	450
CAPITAN REEF	7	SURF	10	10
DELAWARE				
BELL CANYON				
CHERRY CANYON				
BRUSHY CANYON				
BONE SPRING				
GLORIETA				
BLINBRY				
TUBB				
DRINKARD				
ABO				
WC				
PENN				
STRAWN				
ATOKA				
MORROW				
MISS				
DEVONIAN				

11 3/4
@ 395
TOC SURF

8 5/8
@ 2475
TOC SURF

5 1/2
@ 7030
TOC 1600

TD 7317