

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

OCD-HOBBS

FORM APPROVED  
OMB No 1004-0137  
Expires: March 31, 2007

## SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side.

1. Type of Well  
☒ Oil Well ☐ Gas Well ☐ Other2. Name of Operator  
ConocoPhillips Company3a. Address  
3300 N. "A" St., Bldg. 6 Midland TX 797053b. Phone No. (include area code)  
(432)688-68134. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
Sec. 33, T17S, R32E, Unit Letter "H"  
1830' FNL & 1310' FEL

5. Lease Serial No.

LC 059001

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

NM 70987 A

8. Well Name and No.

MCA Unit 470

9. API Well No.

30-025-39765

10. Field and Pool, or Exploratory Area

Maljamar, Grayburg-San Andres

11. County or Parish, State

Lea County

New Mexico

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other New TD
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	and casing info
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	


13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

The MCA 470 APD was approved on 6/9/2010. ConocoPhillips wishes to deepen the originally proposed TD from 4555' to 4650', which remains in the Grayburg-San Andres formation. Attached are the revised depths and casing information.

RECEIVED

AUG 23 2010

HOBBSOCD



14. I hereby certify that the foregoing is true and correct

Name (Printed/Typed)

Jalyn N. Fiske

Title Regulatory Specialist

Signature

Date 08/06/2010

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

REGULATORY ENGINEER

Title

Date

AUG 23 2010

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

MCA 470
---------

Formation Tops and Planned Total Depth	
Formation Call Points	Top (ft MD)
Rustler	1002
Salado	1216
Grayburg	3728
Grayburg - 6	3976
San Andres	4170
San Andres - 7	4170
San Andres - 9	4451
Total Depth (minimum)	4605
Total Depth (maximum)	4650

Casing Depths		
String	Minimum Depth	Maximum Depth
Surface Casing	1027	1072
Production Casing	4595	4640

Note: The Surface Casing and the Production Casing programs reflect an uncertainty of 45' in the setting depth for the shoe because that is the approximate length of a full joint of Range 3 casing. This range for the setting depth will allow us to drill the hole to fit the casing string based on how the tally comes out and will provide for the cementing head to be positioned at the rig floor for safety and efficiency in cementing operations. The casing will be set approximately 10 ft off bottom.