

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

Energy, Minerals and Natural Resources

October 13, 2009

RECEIVED

AUG 30 2010

HOBSOCD

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.

30-041-20941

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

WEST TODD STATE

8. Well Number

001

9. OGRID Number

1092

10. Pool name or Wildcat

Wildcat WOI-f camp

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Armstrong Energy Corporation

3. Address of Operator

P.O. Box 1973, Roswell, NM 88202-1973

4. Well Location

Unit Letter M : 660 feet from the SOUTH line and 660 feet from the WEST line

Section 20 Township 7S Range 35E NMPM Roosevelt County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK. ☐PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐CHANGE PLANS ☐PULL OR ALTER CASING ☐MULTIPLE COMPL ☐DOWNHOLE COMMINGLE ☐OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐P AND A ☐CASING/CEMENT JOB ☐OTHER: Long String Casing ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

08-11-10 Drilling 12-1/4" hole. TD @ 3890'. Cemented @ 3890', ran 3 jts, 126', 8-5/8" csg, 32#/ft, J-55, 8 RD, ST&C, Ran 55 jts, 2310', 8-5/8" csg, 24#/ft, J-55, 8 RD, ST&C. Ran 35 jts, 1470', 8-5/8" csg, 32#/ft, J-55, 8 RD, ST&C. Cemented w/ 20 BBLS FW ahead of cmt, 1505 sx Econocem-HLC, w/ 2% CaCl, 12.9 PPG, 1.77 cu ft/sx, 200 sx Halcem-C, 14.8 PPG, 1.33 cu ft/sx, circ 300 sx. 8-5/8" csg not centered, cut off 13-3/8" head, weld on 8-5/8" weld-on flange, NU on 8-5/8" csg.

Spud Date:

07/30/2010

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

VICE PRESIDENT

DATE 08/27/10

Type or print name

Bruce A. Stubbs

E-mail address:

bastubbs@armstrongenergycorp.com

PHONE:

(575) 625-2222

For State Use Only

APPROVED BY:

TITLE

PETROLEUM ENGINEER

DATE

AUG 30 2010

Conditions of Approval (if any):