Submit 1 Copy To Appropriate District Office State of New Mexico District I Energy, Minerals and Natural Resources	Form C-103 October 13, 2009	
District I Energy, Minerals and Natural Resources 1625 N. French Dr., Hobbs, NM SRECEIVED	WELL API NO.	
District II I I I I I I I I I I I I I I I I I	30-041-20941	
District III 1000 Rio Brazos Rd., Aztec, NM 87 SEP 0.3 2010 1220 South St. Francis Dr.	5. Indicate Type of Lease	
District IV Santa Fe, NM 87505	6. State Oil & Gas Lease No.	
1220 S. St Francis Dr., Santa Fe, 1948 BBSOCD		
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)	7. Lease Name or Unit Agreement Name WEST TODD STATE	
	8. Well Number	
2. Name of Operator	9. OGRID Number	
Armstrong Energy Corporation 3. Address of Operator	1092 V	
P.O. Box 1973, Roswell, NM 88202-1973	Wildcat Wolfcarp	
4. Well Location		
Unit Letter <u>M</u> : <u>660</u> feet from the <u>SOUTH</u> line and	660 feet from the WEST line	
Section 20 Township 7S Range 35E	NMPM Roosevelt County 🗸	
11. Elevation (Show whether DR, RKB, RT, GR, etc.		
12. Check Appropriate Box to Indicate Nature of Notice,	Report or Other Data	
NOTICE OF INTENTION TO: SUBSEQUEN	T REPORT OF:	
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK		
TEMPORARILY ABANDON 🔲 CHANGE PLANS 🔲 COMMENCE DRIL	— — —	
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT DOWNHOLE COMMINGLE	JOB 🗌	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertin	ent dates, including estimated date of starting any	
proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore		
08-30-10 TIH w/ open ended drill pipe, circ hole clean and condition mud.		
Spot 40 sx Class "H" cement 8390'-8290' on bottom		
Spot 40 sx Class "H" cement 7661'-7561'		
Spot 70 sx Class "H" cement 6933'-6833' Spot 45 sx Class "C" cement 4875'-4775'		
Spot 35 sx Class "C" cement 3926'-3826', 8-5/8" casing shoe.		
WOC, RIH and tagged cement plug @ 3800'.		
08-31-10 RD, 8 hrs plugging, 2 hrs ND wellhead, 4 hrs clean pits.		
Spot 35 sx Class "C" cement 2089'-1989'		
Spot 35 sx Class "C" cement 539'-439' Taggad @ 420' ND DOD and out off WHL Start 20 and Char "C"		
Tagged @ 420', ND BOP and cut off WH. Spot 20 sx Class "C" cement 60	-0', surface plug.	
Sand Data: 07/30/2010 Bis Balance Data: Ap	proved for plugging of well bore only.	
Spud Date: Rig Release Date: of	bility under bond is retained pending receipt 2-103 (Subsequent Report of Well Plugging)	
wh	leh may be found at OCD Web Page under may be found at OCD Web Page under may he found at a to the bage under may he was here to the bage at the bage	
I hereby certify that the information above is true and complete to the best of my knowledg		
2 statt		
SIGNATURE	DATE08/27/10	
Type or print name <u>Bruce A. Stubbs</u> E-mail address: <u>bastubbs@armstrongenerg</u>	gycorp.com PHONE: (575) 625-2222	
For State Use Only	RVISOF SEP 0 3 2010	
	DATEDATEDATEDATE	
Conditions of Approval (if any):		

	ł
7.00	