

October 13, 2009

District I

1625 N French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S St Francis Dr., Santa Fe, NM 87505

RECEIVED

SEP 07 2010

CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.

30-041-20941

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

WEST TODD STATE

8. Well Number

001

9. OGRID Number

1092

10. Pool name or Wildcat

Wildcat *Wolfcamp*

SUNDRY HOBBIES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Armstrong Energy Corporation

3. Address of Operator

P.O. Box 1973, Roswell, NM 88202-1973

4. Well Location

Unit Letter M : 660 feet from the SOUTH line and 660 feet from the WEST lineSection 20 Township 7S Range 35E NMPM Roosevelt County ☒

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐CHANGE PLANS ☐PULL OR ALTER CASING ☐MULTIPLE COMPL ☐DOWNHOLE COMMINGLE ☐OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐P AND A ☒CASING/CEMENT JOB ☐OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

08-30-10 TIH w/ open ended drill pipe, circ hole clean and condition mud.

Spot 40 sx Class "H" cement 8390'-8290' on bottom

Spot 40 sx Class "H" cement 7661'-7561'

Spot 70 sx Class "H" cement 6933'-6833'

Spot 45 sx Class "C" cement 4875'-4775'

Spot 35 sx Class "C" cement 3926'-3826', 8-5/8" casing shoe.

WOC, RIH and tagged cement plug @ 3800'.

08-31-10 RD, 8 hrs plugging, 2 hrs ND wellhead, 4 hrs clean pits.

Spot 35 sx Class "C" cement 2089'-1989'

Spot 35 sx Class "C" cement 539'-439'

Tagged @ 420', ND BOP and cut off WH. Spot 20 sx Class "C" cement 60'-0', surface plug.

Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 (Subsequent Report of Well Plugging)
which may be found at OCD Web Page under
Forms, www.enmr.state.nm.us/oed.

Spud Date:

07/30/2010

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

B. Stubbs

TITLE

VICE PRESIDENT

DATE 09/02/10

Type or print name

Bruce A. Stubbs

E-mail address:

bastubbs@armstrongenergycorp.com

PHONE: (575) 625-2222

For State Use Only

APPROVED BY:

E. Gonzalez

TITLE

STAFF MGR

DATE

9-7-10

Conditions of Approval (if any):



500 North Main Street, Suite 200
P.O. Box 1973
Roswell, New Mexico 88202-1973
(575) 625-2222
Fax (575) 622-2512

September 3, 2010

RECEIVED

SEP 07 2010

HOBBSOCD

Oil Conservation Division
1625 N. French Drive
Hobbs, New Mexico 88240

Re: West Todd State #1
Township 7 South, Range 35 East, NMPM
Section 20
Roosevelt County, New Mexico

Dear Sir/Madam:

Enclosed is a corrected Sundry Notices and Reports on Wells, Plug and Abandon, for the captioned well to be filed with your office. The correction made was the signature date.

If you have any questions, please contact Bruce Stubbs at 505-625-2222.

Sincerely,

ARMSTRONG ENERGY CORPORATION

By: 
Irma Cunningham, Geo Tech

Enclosures